

High efficiency, single-digit numeric displays


LA-401DN Series

The LA-401DN series were designed to meet the need for small single-digit numeric displays. These LED numeric displays use GaAsP on GaP for the emitting material (with the exception of green) and are housed in an epoxy resin package. They are single-digit displays with a character height of 10.16 mm.

●Features

- 1) Height of character: 10.16 mm
- 2) Common anode and common cathode configurations are available for each color.
- 3) Each segment has independent pin connections and static drive is possible.
- 4) High-efficiency reflectors are used to achieve a bright, clear display.
- 5) The package surface is painted black and the segments are colored the display color.

●External Dimensions (Units: mm)



●Selection guide

Emitting color \ Common	Red	Orange	Green
Anode	LA-401VD	LA-401DD *	LA-401MD
Cathode	LA-401VN	LA-401DN *	LA-401MN

* Order-based production.


●Pin assignments

Pin No.	Pin No.	Function
1 +	10 +	Common
2 +	2 +	Segment "f"
3 +	3 +	Segment "g"
4 +	4 +	Segment "e"
5 +	5 +	Segment "d"
	6	Common
	7	D.P.
	8	Segment "c"
	9	Segment "b"
	10	Segment "a"

LA-401DN Series

LED displays

● Internal circuit schematic (example of common anode)



● Absolute maximum ratings ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Red		Orange		Green		Unit
		LA-401VD / VN	LA-401DD / DN	LA-401MD / MN	LA-401MD / MN	LA-401MD / MN	LA-401MD / MN	
Power dissipation	P_D	320		320		480		mW
Power dissipation	P_D / seg	40		40		60		mW
Forward current	I_F	15		15		20		mA
Peak forward current	I_{FP}	60*		60*		60*		mA
Reverse voltage	V_R	3		3		3		V
Operating temperature	T_{opr}	-25~+75				$^{\circ}\text{C}$		
Storage temperature	T_{stg}	-30~+85				$^{\circ}\text{C}$		

* Pulse width 1ms duty 1 / 5

● Electrical and optical characteristics ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Conditions	Red			Orange			Green			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
Forward voltage	V_F	$I_F=10\text{mA}$	—	2.0	2.8	—	2.0	2.8	—	2.1	2.8	V
Reverse current	I_R	$V_R=3\text{V}$	—	—	100	—	—	100	—	—	100	μA
Peak wavelength	λ_P	$I_F=10\text{mA}$	—	650	—	—	610	—	—	563	—	nm
Spectral line half width	$\Delta\lambda$	$I_F=10\text{mA}$	—	40	—	—	40	—	—	40	—	nm

◎ Not designed for radiation resistance.

● Luminous intensity

Color	λ_P	Type	Min.	Typ.	Max.	Unit
Red	650	LA-401VD	5.6	16	—	mcd
		LA-401VN				
Orange	610	LA-401DD	3.6	10	—	mcd
		LA-401DN				
Green	563	LA-401MD	5.6	16	—	mcd
		LA-401MN				

Note : Measured at $I_F=10\text{mA}$