



Rated voltage (Vdc)	9 ± 0.5
Operating temperature range (°C) [°F]	0 to 60 [32 to 140]
Storage temperature range (°C) [°F]	- 20 to + 70 [- 4 to + 158]

Output	Item	[MHz]	min.	typ.	max.
Y-OUT	Output level (dB)	0.100000	− 0.7	− 0.2	+ 0.3
		3.571678	− 1.5	− 0.5	+ 0.5
		4.500000	− 1.5	− 0.5	+ 0.5
	Comb attenuation (dB)	3.0760485	13	18	
		3.579545	26	40	
		4.0830415	14	18	
	2T pulse response (%)			1.5	2.5
	Spurious noise (dB)		− 30	− 38	
	Input/output direct voltage deviation (V)		− 0.5	0	+ 0.5
C-OUT	Output level (dB)	3.579545	− 0.5	− 0.5	+ 0.5
	Comb attenuation (dB)	3.571678	− 20	− 35	
	Consumption currents (mA)				40

Output	Item	[MHz]	min.	typ.	max.
Y-OUT	Output level (dB)	0.100000	− 0.7	− 0.2	+ 0.3
		3.571678	− 1.7	− 0.2	+ 1.3
		4.500000	− 3	+ 1	—
	Comb attenuation (dB)	3.0760485	7	10	
		3.579545	26	40	
		4.0830415	11	15	
	2T pulse response (%)			1.5	3
	Spurious noise (dB)		− 30	− 38	
Input/output direct voltage deviation (V)		− 0.5	0	+ 0.5	
C-OUT	Output level (dB)	3.579545	− 1.5	0	+ 1.5
	Comb attenuation (dB)	3.571678	− 1.5	− 30	
	Consumption currents (mA)				65

CATALOG NO. BCE-076