

Video amplifier

NE592

DESCRIPTION

The NE592 is a monolithic, two-stage, differential output, wideband video amplifier. It offers fixed gains of 100 and 400 without external components and adjustable gains from 400 to 0 with one external resistor. The input stage has been designed so that with the addition of a few external reactive elements between the gain select terminals, the circuit can function as a high-pass, low-pass, or band-pass filter. This feature makes the circuit ideal for use as a video or pulse amplifier in communications, magnetic memories, display, video recorder systems, and floppy disk head amplifiers. Now available in an 8-pin version with fixed gain of 400 without external components and adjustable gain from 400 to 0 with one external resistor.


FEATURES

- 120MHz unity gain bandwidth
- Adjustable gains from 0 to 400
- Adjustable pass band
- No frequency compensation required
- Wave shaping with minimal external components
- MIL-STD processing available


APPLICATIONS

- Floppy disk head amplifier
- Video amplifier
- Pulse amplifier in communications
- Magnetic memory
- Video recorder systems

PIN CONFIGURATIONS



BLOCK DIAGRAM



Video amplifier

NE592

ORDERING INFORMATION

| DESCRIPTION | TEMPERATURE RANGE | ORDER CODE | DWG # |
|--------------------|-------------------|------------|-------|
| 14-Pin Plastic DIP | 0 to +70°C | NE592N14 | 0405 |
| 14-Pin Cerdip | 0 to +70°C | NE592F14 | 0581 |
| 14-Pin SO | 0 to +70°C | NE592D14 | 0175 |
| 8-Pin Plastic DIP | 0 to +70°C | NE592N8 | 0404 |
| 8-Pin SO | 0 to +70°C | NE592D8 | 0174 |

NOTES:

N8, N14, D8 and D14 package parts also available in "High" gain version by adding "H" before package designation, i.e., NE592HDB

ABSOLUTE MAXIMUM RATINGS

$T_A = +25^\circ\text{C}$, unless otherwise specified.

| SYMBOL | PARAMETER | RATING | UNIT |
|--------------|---|-------------|------|
| V_{CC} | Supply voltage | ± 8 | V |
| V_{IN} | Differential input voltage | ± 5 | V |
| V_{CM} | Common-mode input voltage | ± 6 | V |
| I_{OUT} | Output current | 10 | mA |
| T_A | Operating ambient temperature range | 0 to +70 | °C |
| T_{STG} | Storage temperature range | -65 to +150 | °C |
| $P_{D\ MAX}$ | Maximum power dissipation, $T_A = 25^\circ\text{C}$ (still air) ¹ | | |
| | F-14 package | 1.17 | W |
| | D-14 package | 0.98 | W |
| | D-8 package | 0.79 | W |
| | N-14 package | 1.44 | W |
| | N-8 package | 1.17 | W |

NOTES:

- Derate above 25°C at the following rates:
 F-14 package at 9.3mW/°C
 D-14 package at 7.8mW/°C
 D-8 package at 6.3mW/°C
 N-14 package at 11.5mW/°C
 N-8 package at 9.3mW/°C

Video amplifier

NE592

DC ELECTRICAL CHARACTERISTICS

$T_A=+25^\circ\text{C}$, $V_{SS}=+6\text{V}$, $V_{CM}=0$, unless otherwise specified. Recommended operating supply voltages $V_S=+6.0\text{V}$. All specifications apply to both standard and high gain parts unless noted differently.

| SYMBOL | PARAMETER | TEST CONDITIONS | NE/SA592 | | | UNIT |
|-------------|---|---|-----------|------|------|---------------------|
| | | | Min | Typ | Max | |
| A_{VOL} | Differential voltage gain, standard part | $R_L=2\text{k}\Omega$, $V_{OUT}=3\text{V}_{p-p}$ | | | | |
| | Gain 1 ¹ | | 250 | 400 | 600 | V/V |
| | Gain 2 ^{2,4} | | 80 | 100 | 120 | V/V |
| | High gain part | | 400 | 500 | 600 | V/V |
| R_{IN} | Input resistance | | | | | |
| | Gain 1 ¹ | | | 4.0 | | k Ω |
| | Gain 2 ^{2,4} | | 10 | 30 | | k Ω |
| C_{IN} | Input capacitance ² | Gain 2 ⁴ | | 2.0 | | pF |
| I_{OS} | Input offset current | | | 0.4 | 5.0 | μA |
| I_{BIAS} | Input bias current | | | 9.0 | 30 | μA |
| V_{NOISE} | Input noise voltage | BW 1kHz to 10MHz | | 12 | | μV_{RMS} |
| V_{IN} | Input voltage range | | ± 1.0 | | | V |
| CMRR | Common-mode rejection ratio | | | | | |
| | Gain 2 ⁴ | $V_{CM}\pm 1\text{V}$, $f<100\text{kHz}$ | 60 | 86 | | dB |
| | Gain 2 ⁴ | $V_{CM}\pm 1\text{V}$, $f=5\text{MHz}$ | | 60 | | dB |
| PSRR | Supply voltage rejection ratio | | | | | |
| | Gain 2 ⁴ | $\Delta V_S=\pm 0.5\text{V}$ | 50 | 70 | | dB |
| V_{OS} | Output offset voltage | | | | | |
| | Gain 1 | $R_L=\infty$ | | | 1.5 | V |
| | Gain 2 ⁴ | $R_L=\infty$ | | | 1.5 | V |
| | Gain 3 ³ | $R_L=\infty$ | | 0.35 | 0.75 | V |
| V_{CM} | Output common-mode voltage | $R_L=\infty$ | 2.4 | 2.9 | 3.4 | V |
| V_{OUT} | Output voltage swing differential | $R_L=2\text{k}\Omega$ | 3.0 | 4.0 | | V |
| R_{OUT} | Output resistance | | | 20 | | Ω |
| I_{CC} | Power supply current | $R_L=\infty$ | | 18 | 24 | mA |

NOTES:

- Gain select Pins G_{1A} and G_{1B} connected together.
- Gain select Pins G_{2A} and G_{2B} connected together.
- All gain select pins open.
- Applies to 14-pin version only.

Video amplifier

NE592

DC ELECTRICAL CHARACTERISTICS

DC Electrical Characteristics $V_{SS}=\pm 6V$, $V_{CM}=0$, $0^{\circ}C \leq T_A \leq 70^{\circ}C$, unless otherwise specified. Recommended operating supply voltages $V_S=\pm 6.0V$. All specifications apply to both standard and high gain parts unless noted differently.

| SYMBOL | PARAMETER | TEST CONDITIONS | NE/SA592 | | | UNIT |
|------------|---|-------------------------------------|-----------|-----|-----|------------|
| | | | Min | Typ | Max | |
| A_{VOL} | Differential voltage gain, standard part | $R_L=2k\Omega$, $V_{OUT}=3V_{P.P}$ | | | | |
| | Gain 1 ¹ | | 250 | | 600 | V/V |
| | Gain 2 ^{2,4} | | 80 | | 120 | V/V |
| | High gain part | | 400 | 500 | 600 | V/V |
| R_{IN} | Input resistance Gain 2 ^{2,4} | | 8.0 | | | k Ω |
| I_{OS} | Input offset current | | | | 6.0 | μA |
| I_{BIAS} | Input bias current | | | | 40 | μA |
| V_{IN} | Input voltage range | | ± 1.0 | | | V |
| CMRR | Common-mode rejection ratio Gain 2 ⁴ | $V_{CM}\pm 1V$, $f<100kHz$ | 50 | | | dB |
| PSRR | Supply voltage rejection ratio Gain 2 ⁴ | $\Delta V_S=\pm 0.5V$ | 50 | | | dB |
| V_{OS} | Output offset voltage Gain 1 Gain 2 ⁴ Gain 3 ³ | $R_L=\infty$ | | | 1.5 | V |
| | | | | | 1.5 | |
| | | | | | 1.0 | |
| V_{OUT} | Output voltage swing differential | $R_L=2k\Omega$ | 2.8 | | | V |
| I_{CC} | Power supply current | $R_L=\infty$ | | | 27 | mA |

NOTES:

- Gain select Pins G_{1A} and G_{1B} connected together.
- Gain select Pins G_{2A} and G_{2B} connected together.
- All gain select pins open.
- Applies to 10- and 14-pin versions only.

AC ELECTRICAL CHARACTERISTICS

$T_A=+25^{\circ}C$ $V_{SS}=\pm 6V$, $V_{CM}=0$, unless otherwise specified. Recommended operating supply voltages $V_S=\pm 6.0V$. All specifications apply to both standard and high gain parts unless noted differently.

| SYMBOL | PARAMETER | TEST CONDITIONS | NE/SA592 | | | UNIT |
|----------|---|--------------------|----------|------|-----|------------|
| | | | Min | Typ | Max | |
| BW | Bandwidth Gain 1 ¹ Gain 2 ^{2,4} | | | 40 | | MHz MHz |
| | | | | 90 | | |
| t_R | Rise time Gain 1 ¹ Gain 2 ^{2,4} | $V_{OUT}=1V_{P.P}$ | | 10.5 | 12 | ns ns |
| | | | | 4.5 | | |
| t_{PD} | Propagation delay Gain 1 ¹ Gain 2 ^{2,4} | $V_{OUT}=1V_{P.P}$ | | 7.5 | 10 | ns ns |
| | | | | 6.0 | | |


NOTES:

- Gain select Pins G_{1A} and G_{1B} connected together.
- Gain select Pins G_{2A} and G_{2B} connected together.
- All gain select pins open.
- Applies to 10- and 14-pin versions only.

Video amplifier

NE592










TYPICAL PERFORMANCE CHARACTERISTICS



Video amplifier


NE592

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)




Video amplifier

NE592



TEST CIRCUITS $T_A = 25^\circ C$, unless otherwise specified.



Video amplifier

NE592

TYPICAL APPLICATIONS

NOTE:

$$\frac{V_0(s)}{v_1(s)} = \frac{1.4 \cdot 10^4}{Z(s) + 2r_e}$$

$$= \frac{1.4 \cdot 10^4}{Z(s) + 32}$$

Basic Configuration

Differentiation with High Common-Mode Noise Rejection

NOTE:
For frequency $F_1 \ll 1/2 \pi (32) C$

$$V_0 = 1.4 \times 10^4 C \frac{dV_1}{dt}$$

Disc/Tape Phase-Modulated Readback Systems

FILTER NETWORKS

| Z NETWORK | FILTER TYPE | $V_0(s)$ TRANSFER $V_1(s)$ FUNCTION |
|-----------|-------------|---|
| | LOW PASS | $\frac{1.4 \times 10^4}{L} \left[\frac{1}{s + R/L} \right]$ |
| | HIGH PASS | $\frac{1.4 \times 10^4}{R} \left[\frac{s}{s + 1/RC} \right]$ |
| | BAND PASS | $\frac{1.4 \times 10^4}{L} \left[\frac{s}{s^2 + R/Ls + 1/LC} \right]$ |
| | BAND REJECT | $\frac{1.4 \times 10^4}{R} \left[\frac{s^2 + 1/LC}{s^2 + 1/LC + s/RC} \right]$ |

NOTES:
 In the networks above, the R value used is assumed to include $2r_e$, or approximately 32Ω .
 $S = j\omega$
 $\omega = 2\pi f$

Signetics

Packaging Information

T.90-20

Military Products

SIGNETICS STANDARD PACKAGE DESCRIPTIONS

All Military package case outlines and physical dimensions conform with the current revision MIL-M-38510, Appendix C, except for package types which are not included in that specification.

The physical dimensions for standard package types which are not included in Appendix C are included herein in Appendix C format. Case outline letters are assigned to these packages according to JEDEC Publication 101 as follows:

- U: Leadless chip carriers
- X: Dual-in-line packages
- Y: Flat packages
- Z: All other configurations

A case outline suffix number is assigned herein for identification purposes only, and is not marked on the product.

Signetics Military products are offered in a wide range of package configurations to optimally fit our customer needs.

- Dual-In-line Packages; Frit glass sealed CERDIP (F package family) with 8-40 leads, and side-brazed ceramic (I package family) with 48-64 leads.
- Flat Packages; Frit glass sealed alumina CERPAC (W package family) with 14-28 leads, and brazed leaded ceramic (Q package family) with 52 leads.

- Ceramic Chip Carriers; triple laminated, metal-lidded LCC (G package family) with 20-68 terminals.
- Pin Grid Array; metal-lidded ceramic pin grid (P package family) with 68-100 leads.
- Shown in Table 1 are the case outline letters assigned according to Appendix C of MIL-M-38510 and JEDEC publication 101. Unless otherwise noted, all package types are Configuration 1 and all lead finishes are hot solder dip Finish "A".

Table 1.

| Package Description | Type Designation | Case Outline | Theta-JC °C/Watt ⁴ |
|---------------------|-------------------|----------------|-------------------------------|
| 8DIP3 | D-4 | P | 28 |
| 14DIP3 | D-1 | C | 28 |
| 16DIP3 | D-2 | E | 28 |
| 18DIP3 | D-6 | V | 28 |
| 20DIP3 | D-8 | R | 28 |
| 22DIP4 | D-7 | W | 28 |
| 24DIP3 | D-9 | L | 28 |
| 24DIP4 | D-11 | X ² | 28 |
| 24DIP6 | D-3 | J | 28 |
| 28DIP6 | D-10 | X ² | 28 |
| 40DIP6 | D-5 | Q | 28 |
| 48DIP6 | D-14 ¹ | X ² | 28 |
| 50DIP9 | D-12 ¹ | X ² | 28 |
| 64DIP9 | D-13 ¹ | X ² | 28 |
| 14FLAT | F-2 | D | 22 |
| 16FLAT | F-5 | F | 22 |
| 18FLAT | F-10 | Y ² | 22 |
| 20FLAT | F-9 | S | 22 |
| 24FLAT | F-6 | K | 22 |
| 28FLAT | F-11 | Y ² | 22 |
| 52FLAT | Y-1 ¹ | Y ² | 22 |
| 18LLCC | C-9 | U ² | 20 |
| 20LLCC | C-2 ³ | 2 | 20 |
| 28LLCC | C-4 ³ | 3 | 20 |
| 32LLCC | C-12 | U ² | 20 |
| 44LLCC | C-5 | U ² | 20 |
| 68LLCC | C-7 | U ² | 20 |
| 68PGA | P-AB | Z ² | 20 |
| 84PGA | P-AB | Z ² | 20 |


NOTES:

1. Configuration 2.
2. Per JEDEC publication 101.
3. Dimension A (LLCC thickness) is 75mils maximum.
4. See RADC test report RADC-TR-86-97 for thermal resistance confidence and derating.

Packaging Information

T-90-20

CASE OUTLINES Y (FLAT PACKAGES)



NOTES:


1. A lead tab (enlargement) or index dot is located within the shaded area shown at Pin 1. Other pin numbers proceed sequentially from Pin 1 counterclockwise (as viewed from the top of the device).
2. This dimension allows for off-center lid, meniscus, and glass overrun.
3. The reference pin spacing is 0.050 between centerlines. Each pin centerline is located within ± 0.005 of its longitudinal position relative to the first and last pin numbers.
4. This dimension is measured at the point of exit of the lead body.
5. This dimension applied to all four corner pins.
6. Lead dimensions include 0.003 inch allowance for hot solder dip lead finish.

| OUTLINE | Y1 | | NOTES |
|---------------|-----------|--------|-------|
| CONFIGURATION | 2 | | |
| NO. LEADS | 52 | | |
| SIG. PKG. | QP | | |
| SYMBOL | INCHES | | |
| | Min | Max | |
| A | 0.045 | 0.100 | |
| b | 0.015 | 0.026 | 6 |
| c | 0.008 | 0.015 | 6 |
| D | - | 1.330 | 2 |
| E | 0.620 | 0.660 | |
| e | 0.050 BSC | | 3 |
| L | 0.250 | 0.370 | |
| Q | 0.054 | 0.0666 | 4 |
| S | - | 0.045 | 5 |
| S1 | 0.005 | - | 5 |

T-90-20

Packaging Information

CASE OUTLINES X (DUAL IN-LINE PACKAGES)




1. An index notch is located within the shaded area shown. Pin 1 is adjacent to the notch to the immediate left (as viewed from the top of the device) and other pin numbers proceed sequentially from Pin 1 counterclockwise.
2. The minimum limit for Dimension b1 is 0.023 inches for all four corner pins.
3. This dimension allows for off-center lid, meniscus, and glass overrun.
4. This dimension is measured at the centerline of the leads for Configuration 2.
5. The reference pin spacing is 0.100 between centerlines. Each pin centerline is located within ± 0.010 of its longitudinal position relative to the first and last pin numbers.
6. This dimension is measured from the seating plane to the base plane.
7. This dimension applies to all four corner pins.
8. Lead dimensions include 0.003 inch allowance for hot solder dip lead finish.


Packaging Information

T-90-20


LEADLESS CHIP CARRIER (LLCC) PINOUTS




24-Lead Logic Pinout for 28 Terminal Chip Carrier



28-Lead Pinout for 28 Terminal Chip Carrier for all Device Types



24-Lead Memory Pinout for 28 Terminal Chip Carrier



22-Lead Memory Pinout for 28 Terminal Chip Carrier

□ = Chip Carrier Terminal Number
 ○ = Dual In-Line Lead Number
 NC = No Connect