

GENERAL DESCRIPTION

The DAC1252X_JVC is a CMOS 8BIT D/A converter for general application. This digital to analog converter has a R2R structure.


Its settling time is 500ns (Typical value).

TYPICAL APPLICATIONS

- Hard Disk Drive (HDD)
- Battery Operated Instruments
- Motor Control Systems
- General Applications

FEATURES

- **Resolution : 8BIT**
- **Differential Linearity Error : ± 1.0 LSB**
- **Integral Linearity Error : ± 1.0 LSB**
- **Settling Time : 500ns**
- **Low Power Consumption : 890uA**
- **Power Down Mode**
- **Operation Temperature Range : $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$**
- **Power Supply : 2.5V Single and 1.8V single**

FUNCTIONAL BLOCK DIAGRAM**Ver 1.0 (June 2000)**

This datasheet is a preliminary version. No responsibility is assumed by SEC for its use nor for any infringements of patents or other rights of third parties that may result from its use. The content of this datasheet is subject to change without any notice.


CORE PIN DESCRIPTION

NAME	I/O TYPE	I/O PAD	PIN DESCRIPTION
D[7:0]	DI	picc_abb	Digital Input Data (8BIT) D[7] : MSB , D[0] : LSB
PD	DI	picc_abb	Power Down (Active Low)
VRT	AB	pia_abb	Voltage Reference Top
VRB	AB	pia_abb	Voltage Reference Bottom
VOUT	AO	poa_abb	Analog Voltage Output
AVDD25A	AP	vdd2t_abb	Analog Power (+2.5V)
AVSS25A	AG	vdd2t_abb	Analog Ground (0.0V)
AVDD25D	DP	vdd2t_abb	Digital Power (+2.5V)
AVSS25D	DG	vss2t_abb	Digital Ground (0.0V)
AVDD18D	DP	vss1t_abb	Digital power (+1.8V)
AVBB25A	AG	vbb_abb	Analog Sub Bias (0.0V)

I/O TYPE ABBR.

- AI : Analog Input
- DI : Digital Input
- AO : Analog Output
- DO : Digital Output
- AB : Analog Bidirectional
- DB : Digital Bidirectional
- AP : Analog Power
- DP : Digital Power
- AG : Analog Ground
- DG : Digital Ground

CORE CONFIGURATION



ABSOLUTE MAXIMUM RATINGS

Characteristics	Symbol	Value	Unit
Supply Voltage	VDD (AVDD25A,AVDD25D)	3.3	V
Analog Output Voltage	VOUT	AVSS25A to AVDD25A	V
Digital Input Voltage	D[7:0]	VSS25D to AVDD18D	V
Reference Voltage	VRT VRB	AVDD25A AVSS25A	V
Operating Temperature Range	Topr	0 to 70	°C

NOTES :

1. ABSOLUTE MAXIMUM RATING specifies the values beyond which the device may be damaged permanently.
Exposure to ABSOLUTE MAXIMUM RATING conditions for extended periods may affect reliability. Each condition value is applied with the other values kept within the following operating conditions and function operation under any of these conditions is not implied.
2. All voltages are measured with respect to VSS(AVSS25A or VSS25AD0 or AVBB25A) unless otherwise specified.
3. 100pF capacitor is discharged through a 1.5kΩ resistor (Human body model)

RECOMMENDED OPERATING CONDITIONS

Characteristics	Symbol	Min	Typ	Max	Unit
Supply Voltage	AVDD25A - AVSS25A AVDD25D - VSS25AD0	2.375	2.5	2.625	V
Supply Voltage Difference	AVDD25A - AVDD25D	-0.1	0.0	0.1	V
Reference Voltage	VRT VRB	- 0.0	- -	2.5 -	V
Digital Input 'Low' Voltage	VIL	-	-	0.3×AVDD18D	V
Digital Input 'High' Voltage	VIH	0.7×AVDD18D	-	-	
Operating Temperature	Topr	0	-	70	°C

NOTE :

It is strongly recommended that to avoid power latch-up all the supply pins(AVDD25A,AVDD25D) be driven from the same source.

DC ELECTRICAL CHARACTERISTICS

(Converter Specifications : AVDD25A=AVDD25D=2.5V, AVSS25A=VSS25AD0=AVBB25A=0V,
PD=High, Top=25°C, VRT=2.5V, VRB=0.0V unless otherwise specified.)

Characteristics	Symbol	Min	Typ	Max	Unit	Conditions
Resolution	Bit	-	8	-	Bits	-
Differential Linearity Error	DLE	-	1.0	-	LSB	-
Integral Linearity Error	ILE	-	1.0	-	LSB	-
Zero Scale Error ¹	V _{ZSE}	-	5	-	mV	VRT=2.5V , VRB=0.0V
Full Scale Voltage Error ²	V _{FSE}	-	5	-	mV	
Maximum Output Voltage	V _{O_MAX}	-	2.499	-	V	V _{O_MAX} = VOUT(D[7:0]=High)
LSB Size	V _{LSB}	-	0.61	-	mV	V _{LSB} = V _{O_MAX} / 256

NOTE 1 : V_{ZSE}=VOUT(D[7:0]=Low) - VRB


2 : V_{FSE}=VOUT(D[7:0]=High) - {(VRT-VRB) × 255/256 + VRB}

AC ELECTRICAL CHARACTERISTICS

(Converter Specifications : AVDD25A=AVDD25D=2.5V, AVSS25A=VSS25AD0=AVBB25A=0V, load cap=25pF
Top=25°C, PD=High, VRT=2.45V, VRB=0.05V unless otherwise specified.)

Characteristics	Symbol	Min	Typ	Max	Unit	Conditions
Supply Current	Ivdd1	-	0.89	-	mA	Ivdd1 = I _{VDD28AA0} + I _{AVDD25D} VRT=2.5V , VRB = 0.0V Data Input : All Low or All High
	Ivdd2	-	1.22	-	mA	Ivdd2 = I _{AVDD25A} + I _{AVDD25D} Data Input : All Low or All High
Supply Current (Power Down Mode)	Ivdd3	-	-	10	uA	Ivdd3 = I _{AVDD25A} + I _{AVDD25D} Data Rate = 2MHz Load cap = 25pF , PWDN=LOW
Short Circuit Current	I _{SC}	-	12	-	mA	VOUT : AVSS25A or AVDD25A Data Input : All High or All Low
Analog Output Delay	T _d	-	65	-	ns	Data Rate = 2MHz Data : All LOW → All HIGH
Analog Output Rise Time	T _r	-	100	-	ns	Data Rate = 2MHz Data : All LOW → All HIGH
Analog Output Fall Time	T _f	-	100	-	ns	Data Rate = 2MHz Data : All HIGH → All LOW
Analog Output Settling Time	T _s	-	500	-	ns	Data Rate = 2MHz Data : All LOW → All HIGH
Power Down Off Time	T _{on}	-	500	-	ns	PD : HIGH → LOW
Power Down On Time	T _{off}	-	500	-	ns	PD : LOW → HIGH

TIMING DIAGRAM



1. Output delay measured from the 50% point of the rising edge of input data to the full scale transition.
2. Settling time measured from the 50% point of full scale transition to the output remaining within $\pm 1/2$ LSB.
3. Output rise/fall time measured between the 10% and 90% points of full scale transition.

FUNCTIONAL DESCRIPTION


1. The DAC1252X_JVC has a 8BIT R-2R block, two decoders, two OP amps, and control block.
2. The digital outputs of two decoders decide the voltage level of R2R block.

$$V_{Rstring} = \frac{V_{RT} - V_{RB}}{2^8} \sum_{n=0}^8 (2^n * D_n)$$

3. Normal Conditions : $V_{RT}=2.45V$, $V_{RB}=0.05V$, $PD=High$

You can change the voltages of V_{RT} and V_{RB} to 2.5V and 0.0V , but the performance of DAC1252X_JVC will be degraded.

CORE EVALUATION GUIDE




TESTABILITY

Whether you use MUX or the internal logic for testability, it is required to be able to select the values of digital inputs (D[7:0]).

See above figure. Only if it is, you can check the main function. (Linearity)

Normal Test Condition : VRT=2.45V , VRB=0.05V , PD=High

CORE LAYOUT GUIDE



1. It is recommended that you use thick analog power metal. when connecting to PAD, the path should be kept as short as possible.
2. Digital power and analog power are separately used.
3. When the core block is connected to other blocks, it must be double guard-ring using N-well and P+ active to remove the substrate and coupling noise.
In that case, the power metal should be connected to PAD directly.
4. The Bulk power is used to reduce the influence of substrate noise.
5. Digital input signal lines must be same length to reduce the difference of delay.

PC BOARD LAYOUT CONSIDERATION**1. PC Board Considerations**

To minimize noise on the power lines and the ground lines, the digital inputs need to be shielded and decoupled. This trace length between groups of VDD (AVDD25A,AVDD25D) and VSS (AVSS25A,VSS25AD0) pins should be as short as possible so as to minimize inductive ringing.

2. Supply Decoupling and Planes

For the decoupling capacitor between the power line and the ground line, 0.1uF ceramic capacitor is used in parallel with a 10uF tantalum capacitor.

The digital power plane(AVDD25D) and analog power plane(AVDD25A) are connected through a ferrite bead, and also the digital ground plane(VSS25AD0) and the analog ground plane(AVSS25A). This ferrite bead should be located within 3inches of the DAC1252X_JVC. The analog power plane supplies power to the DAC1252X_JVC of the analog output pin and related devices.

PRELIMINARY

FEEDBACK REQUEST

We appreciate your interest in our products.

If you have further questions, please specify in the attached form.

Thank you very much.

DC / AC ELECTRICAL CHARACTERISTIC

Characteristics	Min	Typ	Max	Unit	Remarks
Supply Voltage				V	
Power dissipation				mW	
Resolution				Bits	
Analog Output Voltage				V	
Operating Temperature				°C	
Output Load Capacitor				pF	
Output Load Resistor				°C	
Integral Non-Linearity Error				LSB	
Differential Non-Linearity Error				LSB	
Maximum Conversion Rate				MHz	

VOLTAGE OUTPUT DAC

Reference Voltage TOP BOTTOM				V	
Analog Output Voltage Range				V	
Digital Input Format	Binary Code or 2's Complement Code				

CURRENT OUTPUT DAC

Analog Output Maximum Current				mA	
Analog Output Maximum Signal Frequency				kHz	
Reference Voltage				V	
External Resistor for Current Setting(RSET)				W	
Pipeline Delay				sec	

- Do you want to Power down mode?
- Do you want to Internal Reference Voltage(BGR)?
- Which do you want to Serial Input TYPE or parallel Input TYPE?
- Do you need 3.3V and 5V power supply in your system?

