

SCHOTTKY RECTIFIER  
 HIGH EFFICIENCY SERIES

**16SYJQ045C**  
 16A, 45V


**Major Ratings and Characteristics**

Characteristics	Limits	Units
I <sub>F(AV)</sub>	16	A
V <sub>RRM</sub>	45	V
I <sub>FSM</sub> @ t <sub>p</sub> = 8.3ms half-sine	250	A
V <sub>F</sub> @ 16Apk, T <sub>J</sub> = 125°C	0.52	V
T <sub>J</sub> , T <sub>stg</sub> Operating and storage	-55 to 150	°C

**Description/Features**

The 16SYJQ045C Schottky rectifier has been expressly designed to meet the rigorous requirements of HiRel environments. It is packaged in the hermetic isolated D2 PAK ceramic package. The device's forward voltage drop and reverse leakage current are optimized for the lowest power loss and the highest circuit efficiency for typical high frequency switching power supplies and resonant power converters. Full MIL-PRF-19500 quality conformance testing is available on source control drawings to TX, TXV and S levels.

- Hermetically Sealed
- Low Forward Voltage Drop
- High Frequency Operation
- Guard Ring for Enhanced Ruggedness and Long Term Reliability
- Lightweight



16SYJQ045C

International  
**IR** Rectifier

### Voltage Ratings

Part number	16SYJQ045C		
$V_R$ Max. DC Reverse Voltage (V)	45		
$V_{RWM}$ Max. Working DC Reverse Voltage (V)			

### Absolute Maximum Ratings

Parameters	Limits	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current See Fig. 5	16	A	50% duty cycle @ $T_C = 117^\circ\text{C}$ , square waveform
$I_{FSM}$ Max. Peak One Cycle Non - Repetitive Surge Current	250	A	@ $t_p = 8.3$ ms half-sine

### Electrical Specifications

Parameters	Limits	Units	Conditions
$V_{FM}$ Max. Forward Voltage Drop See Fig. 1①	0.63	V	$T_J = -55^\circ\text{C}$
	0.79	V	
	0.56	V	
	0.79	V	$T_J = 25^\circ\text{C}$
	0.52	V	
	0.85	V	
$I_{RM}$ Max. Reverse Leakage Current See Fig. 2①	0.74	mA	$T_J = 25^\circ\text{C}$ $V_R = \text{rated } V_R$
	75	mA	
	210	mA	
$C_J$ Max. Junction Capacitance	2800	pF	$V_R = 5\text{VDC}$ ( 1MHz, 25°C )
$L_S$ Typ. Series Inductance	9.8	nH	Measured from Cathode lead to Anode lead 6mm (0.025in) from package

### Thermal-Mechanical Specifications

Parameters	Limits	Units	Conditions
$T_J$ Max.Junction Temperature Range	-55 to 150	°C	
$T_{stg}$ Max. Storage Temperature Range	-55 to 150	°C	
$R_{thJC}$ Max. Thermal Resistance, Junction to Case	1.15	°C/W	DCoperation See Fig. 4
wt Weight(Typical)	4.3	g	
Die Size	200X200	mils	
Case Style	D2 PAK		

① Pulse Width < 300μs, Duty Cycle < 2%




Fig. 1 - Max. Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage

16SYJQ045C

International  
**IR** Rectifier




Fig. 4 - Max. Thermal Impedance  $Z_{thJC}$  Characteristics




Fig. 5 - Max. Allowable Case Temperature Vs.  
Average Forward Current

International  
**IR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105

**IR LEOMINSTER :** 205 Crawford St., Leominster, Massachusetts 01453, USA Tel: (978) 534-5776

TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.

*Data and specifications subject to change without notice. 09/2006*