

## SWITCHMODE™ Series NPN Silicon Power Transistors

The BUS50 transistor is designed for low voltage, high-speed, power switching in inductive circuits where fall time is critical. It is particularly suited for battery SWITCHMODE applications such as:

- Switching Regulators
- Inverters
- Solenoid and Relay Drivers
- Motor Controls
- Fast Turn-Off Times  
300 ns Inductive Fall Time  $-25^{\circ}\text{C}$  (Typ)
- Operating Temperature Range  $-65$  to  $+200^{\circ}\text{C}$

### MAXIMUM RATINGS

Rating	Symbol	BUS50	Unit
Collector-Emitter Voltage	$V_{\text{CEO(sus)}}$	125	Vdc
Collector-Emitter Voltage	$V_{\text{CEV}}$	200	Vdc
Emitter Base Voltage	$V_{\text{EB}}$	7	Vdc
Collector Current — Continuous	$I_{\text{C}}$	70	Adc
— Peak (1)	$I_{\text{CM}}$	140	
— Overload	$I_{\text{ol}}$		
Base Current — Continuous	$I_{\text{B}}$	20	Adc
— Peak (1)	$I_{\text{BM}}$		
Total Power Dissipation — $T_{\text{C}} = 25^{\circ}\text{C}$	$P_{\text{D}}$	350	Watts
— $T_{\text{C}} = 100^{\circ}\text{C}$		200	
Derate above $25^{\circ}\text{C}$		2	W/ $^{\circ}\text{C}$
Operating and Storage Junction Temperature Range	$T_{\text{J}}, T_{\text{stg}}$	$-65$ to $+200$	$^{\circ}\text{C}$


### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	$R_{\theta\text{JC}}$	0.5	$^{\circ}\text{C/W}$
Maximum Lead Temperature for Soldering Purposes: 1/8" from Case for 5 Seconds	$T_{\text{L}}$	275	$^{\circ}\text{C}$


(1) Pulse Test: Pulse Width = 5 ms, Duty Cycle  $\leq 10\%$ .

## BUS50

70 AMPERES  
NPN SILICON  
POWER TRANSISTOR  
125 VOLTS (BVCEO)  
350 WATTS  
200 V (BVCEV)



CASE 197A-05  
TO-204AE



# BUS50

## ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

### OFF CHARACTERISTICS<sup>2</sup>

Collector–Emitter Sustaining Voltage ( $I_C = 200\text{ mA}$ , $I_B = 0$ , $L = 25\text{ mH}$ )	$V_{CEO(sus)}$	125		Vdc
Collector Cutoff Current at Reverse Bias ( $V_{CE} = 200\text{ V}$ , $V_{BE} = -1.5\text{ V}$ ) ( $V_{CE} = 200\text{ V}$ , $V_{BE} = -1.5\text{ V}$ , $T_C = 125^\circ\text{C}$ )	$I_{CEX}$		0.2 2	mAdc
Collector–Emitter Cutoff Current ( $V_{CE} = 125\text{ V}$ )	$I_{CEO}$		1	mAdc
Emitter Cutoff Current ( $V_{EB} = 7\text{ V}$ )	$I_{EBO}$		0.2	mAdc

### ON CHARACTERISTICS<sup>2</sup>

DC Current Gain ( $I_C = 5\text{ A}$ , $V_{CE} = 4\text{ V}$ ) ( $I_C = 50\text{ A}$ , $V_{CE} = 4\text{ V}$ )	$h_{FE}$	20 15		
Collector–Emitter Saturation Voltage ( $I_C = 35\text{ A}$ , $I_B = 2\text{ A}$ ) ( $I_C = 70\text{ A}$ , $I_B = 7\text{ A}$ )	$V_{CE(sat)}$		1 1.2	Vdc
Base–Emitter Saturation Voltage ( $I_C = 35\text{ A}$ , $I_B = 2\text{ A}$ ) ( $I_C = 70\text{ A}$ , $I_B = 7\text{ A}$ )	$V_{BE(sat)}$		1.8 2	Vdc

### SWITCHING CHARACTERISTICS (Resistive Load) $t_{on}$ and (Inductive Load) $t_{sv}$ , $t_{fi}$



Turn–On Time	$I_C = 70\text{ A}$ , $I_{B1} = 7\text{ A}$ $V_{BE(off)} = -5\text{ V}$ ( $V_{CC} = 125\text{ V}$ )	$t_{on}$	1.2	$\mu\text{s}$
Storage Time		$t_{sv}$	1.5	
Fall Time		$t_{fi}$	0.3	

<sup>2</sup> Pulse Test: Pulse Width  $\leq 300\ \mu\text{s}$ , Duty Cycle  $\leq 2\%$ .

# BUS50

## PACKAGE DIMENSIONS


TO-204AE (TO-3)  
CASE 197A-05  
ISSUE J



- NOTES:  
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.  
2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.530 REF		38.86 REF	
B	0.990	1.050	25.15	26.67
C	0.250	0.335	6.35	8.51
D	0.057	0.063	1.45	1.60
E	0.060	0.070	1.53	1.77
G	0.430 BSC		10.92 BSC	
H	0.215 BSC		5.46 BSC	
K	0.440	0.480	11.18	12.19
L	0.665 BSC		16.89 BSC	
N	0.760	0.830	19.31	21.08
Q	0.151	0.165	3.84	4.19
U	1.187 BSC		30.15 BSC	
V	0.131	0.188	3.33	4.77

SWITCHMODE is a trademark of Semiconductor Components Industries, LLC.

**ON Semiconductor** and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

## PUBLICATION ORDERING INFORMATION

### **NORTH AMERICA Literature Fulfillment:**

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** ONlit@hibbertco.com  
Fax Response Line: 303-675-2167 or 800-344-3810 Toll Free USA/Canada

**N. American Technical Support:** 800-282-9855 Toll Free USA/Canada

**EUROPE:** LDC for ON Semiconductor – European Support

**German Phone:** (+1) 303-308-7140 (Mon-Fri 2:30pm to 7:00pm CET)  
**Email:** ONlit-german@hibbertco.com  
**French Phone:** (+1) 303-308-7141 (Mon-Fri 2:00pm to 7:00pm CET)  
**Email:** ONlit-french@hibbertco.com  
**English Phone:** (+1) 303-308-7142 (Mon-Fri 12:00pm to 5:00pm GMT)  
**Email:** ONlit@hibbertco.com

**EUROPEAN TOLL-FREE ACCESS\*: 00-800-4422-3781**

\*Available from Germany, France, Italy, UK, Ireland

### **CENTRAL/SOUTH AMERICA:**

**Spanish Phone:** 303-308-7143 (Mon-Fri 8:00am to 5:00pm MST)  
**Email:** ONlit-spanish@hibbertco.com  
**Toll-Free from Mexico:** Dial 01-800-288-2872 for Access –  
then Dial 866-297-9322

**ASIA/PACIFIC:** LDC for ON Semiconductor – Asia Support

**Phone:** 1-303-675-2121 (Tue-Fri 9:00am to 1:00pm, Hong Kong Time)  
**Toll Free from Hong Kong & Singapore:**  
**001-800-4422-3781**  
**Email:** ONlit-asia@hibbertco.com

**JAPAN:** ON Semiconductor, Japan Customer Focus Center  
4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031  
**Phone:** 81-3-5740-2700  
**Email:** r14525@onsemi.com

**ON Semiconductor Website:** <http://onsemi.com>

For additional information, please contact your local Sales Representative.