



BRAIDFLEX

P.V.C. PRESSURE HOSE

Construction

Braidflex is constructed from a reinforcing braid of polyester fibre, laminated between two layers of clear P.V.C., producing a strong hose, capable of withstanding high pressures. It is available in two grades - food grade or industrial. Both manufactured to BS6066 1981 tolerances.

Applications

Factory airlines, pneumatic equipment, the conveyance of pressurised liquids and gases and the transport of chemicals, gases, dilute acids and alkalis are all ideal uses for Braidflex.

Technical Details

For sizes and pressures, see table.

Length:

30m Coils (100ft) - other lengths are available to special order.

Temperatures: -10°C to +60°C.

Standard Colours:

clear, black; others also available.

For details of unreinforced P.V.C. tubing, ask for leaflet no. CP200 (Cleartube).

* Average at 20°C

Size: (DIA)		Max. Working Pressure*	
mm	Inches	Bar	PSI
3	1/8	28	400
5	3/16	20	300
6	1/4	17	250
8	5/16	14	200
10	3/8	12	180
12	1/2	10	150
16	5/8	8	120
19	3/4	7	100
22	7/8	6	85
25	1	5.5	80
32	1 1/4	5	75
38	1 1/2	3.5	50
51	2	3	45

Important Note: Please note that the information is to the best of our knowledge, true and accurate. We reserve the right to alter the specifications without notice. Since conditions under which the products may be used are beyond our control, our recommendations are made without warranty or guarantee and we cannot be held responsible for misuse of products or information. However, our experienced technical staff would be happy to advise you on the uses for which our products are suitable.

Southern Division & Headquarters:
FLEXIBLE HOSE SUPPLIES LTD.,
140 EDINBURGH AVENUE,
SLOUGH, BERKS, SL1 4UA
TEL: 01753 570863
FAX: 01753 824141
TELEX: 849182

Midland Division & Manufacturing Plant:
FLEX-METALLIC INDUSTRIES,
CASWELL ROAD, BRACKMILLS INDUSTRIAL ESTATE,
NORTHAMPTON, NN4 0PW
TEL: 01604 762175
FAX: 01604 769915

Northern Division:
FLEXIBLE HOSE SUPPLIES LTD.,
SPRINGFIELD ROAD, KEARSLEY,
BOLTON, LANCs, BL4 8NB
TEL: 01204 795735
FAX: 01204 795767

©1996