

Appearance	Type	Case Size	Power Rating (W)	Resistance Range (Ω)	Resistance Tolerance (%)	T.C.R (ppm/°C)	L x W x T Dimensions (mm)	Packing Qty. 7 Inch Reel (pcs.)	Features	
THICK FILM CHIP RESISTORS General Purpose 5%, 1% 	ERJ-XGEJ	01005	1 / 32 W	10 ~ 1 M	± 5	± 200	0.40 x 0.20 x 0.12	10,000	<ul style="list-style-type: none"> ● Small size and lightweight ● High reliability using metal glaze thick film resistive element and three layers of electrodes ● Compatible with automatic placement of bulk taping and bulk case packaging ● Reflow and flow solderability ● Meets ISO-9001 & QS-9000 standards ● The power rating for one case-size larger is available for ERJ-3E; 6E; and 8E ● Low resistance tolerance: ERJ-3E; 6E; 8E; 14, 12 series: ± 1% NOTE: Chip resistor 5% tolerance Resistance Range (Ω) T.C.R. (ppm / °C) <10 -100 ~ +600 10 - 1 M ± 200 >1M -400 ~ +150	
	ERJ-1GEJ	0201	1 / 20 W	1.0 ~ 1 M	± 5		0.60 x 0.3 x 0.25	15,000		
	ERJ-1GEF			10 ~ 1 M	± 1					
	ERJ-2GEJ	0402	1 / 16 W	1.0 ~ 2.2 M	± 5	± 100	1.0 x 0.5 x 0.35	10,000		
	ERJ-2RKF			10 ~ 1 M	± 1					
	ERJ-3GEYJ	0603	1 / 10 W	1.0 ~ 10 M	± 5	± 200	1.6 x 0.8 x 0.45	5,000		
	ERJ-3KEF			10 ~ 1 M	± 1		± 100			
	ERJ-6GEYJ	0805	1 / 8 W	1.0 ~ 10 M	± 5	± 200	2.0 x 1.25 x 0.6	5,000		
	ERJ-6ENF			10 ~ 2.2 M	± 1		± 100			
	ERJ-8GEYJ	1206	1 / 4 W	1.0 ~ 10 M	± 5	± 200	3.2 x 1.6 x 0.6	5,000		
	ERJ-8ENF			10 ~ 2.2 M	± 1		± 100			
	ERJ-14YJ	1210	1 / 4 W	1.0 ~ 10 M	± 5	± 200	3.2 x 2.5 x 0.6	5,000		
	ERJ-14NF			10 ~ 1 M	± 1		± 100			
	ERJ-12YJ	1812	1 / 2 W	1.0 ~ 10 M	± 5	± 200	4.5 x 3.2 x 0.6	5,000		
	ERJ-12NF			10 ~ 1 M	± 1		± 100			
	ERJ-12ZYJ	2010	1 / 2 W	1.0 ~ 10 M	± 5	± 200	5.0 x 2.5 x 0.6	5,000		
	ERJ-12SF			10 ~ 1 M	± 1		± 100			
ERJ-1TYJ	2512	1 W	1.0 ~ 1 M	± 5	± 200	6.4 x 3.2 x 0.6	4,000			
ERJ-1TNF			10 ~ 1 M	± 1		± 100				
LOW RESISTANCE THICK FILM CHIP RESISTORS Current Sensing 5%, 1% 	ERJ-3RSJ	0603	1 / 10 W	0.1 ~ 0.2	± 5	0.1 ~ 0.91 Ω ± 300	1.6 x 0.8 x 0.45	5,000	<ul style="list-style-type: none"> ● Small size and lightweight ● High reliability using metal glaze thick film resistive elements and three layers of electrodes ● Compatible with automatic placement of bulk taping and bulk case packaging ● Reflow and flow solderability ● Meets ISO-9001 & QS-9000 standards ● Low resistance tolerance: ERJ-2R; 3R; 6R series ... ± 5%, ± 1% 	
	ERJ-3RQJ									0.22 ~ 0.91
	ERJ-3RSF									0.1 ~ 0.2
	ERJ-3RQF			0.22 ~ 9.1	± 5	0.1 ~ 0.91 Ω ± 300	2.0 x 1.25 x 0.6	5,000		
	ERJ-6RSJ	0805	1 / 8 W	0.1 ~ 0.2						
	ERJ-6RQJ									0.22 ~ 0.91
	ERJ-6RSF				0.1 ~ 0.2	± 1	1.0 ~ 9.1 Ω ± 200			
	ERJ-6RQF			0.22 ~ 9.1	± 5	0.1 ~ 0.91 Ω ± 250	3.2 x 1.6 x 0.6	5,000		
	ERJ-8RSJ	1206	1 / 4 W	0.1 ~ 0.2						
	ERJ-8RQJ									0.22 ~ 9.1
	ERJ-8RSF				0.1 ~ 0.2	± 1	1.0 ~ 9.1 Ω ± 200			
	ERJ-8RQF			0.22 ~ 9.1	± 5	0.1 ~ 0.91 Ω ± 200	3.2 x 2.5 x 0.6	5,000		
	ERJ-14RSJ	1210	1 / 4 W	0.1 ~ 0.2						
	ERJ-14RQJ									0.22 ~ 0.91
	ERJ-14RSF				0.1 ~ 0.2	± 1	1.0 ~ 9.1 Ω ± 100			
	ERJ-14RQF			0.22 ~ 9.1	± 5	0.1 ~ 0.91 Ω ± 200	4.5 x 3.2 x 0.6	5,000		
	ERJ-12RSJ	1812	1 / 2 W	0.1 ~ 0.2						
ERJ-12RQJ				0.22 ~ 0.91						
ERJ-12RSF				0.1 ~ 0.2	± 1	1.0 ~ 9.1 Ω 100				
ERJ-12RQF			0.22 ~ 9.1	± 5	0.1 ~ 0.91 Ω ± 200	6.4 x 3.2 x 0.6	4,000			
ERJ-1TRSJ	2512	1 W	0.1 ~ 0.2							
ERJ-1TRQJ								0.22 ~ 0.91		
ERJ-1TRSF				0.1 ~ 0.2	± 1	1.0 ~ 9.1 Ω ± 100				
ERJ-1TRQF			0.22 ~ 0.91	± 1	1.0 ~ 9.1 Ω ± 100					
ULTRA LOW VALUE CHIP RESISTORS Current Sensing (mΩ) 5%, 1% 	ERJ-L03	0603	1 / 10 W	47 ~ 100 milli.	± 5	± 200	1.6 x 0.8 x 0.45	5,000	<ul style="list-style-type: none"> ● Small size and lightweight ● High reliability using metal glaze thick film resistive elements and three layers of electrodes ● Compatible with automatic placement of bulk taping and bulk case packaging ● Reflow and flow solderability ● Meets ISO-9001 & QS-9000 standards ● Low resistance values for ERJ-L14; L12; L1W series: 47 mΩ ~ 100 mΩ 	
	ERJ-L06	0805	1 / 8 W	47 ~ 100 milli.	± 5	± 100	2.0 x 1.25 x 0.5	5,000		
	ERJ-L08	1206	1/4 W	47 ~ 100 milli.	± 5	± 100	3.2 x 1.6 x 0.6	5,000		
	ERJ-L14KJ	1210	1/4 W	20 ~ 100 milli.	± 5	± 100	3.2 x 2.5 x 0.6	5,000		
	ERJ-L14KF				± 1					
	ERJ-L12KJ	1812	1/2 W	20 ~ 100 milli.	± 5	± 100	4.5 x 3.2 x 0.6	5,000		
	ERJ-L12KF				± 1					
	ERJ-L1D	2010	1/2 W	40 ~ 100 milli.	± 5	<47 milli: ± 300 ≥47 milli: ± 100	5.0 x 2.5 x 0.6	5,000		
	ERJ-L1WKJ	2512	1W	40 ~ 100 milli.	± 5	± 100	6.4 x 3.2 x 1.1	3,000		
	ERJ-L1WKF				± 1					
	ERJ-M1WT	2512	1W	1 ~ 4 milli.	± 5	1 ~ 2 mΩ ± 500 1 ~ 2 mΩ ± 500	6.4 x 3.2 x 0.8	3,000		
	ERJ-M1WTF			3 ~ 4 milli.	± 1					
	ERJ-M1WSJ			3 ~ 20 milli.	± 5	≥ 5 mΩ: ± 100 < 5 mΩ: ± 350				
ERJ-M1WSF	± 1									

NOTE: These parts are RoHS compliant.

Design and specifications are subject to change without notice. Please review technical specifications before purchase.
For any safety concerns regarding this product, please contact us immediately for technical consultation.

Surface Mount Chip Resistors

Appearance	Type	Case Size	Power Rating (W)	Resistance Range (Ω)	Resistance Tolerance (%)	T.C.R. (ppm/°C)	L x W x T Dimensions (mm)	Packing Qty. 7 Inch Reel (pcs.)	Features				
Ultra Precision 0.1%, 0.5% 	THIN FILM CHIP RESISTORS	ERA-3YEB	0603	1 / 16 W	100 ~ 33 K	± 0.1	± 25	5,000	<ul style="list-style-type: none"> ● Small size and lightweight ● High reliability ● Low T.C.R. and current noise ● Excellent non-linearity ● Reflow & flow solderability ● Meets ISO-9001 standards 				
	EBA-6YEB	0805	1 / 10 W	100 ~ 100 K									
	ERA-8YEB	1206	1 / 8 W	100 ~ 100 K									
	ERA-14EB	1210	1 / 4 W	100 ~ 100 K	± 0.5	± 25	1.6 x 0.8 x 0.45	5,000					
	ERA-3YED	0603	1 / 16 W	10 ~ 91									
	ERA-3YHD			100 ~ 33 K									
	ERA-3YKD	0805	1 / 10 W	36K ~ 330K	± 0.5	± 50	2.0 x 1.25 x 0.5	5,000					
	ERA-6YED			10 ~ 91									
	ERA-6YHD			100 ~ 100 K									
ERA-6YKD			110K ~ 1M		± 100								
LINEAR THERMISTOR 	ERAS	0805	1 / 10 W	1 K ~ 10 K	± 5	1500 ± 200	2.0 x 1.25 x 0.5	5,000	<ul style="list-style-type: none"> ● Excellent linearity of temperature coefficient to resistance value ● Good for temperature compensation circuit in applications such as VRM and/or PA module 				
				1 K ~ 4.7 K	± 5	2700 ± 10%							
				5.6 ~ 470 K	± 5	3900 ± 10%							
	ERAV	0603	1 / 16 W	1 K ~ 10 K	± 5	1500 ± 200	1.6 x 0.8 x 0.45	5,000					
				1 K ~ 3.3 K	± 5	2700 ± 10%							
				5.6 ~ 390	± 5	3900 ± 10%							
Chip Attenuator 	EXB-24AT	0404	1 / 25 W Package	Attenuation Range 1 ~ 5 dB	Attenuation Tolerance ± 0.3 dB	Characteristic Impedance 50 Ω	1.0 x 1.0 x 0.35	10,000	<ul style="list-style-type: none"> ● Space saving design using unbalanced pie-type attenuator 				
				6 ~ 10 dB	± 0.5 dB								
CHIP RESISTOR ARRAY 	EXB-14V	0201 x 2 Flat Term	1 / 32 W	10 ~ 1 M	± 5	± 200 x 10 ⁻⁶ / °C	0.8 x 0.6 x 0.35	10,000	<ul style="list-style-type: none"> ● High density of resistors in single array chip ● Improved placement efficiency (2 to 4 times greater) compared to flat chip type resistors 				
							EXB-18V			0201 x 4 Flat Term	10 ~ 1 M	± 5	1.4 x 0.6 x 0.35
							EXB-N8V			0402 x 4 Concave Term	1 ~ 1 M	± 5	2.0 x 1.0 x 0.45
	EXB-24V	0402 x 2 Convex Term	1 / 16 W	1 ~ 1 M	± 5	10 - 1 M : ± 200	1.0 x 1.0 x 0.35	5,000					
							EXB-28V			0402 x 4 Convex Term	1 / 32 W	2.0 x 1.0 x 0.35	
	EXB-2HV	0402 x 8 Convex Term	1 / 16 W Element	1 ~ 1 M	± 5	10 > : -100 - + 600	3.8 x 1.6 x 0.45	5,000					
	EXB-34V	0603 x 2 Convex Term					1.6 x 1.6 x 0.50						
	EXB-38V	0603 x 4 Convex Term					3.2 x 1.6 x 0.50						
	EXB-V4V	0603 x 2 Concave Term	1.6 x 1.6 x 0.60	2,500									
	EXB-V8V	0603 x 4 Concave Term	3.2 x 1.6 x 0.60										
	EXB-S8V	0805 x 4 Concave Term	1 / 10 W Element	10 ~ 1 M			5.08 x 2.2 x 0.70	2,500					
CHIP R-NETWORK 	EXB-D10C	1206 Concave Term	1 / 20 W Element	47 ~ 1 M	± 5	± 200	3.2 x 1.6 x 0.55	5,000	<ul style="list-style-type: none"> ● High density placement for digital signal applications: 8 bussed resistors for pull up/down circuits ● Superior mountability due to unique concave terminal 				
							EXB-E10C	1608 Concave Term		1 / 16 W Element	4.0 x 2.1 x 0.55	4,000	
							EXB-A10P	2512 Concave Term		1 / 16 W Element	6.4 x 3.1 x 0.55		
CHIP R-C-NETWORK 	EZA-DT	1206	R = 1 / 16 W C = 12 V	Combination of R and C R = 22, 47, 100, 220, 470, 1KΩ C = 22, 47, 100 pF			3.2 x 1.6 x 0.65	5,000	<ul style="list-style-type: none"> ● Four R-C filters for noise reduction in a 1206 & 1608 package 				
			EZA-ST				1608	R = 1 / 16 W C = 25 V		4.0 x 2.1 x 0.65	4,000		

■ EIA Standard Resistance Values

	E-96 Tolerance ±1%			E-24 ±5%, 0.5%, 0.1%	E-12 ±10%	E-6 ±20%
100	178	316	562	1.0	1.0	1.0
102	182	324	576	1.1	-	-
105	187	332	590	1.2	1.2	-
107	191	340	604	1.3	-	-
110	196	348	619	1.5	1.5	1.5
113	200	357	634	1.6	-	-
115	205	365	649	1.8	1.8	-
118	210	374	665	2.0	-	-
121	215	383	681	2.2	2.2	2.2
124	221	392	698	2.4	-	-
127	226	402	715	2.7	2.7	-
130	232	412	732	3.0	-	-

	E-96 Tolerance ±1%			E-24 ±5%, 0.5%, 0.1%	E-12 ±10%	E-6 ±20%
133	237	422	750	3.3	3.3	3.3
137	243	432	768	3.6	-	-
140	249	442	787	3.9	3.9	-
143	255	453	806	4.3	-	-
147	261	464	825	4.7	4.7	4.7
150	267	475	845	5.1	-	-
154	274	487	866	5.6	5.6	-
158	280	499	887	6.2	-	-
162	287	511	909	6.8	6.8	6.8
165	294	523	931	7.5	-	-
169	301	536	953	8.2	8.2	-
174	309	549	976	9.1	-	-

NOTE: These parts are RoHS compliant.

Design and specifications are subject to change without notice. Please review technical specifications before purchase. For any safety concerns regarding this product, please contact us immediately for technical consultation.