


CABLE MODEM LOW PASS TRANSMIT FILTERS



-  For use in HFC and cable modems
-  Domestic and international versions
-  Less than 1 dB inband insertion loss
-  Small group delay variation
-  Small surface mount package



Electrical Specifications @ 25°C — Operating Temperature -40°C to +85°C

Part Number	In/Out Impedance	Passband	Insertion Loss (MAX)	Return Loss (MIN)	GDV (MAX)	Stopband	Attenuation (MIN)
B5004	75 Ω	5-42 MHz	1 dB	-18 dB	24 ns	at 54 MHz 78 to 860 MHz	10 dB 50 dB
B5005	75 Ω	5-65 MHz	1 dB	-17.5 dB	15 ns	at 84 MHz 120 to 860 MHz	10 dB 55 dB




Mechanical

Schematic

B5004/5005



SUGGESTED PAD LAYOUT



Weight 1.0 grams
Tube35/tube

Dimensions: Inches
mm
Unless otherwise specified, all tolerances are $\pm \frac{.005}{0.13}$

For More Information :

Corporate

12220 World Trade Drive
San Diego, CA 92128
Tel: 619 674 8100
FAX: 619 674 8262
<http://www.pulseeng.com>
Quick-Facts: 619 674 9672

Europe

1 & 2 Huxley Road
The Surrey Research Park
Guildford, Surrey GU2 5RE
United Kingdom
Tel: 44 1483 401700
FAX: 44 1483 401701

Asia

150 Kampong Ampat
#07-01/02
KA Centre
Singapore 368324
Tel: 65 287 8998
FAX: 65 280 0080

Distributor

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

 Printed on recycled paper. ©1999, Pulse Engineering, Inc.

B907.A (1/99)