

Micro Commercial Components

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 BAS16T BAW56T BAV70T BAV99T

Features

- Ultra-Small Surface Mount Package
- For General Purpose Switching Applications
- High Conductance
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1










Maximum Ratings


- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C


Electrical Characteristics @ 25°C Unless Otherwise Specified


Peak Repetitive Reverse Voltage	V_{RRM}	85V	
Continuous Forward Current	I _F	75mA	
Power Dissipation	P_{D}	150mW	
Peak Forward Surge Current @t=1.0us @t=1.0ms @t=1.0s	I _{FSM}	4.0A 1.0A 0.5A	
Maximum Instantaneous Forward Voltage	V _F	715mV 855mV 1000mV 1250mV	$I_F = 1mA$ $I_F = 10mA$; $I_F = 50mA$ $I_F = 150mA$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	2μA 0.03μA	V _R =75Volts V _R =25Volts
Typical Total Capacitance	C _T	1.5pF	Measured at 1.0MHz, V _R =0V
Reverse Recovery Time	T _{rr}	4nS	IF = IR = 10mA, Irr = $0.1 \times IR$, RL = 100Ω

150mW 85Volt Switching Diode











DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.059	.067	1.50	1.70		
В	.030	.033	0.75	0.85		
C	.057	.069	1.45	1.75		
D	.020 Nominal		0.50Nominal			
Е	.035	.043	0.90	1.10		
G	.000	.004	.000	.100		
H	.028	.031	.70	0.80		
J	.004	.008	.100	.200		
K	.010	.014	.25	.35		


BAS16T/BAW56T BAV70T/BAV99T








 T_S , SOLDERING POINT TEMPERATURE (°C) Fig. 1 Current Derating Curve



V , INSTANTANEOUS FORWARD VOLTAGE (V) Fig. 2 Forward Characteristics



T_i, JUNCTION TEMPERATURE (°C) Fig. 3, Typical Reverse Characteristics



Ordering Information

Device	Packing
(Part Number)-TP	Tape&Reel3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.