

élantec
 HIGH PERFORMANCE ANALOG INTEGRATED CIRCUITS

EL2030/EL2030C

120 MHz Current Feedback Amplifier

ELANTEC INC

T-79-07-10

Features

- 3 dB bandwidth = 120 MHz, $A_V = 1$
- 3 dB bandwidth = 110 MHz, $A_V = 2$
- 0.01% differential gain and 0.01° differential phase (NTSC, PAL)
- 0.05% differential gain and 0.02° differential phase (HDTV)
- Slew rate 2000 V/ μ s
- 65 mA output current
- Drives $\pm 10V$ into 200 Ω load
- Characterized at $\pm 5V$ and $\pm 15V$
- Low voltage noise
- Current mode feedback
- Settling time of 40 ns to 0.25% for a 10V step
- Output short circuit protected
- Low cost

Applications

- Video gain block
- Video distribution amplifier
- HDTV amplifier
- Residue amplifiers in ADC
- Current to voltage converter
- Coax cable driver

Ordering Information

Part No.	Temp. Range	Package	Outline #
EL2030CN	0°C to +75°C	8-Pin P-DIP	MDP0031
EL2030CM	0°C to +75°C	20-Lead SOL	MDP0027
EL2030CJ	0°C to +75°C	14-Pin CerDIP	MDP0014
EL2030J	-55°C to +125°C	14-Pin CerDIP	MDP0014
EL2030J/883B	-55°C to +125°C	14-Pin CerDIP	MDP0014
EL2030L	-55°C to +125°C	20-Pad LCC	MDP0007
EL2030L/883B	-55°C to +125°C	20-Pad LCC	MDP0007

5962-90818 is the SMD version of this device.

General Description


The EL2030 is a very fast, wide bandwidth amplifier optimized for gains between -10 and +10. Built using the Elantec monolithic Complementary Bipolar process, this amplifier uses current mode feedback to achieve more bandwidth at a given gain than a conventional voltage feedback operational amplifier.

Due to its wide operating supply range ($\pm 15V$) and extremely high slew rate of 2000 V/ μ s, the EL2030 drives $\pm 10V$ into 200 Ω at a frequency of 30 MHz, while achieving 110 MHz of small signal bandwidth or $A_V = +2$. This bandwidth is still 95 MHz for a gain of +10. On $\pm 5V$ supplies the amplifier maintains a 90 MHz bandwidth for $A_V = +2$. When used as a unity gain buffer, the EL2030 has a 120 MHz bandwidth with the gain precision and low distortion of closed loop buffers.

The EL2030 features extremely low differential gain and phase, a low noise topology that reduces noise by a factor of 2 over competing amplifiers, and settling time of 40 ns to 0.25% for a 10V step. The output is short circuit protected. In addition, datasheet limits are guaranteed for $\pm 5V$ and $\pm 15V$ supplies.

Elantec's products and facilities comply with MIL-STD-883 Revision C, MIL-I-45208A, and other applicable quality specifications. For information on Elantec's military processing, see Elantec document, QRA-2: *Elantec's Military Processing, Monolithic Integrated Circuits*.

Connection Diagrams



EL2030/EL2030C

ELANTEC INC

120 MHz Current Feedback Amplifier**Absolute Maximum Ratings** ($T_A = 25^\circ\text{C}$)

V_S	Supply Voltage	$\pm 18\text{V}$ or 36V	T_J	Operating Junction Temperature	
V_{IN}	Input Voltage	$\pm 15\text{V}$ or V_S		Ceramic Packages	175°C
ΔV_{IN}	Differential Input Voltage	$\pm 6\text{V}$		Plastic Packages	150°C
P_D	Maximum Power Dissipation	See Curves	T_{ST}	Storage Temperature	-65°C to $+150^\circ\text{C}$
I_{IN}	Input Current	$\pm 10\text{ mA}$		Lead Temperature	
I_{OP}	Peak Output Current	Short Circuit Protected		DIP Package	300°C
	Output Short Circuit Duration	Continuous		(Soldering: < 5 seconds—CN; < 10 seconds—J)	
	(Note 1)			SOL Package	
T_A	Operating Temperature Range			Vapor Phase (60 seconds)	215°C
	EL2030	-55°C to $+125^\circ\text{C}$		Infrared (15 seconds)	220°C
	EL2030C	0°C to $+75^\circ\text{C}$			

Important Note:

All parameters having Min/Max specifications are guaranteed. The Test Level column indicates the specific device testing actually performed during production and Quality inspection. Elantec performs most electrical tests using modern high-speed automatic test equipment, specifically the LTX77 Series system. Unless otherwise noted, all tests are pulsed tests, therefore $T_J = T_C = T_A$.

Test Level	Test Procedure
I	100% production tested and QA sample tested per QA test plan QCX0002.
II	100% production tested at $T_A = 25^\circ\text{C}$ and QA sample tested at $T_A = 25^\circ\text{C}$, T_{MAX} and T_{MIN} per QA test plan QCX0002.
III	QA sample tested per QA test plan QCX0002.
IV	Parameter is guaranteed (but not tested) by Design and Characterization Data.
V	Parameter is typical value at $T_A = 25^\circ\text{C}$ for information purposes only.

Open Loop DC Electrical Characteristics $V_S = \pm 15\text{V}$, $R_L = 200\Omega$, unless otherwise specified

Parameter	Description	Condition	Temp	Min	Typ	Max	Test Level		Units
							EL2030	EL2030C	
V_{OS}	Input Offset Voltage	$V_S = \pm 15\text{V}$	25°C		10	20	I	I	mV
			T_{MIN}, T_{MAX}			30	I	III	mV
		$V_S = \pm 5\text{V}$	25°C		5	10	I	I	mV
			T_{MIN}, T_{MAX}			15	I	III	mV
$\Delta V_{OS}/\Delta T$	Offset Voltage Drift				25		V	V	$\mu\text{V}/^\circ\text{C}$
$+I_{IN}$	+ Input Current	$V_S = \pm 5\text{V}, \pm 15\text{V}$	25°C		5	15	I	I	μA
			T_{MIN}, T_{MAX}			25	I	III	μA
$-I_{IN}$	- Input Current		25°C		10	40	I	I	μA
			T_{MIN}, T_{MAX}			50	I	III	μA
$+R_{IN}$	+ Input Resistance		Full	1.1	2.0		I	II	M Ω
C_{IN}	Input Capacitance		25°C		1		V	V	pF
CMRR	Common Mode Rejection Ratio (Note 2)	$V_S = \pm 5\text{V}, \pm 15\text{V}$	Full	50	60		I	II	dB
-ICMR	Input Current Common Mode Rejection (Note 2)		25°C		5	10	I	I	$\mu\text{A}/\text{V}$
			T_{MIN}, T_{MAX}			20	I	III	$\mu\text{A}/\text{V}$
PSRR	Power Supply Rejection Ratio (Note 3)		Full	60	70		I	II	dB
$+IPSR$	+ Input Current Power Supply Rejection (Note 3)		25°C		0.1	0.5	I	II	$\mu\text{A}/\text{V}$
			T_{MIN}, T_{MAX}			1.0	I	III	$\mu\text{A}/\text{V}$
$-IPSR$	- Input Current Power Supply Rejection (Note 3)		25°C		0.5	5.0	I	II	$\mu\text{A}/\text{V}$
			T_{MIN}, T_{MAX}			8.0	I	III	$\mu\text{A}/\text{V}$

ELANTEC INC

EL2030/EL2030C

120 MHz Current Feedback Amplifier

EL2030/EL2030C

Open Loop DC Electrical Characteristics

 $V_S = \pm 15V$, $R_L = 200\Omega$, unless otherwise specified — Contd.

Parameter	Description	Condition	Temp	Min	Typ	Max	Test Level		Units
							EL2030	EL2030C	
R_{OL}	Transimpedance ($\Delta V_{OUT}/\Delta(-I_{IN})$) $V_{OUT} = \pm 10V$	$V_S = \pm 15V$	25°C	88	150		I	II	V/mA
			T_{MIN}, T_{MAX}	75			I	III	V/mA
	$V_{OUT} = \pm 2.5V$ (Note 6)	$V_S = \pm 5V$	25°C	80	120		I	II	V/mA
			T_{MIN}, T_{MAX}		70		I	III	V/mA
A_{VOL}	Open Loop DC Voltage Gain $V_{OUT} = \pm 10V$	$V_S = \pm 15V$	Full	60	70		I	II	dB
	$V_{OUT} = \pm 2.5V$ (Note 6)	$V_S = \pm 5V$	Full	56	65		I	II	dB
V_O	Output Voltage Swing (Note 6)	$V_S = \pm 15V$	Full	12	13		I	II	V
		$V_S = \pm 5V$	Full	3	3.5		I	II	V
I_{OUT}	Output Current (Note 9)	$V_S = \pm 15V$	Full	60	65		I	II	mA
		$V_S = \pm 5V$	Full	30	35		I	II	mA
R_{OUT}	Output Resistance		25°C		5		V	V	Ω
I_S	Quiescent Supply Current		Full		15	21	I	II	mA
I_{SC}	Short Circuit Current		25°C		85		V	V	mA

Closed Loop AC Electrical Characteristics

 $V_S = \pm 15V$, $A_V = +2$, $R_F = 820\Omega$, $R_G = 820\Omega$ and $R_L = 200\Omega$

Parameter	Description	Condition	Temp	Min	Typ	Max	Test Level		Units
							EL2030	EL2030C	
SR	Slew Rate (Note 7)		25°C	1200	2000		IV	IV	V/ μ s
FPBW	Full Power Bandwidth (Note 4)		25°C	19	31.8		IV	IV	MHz
t_r, t_f	Rise Time, Fall Time	$V_{PP} = 250$ mV	25°C		3		V	V	ns
t_s	Settling Time to 0.25% for 10V step (Note 5)		25°C		40		V	V	ns
ΔG	Differential Gain (Note 8)		25°C		0.01		V	V	% p-p
$\Delta \phi$	Differential Phase (Note 8)		25°C		0.01		V	V	° p-p
eN	Input Spot Noise at 1 kHz $R_G = 101$; $R_F = 909$		25°C		4		V	V	nV/ $\sqrt{Hz}$

Note 1: A heat sink is required to keep the junction temperature below absolute maximum when the output is shorted.

Note 2: $V_{CM} = \pm 10V$ for $V_S = \pm 15V$. For $V_S = \pm 5V$, $V_{CM} = \pm 2.5V$.

Note 3: V_{OS} is measured at $V_S = \pm 4.5V$ and at $V_S = \pm 18V$. Both supplies are changed simultaneously.

Note 4: Full Power Bandwidth is specified based on Slew Rate measurement $FPBW = SR/2\pi V_P$.

Note 5: Settling Time measurement techniques are shown in: "Take The Guesswork Out of Settling Time Measurements", EDN, September 19, 1985. Available from the factory upon request.

Note 6: $R_L = 100\Omega$.


Note 7: $V_O = \pm 10V$, tested at $V_O = \pm 5$. See test circuit.

Note 8: NTSC (3.58 MHz) and PAL (4.43 MHz).







Note 9: For $V_S = \pm 15V$, $V_{OUT} = \pm 10V$. For $V_S = \pm 5V$, $V_{OUT} = \pm 2.5V$.

EL2030/EL2030C**120 MHz Current Feedback Amplifier**

ELANTEC INC

Typical Performance Curves

2030-5

Figure 1. NTSC Video Differential Gain and Phase Test Set-Up

2030-6

ELANTEC INC


EL2030/EL2030C

120 MHz Current Feedback Amplifier

EL2030/EL2030C






1

Typical Performance Curves — Contd.



2030-7

Figure 2. HDTV and Wideband Video Differential Gain and Phase Test Set-Up












2030-8










EL2030/EL2030C

ELANTEC INC

120 MHz Current Feedback Amplifier








Typical Performance Curves — Contd.



Typical Performance Curves — Contd.

EL2030/EL2030C

ELANTEC INC

120 MHz Current Feedback Amplifier**Typical Performance Curves — Contd.****Equivalent Input Noise****Long-Term Output Settling Error vs Time****Long-Term Output Settling Error vs Time, $V_S = \pm 5\text{V}$** **8-Lead Plastic DIP
Maximum Power Dissipation
vs Ambient Temperature****14-Lead CerDIP
Maximum Power Dissipation
vs Ambient Temperature****20-Pad LCC
Maximum Power Dissipation
vs Ambient Temperature****20-Lead SOL
Maximum Power Dissipation
vs Ambient Temperature**

ELANTEC INC


EL2030/EL2030C

120 MHz Current Feedback Amplifier

EL2030/EL2030C

Typical Performance Curves — Contd.


Large Signal Response



$A_V = +1$, $R_F = 1 \text{ k}\Omega$,
 $R_L = 200\Omega$, $V_S = \pm 15\text{V}$

2030-12


Large Signal Response



$A_V = +2$, $R_F = R_G = 820\Omega$,
 $R_L = 200\Omega$, $V_S = \pm 15\text{V}$

2030-13


Large Signal Response



$A_V = +10$, $R_F = 750\Omega$, $R_G = 82\Omega$,
 $R_L = 200\Omega$, $V_S = \pm 15\text{V}$

2030-14


Large Signal Response



$A_V = +2$, $R_F = R_G = 750\Omega$,
 $R_L = 200\Omega$, $V_S = \pm 15\text{V}$

2030-15


Burn-In Circuit



2030-16

ALL PACKAGES USE THE SAME SCHEMATIC.

Test Circuit



2030-17

EL2030/EL2030C

ELANTEC INC

120 MHz Current Feedback Amplifier

Application Information

Product Description

The EL2030 is a current mode feedback amplifier similar to the industry standard EL2020, but with greatly improved AC characteristics. Most significant among these are the extremely wide bandwidth and very low differential gain and phase. In addition, the EL2030 is fully characterized and tested at $\pm 5V$ and $\pm 15V$ supplies.

Power Supply Bypassing/Lead Dressing

It is important to bypass the power supplies of the EL2030 with $0.1 \mu F$ ceramic disc capacitors. Although the lead length is not critical, it should not be more than $\frac{1}{2}$ inch from the IC pins. Failure to do this will result in oscillation, and possible destruction of the part. Another important detail is the lead length of the inputs. The inputs should be designed with minimum stray capacitance and short lead lengths to avoid ringing and distortion.

Differential Gain and Differential Phase

Composite video signals contain intensity, color, hue, timing and audio information in AM, FM, and Phase Modulation. These video signals pass through many stages during their production, processing, archiving and transmission. It is important that each stage not corrupt these signals to provide a "high fidelity" image to the end viewer.

An industry standard way of measuring the distortion of a video component (or system) is to measure the amount of differential gain and phase error it introduces. A 100 mV peak to peak sine wave at 3.58 MHz for NTSC (4.3 MHz for PAL), with 0V DC component serves as the reference. The reference signal is added to a DC offset, shifting the sine wave from 0V to 0.7V which is then applied to the device under test (DUT). The output signal from the DUT is compared to the reference signal. The Differential Gain is a measure of the change in amplitude of the sine wave and is measured in percent. The Differential Phase is a measure of the change in the phase of the sine wave and is measured in degrees. Typically, the maximum positive and negative deviations

are summed to give peak differential gain and differential phase errors. The test setup in Figure 1 was used to characterize the EL2030. For higher than NTSC and PAL frequencies, an alternate Differential Gain and Phase measurement can be made using an HP3577A Network Analyser and the setup shown in Figure 2. The frequency response is normalized to gain or phase with 0V DC at the input. From the normalized value a DC offset voltage is introduced and the Differential Gain or Phase is the deviation from the normalized value.

Video Applications

The video signals that must be transmitted for modest distances are usually amplified by a device such as the EL2030 and carried via coax cable. There are at least two ways to drive cables, single terminated and double terminated.

When driving a cable, it is important to terminate it properly to avoid unwanted signal reflections. Single termination (75Ω to ground at receive end) may be sufficient for less demanding applications. In general, a double terminated cable (75Ω in series at drive end and 75Ω to ground at receive end) is preferred since the impedance match at both ends of the line will absorb signal reflections. However, when double termination is used (a total impedance of 150Ω), the received signal is reduced by half; therefore, the amplifier is usually set at a gain of 2 or higher to compensate for attenuation.

Video signals are 1V peak-peak in amplitude, from sync tip to peak white. There are 100 IRE (0.714V) of picture (from black to peak white of the transmitted signal) and 40 IRE (0.286V) of sync in a composite video signal ($140 \text{ IRE} = 1V$).

For video applications where a gain of two is used (double termination), the output of the video amplifier will be a maximum of 2V peak-peak. With $\pm 5V$ power supply, the EL2030 output swing of 3.5V is sufficient to satisfy the video output swing requirements. The EL2030 can drive two double terminated coax cables under these conditions. With $\pm 15V$ supplies, driving four double terminated cables is feasible.

ELANTEC INC

EL2030/EL2030C

120 MHz Current Feedback Amplifier

EL2030/EL2030C

Video Applications — Contd.


Although the EL2030's video characteristics (differential gain and phase) are impressive with $\pm 5V$ supplies at NTSC and PAL frequencies, it can be optimized when the supplies are increased to $\pm 15V$, especially at 30 MHz HDTV applications. This is primarily due to a reduction in internal parasitic junction capacitance with increased power supply voltage.

The following table summarizes the behavior of the EL2030 at $\pm 5V$ and $\pm 15V$ for NTSC. In ad-

dition, 30 MHz HDTV data is included. Refer to the differential gain and phase typical performance curves for more data.

$\pm V_s$	Rload	A_v	Δ Gain	Δ Phase	Comments
15V	75 Ω	1	0.02%	0.03°	Single terminated
15V	150 Ω	1	0.02%	0.02°	Double terminated
5V	150 Ω	1	0.05%	0.02°	Double terminated
15V	75 Ω	2	0.02%	0.08°	Single terminated
15V	150 Ω	2	0.01%	0.02°	Double terminated
5V	150 Ω	2	0.03%	0.09°	Double terminated
15V	150 Ω	2	0.05%	0.02°	HDTV, Double terminated

Equivalent Circuit



2030-18

1

EL2030/EL2030C

120 MHz Current Feedback Amplifier

ELANTEC INC

EL2030 Macromodel

* Revision A. March 1992

* Enhancements include PSRR, CMRR, and Slew Rate Limiting

* Connections: + input

*		- input			
*			+ Vsupply		
*			- Vsupply		
*				output	
*					

.subckt M2030 3 2 7 4 6

* Input Stage

e1 10 0 3 0 1.0
vis 10 9 0V
h2 9 12 vxx 1.0
r1 2 11 50
l1 11 12 48nH
iinp 3 0 5μA
iinm 2 0 10μA
r12 3 0 2Meg

* Slew Rate Limiting

h1 13 0 vis 600
r2 13 14 1K
d1 14 0 dclamp
d2 0 14 dclamp

* High Frequency Pole

*e2 30 0 14 0 0.001666666666
l3 30 17 0.5μH
c5 17 0 1pF
r5 17 0 500

* Transimpedance Stage

g1 0 18 17 0 1.0
rol 18 0 150K
cdp 18 0 2.8pF

* Output Stage

q1 4 18 19 qp
q2 7 18 20 qn
q3 7 19 21 qn
q4 4 20 22 qp
r7 21 6 4
r8 22 6 4

ELANTEC INC

EL2030/EL2030C
120 MHz Current Feedback Amplifier

EL2030/EL2030C

EL2030 Macromodel — Contd.

ios1 7 19 2.5mA

ios2 20 4 2.5mA

*

* Supply Current

*

ips 7 4 9mA

*

* Error Terms

*

ivos 0 23 5mA

vxx 23 0 0V

e4 24 0 6 0 1.0

e5 25 0 7 0 1.0

e6 26 0 4 0 1.0

r9 24 23 3K

r10 25 23 1K

r11 26 23 1K

*

* Models

*

.model qn npn (is=5e-15 bf=100 tf=0.1nS)

.model qp pnp (is=5e-15 bf=100 tf=0.1nS)


.model dclamp d(is=1e-30 ibv=0.266 bv=3.7 n=4)

.ends

1

EL2030/EL2030C**120 MHz Current Feedback Amplifier**

ELANTEC INC

EL2030 Macromodel — Contd.

2030-19