

DESIGNED TO UL/CSA STANDARD

5 x 20 mm Medium Acting Fuse



- Designed to UL/ CSA/ANCE 248 Standard.
- Available in Cartridge, Axial and Radial Lead Format.
- Available in ratings of 1A to 6.3A.

ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Ampere Rating	Opening Time
110%	1–3.5	4 hours, Minimum
	4–6.3	1 hour, Minimum
135%	1–6.3	1 hour, Maximum
200%	1–6.3	3 seconds, Maximum

AGENCY APPROVALS: Listed by Underwriters Laboratories and Certified by CSA. Approved by MITI.

PACKAGING: For Axial Leads add packaging suffix XE. For Radial Leads add packaging suffix XW. For tape and reel options contact Littelfuse.

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating	Nominal Resistance Cold Ohms	Nominal Melting I ² t A ² Sec
0233 001	1	250	0.18	2.03
0233 1.25	1.25	250	0.13	3.48
0233 01.6	1.6	250	0.088	6.31
0233 002	2	250	0.068	10.2
0233 02.5	2.5	250	0.052	17.5
0233 003	3	250	0.043	27.0
0233 3.15	3.15	250	0.038	30.6
0233 03.5	3.5	250	0.034	37.3
0233 004	4	125	0.032	53.0
0233 005	5	125	0.022	92.4
0233 006	6	125	0.018	135
0233 06.3	6.3	125	0.017	156

