




RoHS 2002/95/EC Compliant

TECHNICAL DATA SHEET



Thermoelectric Cooler RC6-2.5

Performance Values

| | | |
|----------------------------------|------|------|
| Hot Side Temperature (°C) | 27°C | 50°C |
| Δ Tmax (°C-dry N ₂): | 65 | 73 |
| Qmax (watts): | 13 | 14 |
| I _{max} (amps): | 2.5 | 2.5 |
| V _{max} (vdc): | 8.2 | 9.2 |
| AC Resistance (ohms): | 2.8 | --- |



Mechanical Characteristics



Ceramic Material: Alumina (AC)

Dimensions in [] are millimeters

Ordering Options

| Model Number | Description |
|--------------|-------------------------|
| RC6-2.5-01 | Base Model w/ leads |
| RC6-2.5-01L | Lapped Model |
| RC6-2.5-01S | Sealed Model |
| RC6-2.5-01LS | Lapped and Sealed Model |



Features

- **RoHS 2002/95/EC compliant**
- Solid-state reliability.
- Built with high temperature solder with the ability to withstand higher assembly processing temperatures for short periods of time (<160°C).
- Superior nickel diffusion barriers on elements
- High strength for rugged environment.
- Porched configuration for enhanced leadwire strength
- RTV sealing available (Optional)
- Lapped option available for multiple module applications.



Performance Curves

Environment: One atmosphere dry nitrogen



For performance information in a vacuum or with hot side temperatures other than 27°C or 50°C, consult one of our Applications Engineers.

Installation

Recommended mounting methods: Bonding with thermal epoxy or soldering with metallized ceramics. For additional information, please refer to our TEC Installation Guide.

Operation Cautions

For maximum reliability, storage and operation below 85°C in a non-condensing environment is recommended. To minimize thermal stress, use linear/proportional temperature control or a similar method rather than an ON/OFF method.

Addresses

Marlow Industries, Inc.
10451 Vista Park Road
Dallas Texas 75238-1645
214-340-4900 (tel)
214-341-5212 (fax)
www.marlow.com

Marlow Industries Europe
Aberdeen House, South Road
Haywards Heath
West Sussex RH164NG UK
+44 (0)1444-443404 (tel)
+44 (0)1444-443334(fax)

Marlow Industries Japan
1-1-8-401
Uehara, Shibuya-ku
Tokyo, Japan 151-0064
+81 (3) 5454-5280 (tel)
+81 (3) 5454-5281 (fax)