




Technical Data Sheet

C18 CONNECTORS FOR USE WITH SUPERSCREEN CONDUITS


C18 MALE CONNECTOR



MATL: BRASS TO BS2874

CONDUIT SIZE mm	THREAD SIZE	ORDERING CODE	DIMENSIONS (mm)					NATO STOCK NUMBER
			THREAD DIA. A	MIN. BORE B	ACROSS FLATS C	THREAD LENGTH D	NOM. LENGTH E	
16	16mm	BGM 0303	16.0	11.88	24.0	12.5	36.0	5975-09-885-8881
20	20mm	BGM 0404	20.0	13.88	30.0	14.0	39.0	5975-09-593-8340
25	25mm	BGM 0505	25.0	20.78	38.0	17.0	48.0	5975-09-019-0886
32	32mm	BGM 0606	32.0	23.88	48.0	19.0	57.0	5975-09-127-4389
40	40mm	BGM 0707	40.0	22.65	58.3	18.9	66.0	.
50	50mm	BGM 0808	50.0	45.35	65.5	22.2	70.0	.
63	63mm	BGM 0909	63.0	56.65	80.0	23.4	84.0	.

C18 FEMALE CONNECTOR



MATL: BRASS TO BS2874

CONDUIT SIZE mm	THREAD SIZE	ORDERING CODE	DIMENSIONS (mm)					NATO STOCK NUMBER
			THREAD DIA. A	MIN. BORE B	ACROSS FLATS C	THREAD LENGTH D	NOM. LENGTH E	
16	16mm	BTM 0303	16.0	14.01	24.0	13.0	36.0	5975-09-375-3248
20	20mm	BTM 0404	20.0	18.01	30.0	14.0	39.0	5975-09-521-3808
25	25mm	BTM 0505	25.0	23.01	38.0	17.0	48.0	5975-09-701-3495
32	32mm	BTM 0606	32.0	30.01	48.0	19.0	57.0	5975-09-039-3051
40	40mm	BTM 0707	40.0	28.01	58.3	22.4	66.0	.
50	50mm	BTM 0808	50.0	48.01	65.5	23.2	70.0	.
63	63mm	BTM 0909	63.0	61.01	80.0	25.5	84.0	.

METRIC THREADS TO BS 8053

FOR SCREENING PROPERTIES SEE TECHNICAL DATA SHEET No. 810088

IP RATING WITH KOPEX SUPERSCREEN CONDUITS

OPERATING TEMPERATURE RANGE
COMPLIANCE WITH STANDARDS

IP 67 (NO INGRESS OF TALCUM POWDER UNDER VACUUM AND NO INGRESS OF
AT 1m DEPTH FOR 30 MINUTES)
-40 TO +130 DEGREES CELSIUS DEPENDING ON CONDUIT TYPE
ACCEPTED BY LLOYDS REGISTER OF SHIPPING FOR SUITABLE APPLICATIONS

FITTING INSTRUCTIONS INCLUDED WITH PRODUCT AND AVAILABLE ON REQUEST - LEAFLET No. 808889

THE COMPANY'S POLICY IS ONE OF CONTINUAL IMPROVEMENT AND IT RESERVES THE RIGHT TO CHANGE SPECIFICATIONS AT ANY TIME
WITHOUT PRIOR NOTICE.

810X

KOPEX INTERNATIONAL LIMITED 180 Bath Road, Slough, Berks., SL14AR, England. Tel: (01753) 534921, Telex: 848347, Fax: (01753) 6

TOTAL P.03