

1015 MP

15 Watt, 50 Volts, Class C
Avionics 1025 - 1150 MHz


GENERAL DESCRIPTION

The 1015 MP is a COMMON BASE bipolar transistor. It is designed for pulsed systems in the frequency band 1025-1150 MHz. The device has gold thin-film metallization for proven highest MTTF. The transistor includes input prematch for broadband capability. Low thermal resistance package reduces junction temperature, extends life.

ABSOLUTE MAXIMUM RATINGS

Maximum Power Dissipation @ 25°C ²		50 Watts Pk
Maximum Voltage and Current		
BVces	Collector to Emitter Voltage	65 Volts
BVebo	Emitter to Base Voltage	3.5 Volts
Ic	Collector Current	1.0 Amps Pk
Maximum Temperatures		
Storage Temperature		- 65 to + 150°C
Operating Junction Temperature		+ 200°C

CASE OUTLINE 55FU, STYLE 1



ELECTRICAL CHARACTERISTICS @ 25 °C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Pout	Power Out	F= 1025-1150 MHz	15			Watts
Pin	Power Input	Vcc = 50 Volts			1.5	Watts
Pg	Power Gain	PW = 10 μsec	10	11		dB
ηc	Efficiency	DF = 1%		40		%
VSWR	Load Mismatch Tolerance	F = 1090 MHz			20:1	

BVebo	Emitter to Base Breakdown	Ie = 5 mA	3.5			Volts
BVces	Collector to Emitter Breakdown	Ic = 15mA	65			Volts
Hfe	DC Current Gain to Emitter	Vce = 5V, Ic = 100 mA	20			
Cob	Output Capacitance	Vcb = 50 V, f = 1 MHz		5.0	7.5	pF
θjc ²	Thermal Resistance	Pulsed			3.5	°C/W

Note 1: At rated output power and pulse conditions

2: At rated pulse conditions

Initial Issue June, 1995

GHz TECHNOLOGY INC. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. GHz RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.