

NEC[®]**PNP SILICON HIGH
FREQUENCY TRANSISTOR**T-31-17
**NE88900
NE88912
NE88933
NE88935****FEATURES**

- **PNP COMPLEMENT TO NE327**
- **HIGH GAIN BANDWIDTH PRODUCT:** $f_T = 4$ GHz
- **HIGH GAIN:** 18 dB at 500 MHz
- **LOW NOISE:** 2 dB at 500 MHz
- **RELIABLE:** Gold Metallization and Rugged Packages

DESCRIPTION AND APPLICATIONS

The NE889 series of PNP silicon transistors is designed for ultra high speed current mode switching applications and microwave amplifiers up to 2 GHz. The NE889 is available in several package styles and in chip form (NE88900). The NE88935 is an economical metal ceramic stripline version which features low parasitic elements and is ideal for low cost hybrid circuits. Reliability is assured by NEC's stringent production controls, which are patterned after MIL-S-19500 and Pt/Si-Ti-Pt-Au metallization.

PERFORMANCE SPECIFICATIONS ($T_A = 25^\circ\text{C}$)

PART NUMBER EIAJ ¹ REGISTERED NUMBER PACKAGE OUTLINE			NE88900 00 (CHIP)			NE88912 2SA1228 12 (TO-72)			NE88933 2SA1424 33 (MINI-MOLD)			NE88935 2SA1223 35 (MICRO-X)		
SYMBOLS	PARAMETERS AND CONDITIONS	UNITS	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX
f_T	Gain Bandwidth Product at $V_{CE} = -5$ V, $I_C = -15$ mA	GHz		4			4		3	4		3	4	
$ S_{21E} ^2$	Insertion Power Gain at $V_{CE} = -10$ V, $I_C = -15$ mA, $f = 0.5$ GHz $f = 1$ GHz $f = 2$ GHz	dB dB dB					13 7.2 2		6	8		8	16 10 4.2	
NF _{MIN}	Minimum Noise Figure ² at $V_{CE} = -10$ V, $I_C = -3$ mA, $f = 0.2$ GHz $f = 0.5$ GHz $f = 1$ GHz	dB dB dB		2.5			2 2.5 3			3	4		1.8 2 2.5	3.5 4
MAG	Maximum Available Gain ³ at $V_{CE} = -10$ V, $I_C = -15$ mA, $f = 0.5$ GHz $f = 1$ GHz $f = 2$ GHz	dB dB dB		12			14.5 9 3			9.3			18 12 7	

Notes:

1. Electronic Industrial Association of Japan.
2. Output and Input are tuned for minimum noise figure.
3. Maximum Available Gain (MAG) is calculated from the device S-Parameters using the following equation,

$$\text{MAG} = |S_{21E}|^2 \cdot \frac{1}{1 - |S_{11E}|^2} \cdot \frac{1}{1 - |S_{22E}|^2}$$

NE88900, NE88912, NE88933, NE88935**ELECTRICAL CHARACTERISTICS** ($T_A = 25^\circ\text{C}$)

PART NUMBER EIAJ ¹ REGISTERED NUMBER PACKAGE OUTLINE			NE88900 00 (CHIP)			NE88912 2SA1228 12 (TO-72)			NE88933 2SA1424 33 (MINI-MOLD)			NE88935 2SA1223 35 (MICRO-X)		
SYMBOLS	PARAMETERS AND CONDITIONS	UNITS	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX
I _{CEO}	Collector Cutoff Current at $V_{CB} = -10\text{ V}$, $I_E = 0$	μA			-0.1			-0.1			-0.1			-0.1
I _{EB0}	Emitter Cutoff Current at $V_{EB} = -2\text{ V}$, $I_C = 0$	μA			-0.1			-0.1			-0.1			-0.1
h _{FE}	Forward Current Gain at $V_{CE} = -10\text{ V}$, $I_C = -15\text{ mA}$		20	90	200	20	90	200	20	90	200	20	90	200
C _{CB}	Collector to Base Capacitance* at $V_{CB} = -5\text{ V}$, $I_E = 0\text{ mA}$, $f = 1\text{ MHz}$	pF		1.2	1.5		1.2	1.5		1.1	3		1	1.5
R _{TH}	Thermal Resistance (Junction-to-Case)	$^\circ\text{C/W}$			31			500			700			620
P _T	Total Power Dissipation	mW						300			200			250



Notes:







- Electronic Industrial Association of Japan.
- Capacitance is measured with emitter and case connected to the guard terminal at the bridge.







ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$)

SYMBOLS	PARAMETERS	UNITS	RATINGS
V _{CEO}	Collector to Base Voltage	V	-20
V _{CE0}	Collector to Emitter Voltage	V	-12
V _{EB0}	Emitter to Base Voltage	V	-3
I _C	Collector Current	mA	-50
T _J	Junction Temperature	$^\circ\text{C}$	200
T _{STG}	Storage Temperature	$^\circ\text{C}$	-65 to +200*


*The NE88935 Grade D (Industrial) version has a T_{STG} of -65 to +150 $^\circ\text{C}$.

TYPICAL DEVICE CHARACTERISTICS ($T_A = 25^\circ\text{C}$)


OUTLINE DIMENSIONS (Units in mm)**NE88900 (CHIP)**Chip Thickness: 160 μ m TYP**OUTLINE 33 (SOT-23)****OUTLINE 12 (TO-72)****OUTLINE 35 (MICRO-X)****TYPICAL PERFORMANCE CHARACTERISTICS** ($T_A = 25^\circ\text{C}$)**GAIN BANDWIDTH vs. COLLECTOR CURRENT****DEVICE CAPACITANCE**

TYPICAL PERFORMANCE CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

TYPICAL COMMON EMITTER SCATTERING PARAMETERS



NE88900
Coordinates in Ohms
Frequency in GHz
(VCE = -10 V, IC = -30 mA)



S-MAGN AND ANGLES:

VCE = -10 V, IC = -5 mA

FREQUENCY (MHz)

S11

S21

S12

S22

100

.75 -39

11.69 154

.021 78

.90 -21

500

.55 -128

5.34 103

.097 44

.40 -64

1000

.49 -155

2.89 84

.128 47

.27 -74

1500

.49 -173

2.03 72

.160 48

.20 -80

2000

.53 176

1.60 63

.195 51

.19 -89

VCE = -10 V, IC = -10 mA

100

.60 -60

17.27 146

.016 71

.82 -30

500

.53 -149

6.10 98

.066 50

.28 -78

1000

.50 -168

3.21 82

.107 57

.19 -91

1500

.51 178

2.24 71

.146 58

.14 -99

2000

.55 170

1.74 63

.186 59

.13 -108

VCE = -10 V, IC = -20 mA

100

.48 -88

21.54 138

.007 70

.72 -38

500

.54 -162

6.39 94

.045 58

.21 -87

1000

.51 -175

3.31 80

.093 64

.15 -99

1500

.53 173

2.29 70

.139 63

.10 -105

2000

.57 166

1.77 62

.182 65

.11 -115

VCE = -10 V, IC = -30 mA

100

.44 -105

22.51 135

.004 78

.68 -39

500

.55 -166

6.25 92

.044 61

.18 -84

1000

.53 -178

3.22 79

.090 68

.14 -92

1500

.54 172

2.22 69

.134 66

.09 -94

2000

.59 165


1.71 61

.177 66


.11 -106

NE88900, NE88912, NE88933, NE88935

TYPICAL COMMON EMITTER SCATTERING PARAMETERS



NE88912
Coordinates in Ohms
Frequency in GHz
($V_{CE} = -10\text{ V}$, $I_C = -30\text{ mA}$)



S-MAGN AND ANGLES:

 $V_{CE} = -10\text{ V}$, $I_C = -5\text{ mA}$

FREQUENCY (MHz)

	S11		S21		S12		S22	
100	.65	-40	10.20	141	.035	70	.85	-20
500	.30	-114	3.95	88	.112	59	.55	-41
1000	.20	-154	2.23	62	.178	56	.49	-54
1500	.16	-173	1.62	41	.237	49	.51	-72
2000	.12	-164	1.30	21	.281	37	.57	-89

 $V_{CE} = -10\text{ V}$, $I_C = -10\text{ mA}$

	S11		S21		S12		S22	
100	.49	-51	13.51	132	.031	73	.78	-23
500	.22	-128	4.25	83	.106	64	.49	-38
1000	.17	-166	2.34	60	.182	59	.46	-51
1500	.14	-179	1.70	40	.244	50	.49	-69
2000	.09	-167	1.36	21	.290	38	.54	-87



 $V_{CE} = -10\text{ V}$, $I_C = -20\text{ mA}$

	S11		S21		S12		S22	
100	.36	-65	14.73	123	.027	72	.70	-24
500	.19	-145	4.11	79	.103	67	.49	-34
1000	.17	-179	2.25	57	.179	61	.47	-49
1500	.14	-166	1.63	37	.246	52	.50	-68
2000	.08	-179	1.29	17	.287	39	.57	-87

 $V_{CE} = -10\text{ V}$, $I_C = -30\text{ mA}$

	S11		S21		S12		S22	
100	.30	-80	13.70	119	.021	70	.68	-22
500	.22	-159	3.62	77	.099	69	.51	-31
1000	.21	-168	1.99	54	.174	63	.51	-49
1500	.18	-150	1.44	34	.238	54	.54	-68
2000	.10	-140	1.15	14	.282	42	.59	-89

TYPICAL COMMON EMITTER SCATTERING PARAMETERS



NE88935
Coordinates in Ohms
Frequency in GHz
(VCE = -10 V, IC = -20 mA, Zo = 50 Ω)

S-MAGN AND ANGLES:

VCE = -10 V, IC = -5 mA

FREQUENCY (MHz)

S11

S21

S12

S22

500	.46	-133	5.08	104	.11	40	.30	-56
1000	.54	-170	2.82	72	.14	29	.25	-96
2000	.56	153	1.51	38	.19	22	.19	-133
3000	.59	130	1.05	12	.24	10	.23	-168

VCE = -10 V, IC = -10 mA

500	.50	-160	6.11	97	.08	43	.18	-76
1000	.57	177	3.12	70	.11	38	.19	-117
2000	.59	147	1.63	38	.17	31	.16	-156
3000	.62	126	1.12	14	.22	18	.22	175

VCE = -10 V, IC = -20 mA

500	.56	-176	6.53	93	.06	50	.10	-95
1000	.59	170	3.19	68	.09	47	.15	-128
2000	.62	144	1.65	38	.16	38	.15	-163
3000	.65	125	1.12	13	.21	24	.21	172

VCE = -10 V, IC = -30 mA

500	.59	178	6.44	91	.06	54	.07	-94
1000	.60	168	3.10	67	.09	51	.14	-122
2000	.63	143	1.59	37	.16	40	.14	-157
3000	.66	124	1.07	12	.21	26	.21	178