

Features

- Settling time for 10V swings to 0.1% of 90 ns; to 0.01% of 200 ns
- Unity gain bandwidth—50 Mhz
- High slew rate—700 V/ μ s
- Large power bandwidth—5 MHz
- Large open loop gain—100 dB
- Low input offset voltage—1 mV
- Low input bias current—250 nA
- Inputs tolerant of overload
- Uses standard ± 5 V to ± 15 V supplies
- Output tolerant of load capacitance
- MIL-STD-883 Rev. C Compliant

Applications

- 12-bit DAC output amplifiers
- Fast-settling instrumentation amplifiers
- Driving 12-bit A/D converters
- Radar systems
- Replacement of costly hybrids

Ordering Information

Part No.	Temp. Range	Pkg.	Outline*
EL2028CJ	0°C to +75°C	CerDIP	MDP0014
EL2028CN	0°C to +75°C	P-DIP	MDP0031
EL2028J	-55°C to +125°C	CerDIP	MDP0014
EL2028J/883B	-55°C to +125°C	CerDIP	MDP0014

General Description

The EL2028 monolithic operational amplifier is designed for extremely fast and clean settling with millivolt accuracy. It settles to 0.01% from a 10V step in 200 ns but has no thermal tail nor input slew overload penalties. The EL2028 is a true operational amplifier with low bias currents and large voltage gain, and is compensated for unity gain feedback.


The inputs of the EL2028 are capable of 26V of differential overload without damage nor increased bias current. The input circuitry does not exhibit slew aberrations even for signals beyond the output slew limit of 700 V/ μ s. The output is capable of large currents and is current-limited, and can drive as much as 100 pF stably. Even under capacitive loading the amplifier delivers a -3 dB bandwidth of 50 MHz.

The EL2028 can be used in circuits where current-feedback amplifiers were previously required for adequate speed, while offering at least a tenfold accuracy improvement.

Elantec's EL2028/883B complies with MIL-STD-883 Revision C in all aspects, including burn-in at 125°C. Elantec's facilities comply with MIL-I-45208A and other applicable quality specifications. For information on Elantec's military processing, see the Elantec document QRA-2: *Elantec's Military processing-Monolithic Products*.

Connection Diagram

14-Pin DIP Package



Top View

2028-1

EL2028/EL2028C

0.01% 200 ns Unity Gain Stable Operational Amplifier

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$)

Voltage between V^+ and V^-	35V	Operating Ambient Temperature Range	
Voltage at GND Pin	V^+ to V^-	EL2028	-55°C to $+125^\circ\text{C}$
Voltage between $-IN$ and $+IN$ Pins	26V	EL2028C	0°C to $+75^\circ\text{C}$
Voltage at $-IN$ or $+IN$ Pins	V^+ to V^-	Operating Junction Temperature	
Output Current	50 mA (Peak)	CerDIP	175°C
	30 mA (Continuous)	Plastic DIP	150°C
Current into $+IN$, $-IN$, GND, or Balance Pins	5 mA	Lead Temperature (Soldering 5 seconds)	300°C
Internal Power Dissipation	See Curves	Storage Temperature Range	-65°C to $+150^\circ\text{C}$

Important Note:

All parameters having Min/Max specifications are guaranteed. The Test Level column indicates the specific device testing actually performed during production and Quality inspection. Elantec performs most electrical tests using modern high-speed automatic test equipment, specifically the LTX77 Series system. Unless otherwise noted, all tests are pulsed tests, therefore $T_J = T_C = T_A$.

Test Level

Test Procedure

- I 100% production tested and QA sample tested per QA test plan QCX0002.
- II 100% production tested at $T_A = 25^\circ\text{C}$ and QA sample tested at $T_A = 25^\circ\text{C}$, T_{MAX} and T_{MIN} per QA test plan QCX0002.
- III QA sample tested per QA test plan QCX0002.
- IV Parameter is guaranteed (but not tested) by Design and Characterization Data.
- V Parameter is typical value at $T_A = 25^\circ\text{C}$ for information purposes only.

DC Electrical Characteristics $V_S = \pm 15\text{V}$; $R_L = 1\text{k}\Omega$; $T_A = 25^\circ\text{C}$ unless otherwise specified

Parameter	Description	Temp	Min	Typ	Max	EL2028 Test Level	EL2028C Test Level	Units
V_{OS}	Input Offset Voltage EL2028	25°C		0.25	2.0	I		mV
	EL2028C	25°C		0.25	1.0		I	mV
	EL2028	Full			3.0	I		mV
	EL2028C	Full			3.0		III	mV
TCV_{OS}	Average Offset Voltage Drift	Full		3		V	V	$\mu\text{V}/^\circ\text{C}$
I_B	Input Bias Current	25°C		250	500	I	I	nA
		Full			800	I	III	nA
I_{OS}	Input Offset Current	25°C		120	250	I	I	nA
		Full			350	I	III	nA
$R_{IN, DIFF}$	Input Differential Resistance	25°C		10		V	V	$\text{M}\Omega$
$R_{IN, COMM}$	Input Common-Mode Resistance	25°C		120		V	V	$\text{M}\Omega$
C_{IN}	Input Capacitance	25°C		2		V	V	pF
V_{CM}	Common-Mode Input Range	Full	± 11	± 12		I	II	V
E_{IN}	Input Noise Voltage ($f = 1\text{ kHz}$, $R_G = 0\Omega$)	25°C		10		V	V	$\text{nV}/\sqrt{\text{Hz}}$
A_{VOL}	Large Signal Voltage Gain ($V_O = \pm 10\text{V}$)	25°C	45	80		I	I	V/mV
		Full	20			I	III	V/mV
CMRR	Common-Mode Rejection Ratio (Note 1)	Full	80	95		I	II	dB
PSRR	Power-Supply Rejection Ratio (Note 2)	Full	80	95		I	II	dB
V_O	Output Voltage Swing	Full	± 11	± 12		I	II	V
I_O	Output Current (Note 3)	Full	± 25	± 50		I	II	mA
I_S	Supply Current	Full		14	17	I	II	mA

EL2028/EL2028C

0.01% 200 ns Unity Gain Stable Operational Amplifier

EL2028/EL2028C

AC Electrical Characteristics

$V_S = \pm 15V$; $R_L = 1\text{ k}\Omega$; $C_L = 25\text{ pF}$; $T_A = 25^\circ\text{C}$; Unless otherwise specified

Parameter	Description	Min	Typ	Max	EL2028 Test Level	EL2028C Test Level	Units
BW	Unity Gain -3 dB Bandwidth (Note 4)		50		V	V	MHz
GBW	Gain-Bandwidth Product (Note 4)		25		V	V	MHz
FPBW	Full-Power Bandwidth ($V_O = \pm 10V$)		5		V	V	MHz
SR	Slew Rate ($V_O = \pm 10V$)		700		V	V	V/ μs
t_r	Rise Time (Notes 4, 5)		8		V	V	ns
O_S	Overshoot (Notes 4, 5)		10		V	V	%
t_s	Settling Time (Note 4) to 0.1% 10V Step to 0.01%		90 200		V V	V V	ns ns

Note 1: Two tests are performed with $V_{CM} = 0V$ to $-11V$ and $V_{CM} = 0V$ to $11V$.


Note 2: Two tests are performed with $V_+ = 15V$, V_- changed from $-5V$ to $-15V$; $V_- = -15V$, V_+ changed from $5V$ to $15V$.

Note 3: The inputs are overdriven by $\pm 15V$ and the output $R_L = 100\Omega$.

Note 4: A $100\Omega + 100\text{ pF}$ snubber is used to load the output—see Applications section.


Note 5: $V_{IN} = 100\text{ mV}$ peak-to-peak.

Test Circuit




2028-2

Burn-In Circuit




2028-3


1

EL2028/EL2028C**0.01% 200 ns Unity Gain Stable Operational Amplifier****Typical Performance Curves****Input Bias Current vs
Common-Mode Voltage**


2028-4

**Input Bias Current
vs Temperature**


2028-5

**Voltage Gain
vs Temperature**


2028-6

**Supply Current vs
Supply Voltage**

2028-7


**Common-Mode Rejection
Ratio vs Frequency**

2028-8


**Power Supply Rejection
Ratio vs Frequency**

2028-9


Typical Performance Curves — Contd.




2028-10




2028-11




2028-12




2028-13




2028-14




2028-15

EL2028/EL2028C**0.01% 200 ns Unity Gain Stable Operational Amplifier****Typical Performance Curves — Contd.****Small-Signal Pulse Response—No Snubber**


2028-16

**Small-Signal Pulse Response—
100Ω + 100 pF Snubber**


2028-17

Large-Signal Pulse Response—No Snubber


2028-18

**Settling Time vs
Output Swing**

2028-19




2028-20




2028-21

Typical Performance Curves — Contd.



2028-22



2028-23

Applications Information

The EL2028 is a conventional high-accuracy operational amplifier with the speeds and bandwidths normally found only in current-feedback amplifiers. All the usual op amp configurations may be applied since the device is unity gain stable. The EL2028 will work well with a wide variety of loads and power supplies.

Power Supplies and Grounding

As with all high-frequency amplifiers, it is necessary to bypass the supply pins to ground close to the part. 0.01 μF capacitors of the ceramic type will suffice, although tantalum capacitors of any available value are perhaps the best choice. Tantalum capacitors have low series inductance yet are not high-Q in nature, helping to damp supply variations caused by load currents.

The EL2028 will work well from $\pm 5\text{V}$ supplies, with the input and output swings reduced to $\pm 1\text{V}$ over temperature, $\pm 2\text{V}$ nominally. At higher supplies, the part's dissipation must be maintained within package limits when the device and any load-related dissipations are calculated. Clip-on heatsinks are effective in reducing die temperature. Note that the device will warm approximately 36°C upon power-up; any accurate DC tests should either be done within 1 second or after 1 minute of turn-on at maximum supplies.

Although the part is current-limited at its output, that current can cause enough dissipation such that the maximum die temperature specification will be exceeded.

The EL2028 has a unique ground pin connection. The compensation capacitor returns to this pin rather than ground to aid in noise and settling characteristics. The input bias current compensation circuitry is also referred to this pin, so it cannot be connected to a voltage outside the input common-mode range.

Input Circuitry

The input appears as a high impedance even when the amplifier is overloaded. The input will not be damaged by transient nor continuous overloads, although an additional supply current of 2 mA per volt of overload will result. This should be considered in the device thermal calculations.

Like many other high-speed amplifiers, the input circuitry can resonate or even oscillate when driven by high-impedance inputs. The worst situation is when the device looks into an unterminated coaxial cable or a large inductance. Normal circuit interconnects cause no trouble. If the source impedance is difficult, a snubber similar to the output snubber can be added in parallel with the input.

EL2028/EL2028C

0.01% 200 ns Unity Gain Stable Operational Amplifier

Applications Information — Contd.

High values of feedback impedance can sacrifice loop stability. The main point is that the pole caused by any stray capacitance and the feedback network impedance should be several times greater than the EL2028's gain-bandwidth product divided by the noise gain of the feedback loop. If this condition cannot be met, the feedback resistor can have a small (1 pF–2 pF) capacitor in parallel to improve closed-loop phase margin.

Output Circuitry

The output circuitry was designed to deliver more current than the device can safely continuously output so that the transient currents caused by fast slews can be developed. For instance, a 50 pF load will draw 35 mA in response to a 700 V/ μ s output transient. The snubber network will draw similar currents, and it may not be useable if the amplifier is called upon to deliver

large outputs continuously at high frequencies. In any event, the device is rated at 30 mA continuously.

The output circuit will resonate with capacitive loads if it is not damped. The output impedance of all amplifiers is approximately modeled as an inductor in series with a DC resistance. The equivalent component values for the EL2028 are 300 nH and 20 Ω . To reduce the output stage resonance with capacitive loads, the snubber network can be added to de-Q the load. The EL2028 will comfortably drive 100 pF with the snubber values of 100 pF and 100 Ω .

Offset Adjust

To effect input offset voltage adjustment, a 10k to 100k potentiometer is connected to the balance pins with the wiper connected to V $-$. ± 2.8 mV of adjustment is possible.

EL2028/EL2028C

0.01% 200 ns Unity Gain Stable Operational Amplifier

EL2028/EL2028C

EL2028 Macromodel

```
* Connections:      + input
*                   |
*                   | - input
*                   |
*                   | + Vsupply
*                   |
*                   | - Vsupply
*                   |
*                   | output
*                   |
.subckt M2028      5      4      11      6      10
```

* Input Stage

```
il 37 6 2mA
r1 36 37 2K
r2 38 37 2K
r3 11 30 2K
r4 11 39 2K
q1 30 5 36 qn
q2 39 4 38 qna
e1 33 0 39 30 1
r5 33 0 1Meg
```

* Compensation Section

```
ga 0 34 33 0 1m
rh 34 0 80Meg
ch 34 0 5pF
rc 34 40 100
cc 40 0 1pF
```

* Poles

```
ep 41 0 40 0 1
r6 41 42 150
c1 42 0 10pF
r7 42 43 150
c2 43 0 10pF
```

* Output Stage

```
i2 11 50 1.25mA
i3 51 6 1.25mA
q3 6 43 50 qp
q4 11 43 51 qn
q5 11 50 52 qn
q6 6 51 53 qp
r8 52 10 5
r9 10 53 5
```


* Power Supply Current

```
ips 11 6 9mA
```

* Models

```
.model qn npn(is = 800e - 18 bf = 2000 tf = 0.1nS)
.model qna npn(is = 824e - 18 bf = 2700 tf = 0.1nS)
.model qp pnp(is = 800e - 18 bf = 260 tf = 0.1nS)
.ends
```

1

EL2028/EL2028C**0.01% 200 ns Unity Gain Stable Operational Amplifier****EL2028 Macromodel — Contd.**

2028-24