


角形 Square Type

□ 5.3 mm×1.8 mm 3連 3-Element Array

Type No.	Lighting Color
LN03202P	Red
LN03302P	Green
LN03402P	Amber









絶対最大定格 Absolute Maximum Ratings (Ta=25 °C)

Lighting Color	P _D (mW)	I _F (mA)	I _{FP} (mA)*	V _R (V)	T _{opr} (°C)	T _{stg} (°C)
Red	70	25	150	4	-25~+85	-30~+100
Green	90	30	150	4	-25~+85	-30~+100
Amber	90	30	150	4	-25~+85	-30~+100

★ I_{FP}の条件は, duty 10%, Pulse width 1 msec. The condition of I_{FP} is duty 10%, Pulse width 1 msec

Electro-Optical Characteristics (Ta=25 °C)

Type No.	Lighting Color	Lens Color	I _O			V _F		λ _P	Δ λ	I _F	I _R	
			Typ.	Min.	I _F	Typ.	Max.	Typ.	Typ.		Max.	V _R
LN03202P	Red	Red Diffused	0.6	0.3	15	2.2	2.8	700	100	20	5	4
LN03302P	Green	Green Diffused	1.5	0.4	20	2.2	2.8	565	30	20	10	4
LN03402P	Amber	Amber Diffused	1.5	0.6	20	2.2	2.8	590	30	20	10	4
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	μA	V



6932852 0015002 153

Panasonic