



256MB- 32Mx64 SDRAM UNBUFFERED

FEATURES

- PC100 and PC133 compatible
- Burst Mode Operation
- Auto and Self Refresh capability
- LVTTL compatible inputs and outputs
- Serial Presence Detect with EEPROM
- Fully synchronous: All signals are registered on the positive edge of the system clock
- Programmable Burst Lengths: 1, 2, 4, 8 or Full Page
- 3.3 volt $\pm$ 0.3v Power Supply
- 168- Pin DIMM JEDEC

DESCRIPTION

The WED3DG6433V is a 32Mx64 synchronous DRAM module which consists of four 32Mx16 SDRAM components in TSOP- 11 package and one 2K EEPROM in an 8- pin TSSOP package for Serial Presence Detect which are mounted on a 168 Pin DIMM multilayer FR4 Substrate.

PIN CONFIGURATIONS (FRONT SIDE/BACK SIDE)

Pin	Front	Pin	Front	Pin	Front	Pin	Back	Pin	Back	Pin	Back
1	VSS	29	DQM1	57	DQ18	85	VSS	113	DQM5	141	DQ50
2	DQ0	30	CS0	58	DQ19	86	DQ32	114	CS1	142	DQ51
3	DQ1	31	DNU	59	VDD	87	DQ33	115	RAS	143	VDD
4	DQ2	32	VSS	60	DQ20	88	DQ34	116	VSS	144	DQ52
5	DQ3	33	A0	61	NC	89	DQ35	117	A1	145	NC
6	VDD	34	A2	62	NC	90	VCC	118	A3	146	NC
7	DQ4	35	A4	63	NC	91	DQ36	119	A5	147	DNU
8	DQ5	36	A6	64	VSS	92	DQ37	120	A7	148	VSS
9	DQ6	37	A8	65	DQ21	93	DQ38	121	A9	149	DQ53
10	DQ7	38	A10/AP	66	DQ22	94	DQ39	122	BA0	150	DQ54
11	DQ8	39	BA1	67	DQ23	95	DQ40	123	A11	151	DQ55
12	VSS	40	VDD	68	VSS	96	VSS	124	VDD	152	VSS
13	DQ9	41	VDD	69	DQ24	97	DQ41	125	NC	153	DQ56
14	DQ10	42	CLK0	70	DQ25	98	DQ42	126	A12	154	DQ57
15	DQ11	43	VSS	71	DQ26	99	DQ43	127	VSS	155	DQ58
16	DQ12	44	DNU	72	DQ27	100	DQ44	128	CKE0	156	DQ59
17	DQ13	45	CS2	73	VDD	101	DQ45	129	NC	157	VDD
18	VDD	46	DQM2	74	DQ28	102	VDD	130	DQM6	158	DQ60
19	DQ14	47	DQM3	75	DQ29	103	DQ46	131	DQM7	159	DQ61
20	DQ15	48	DNU	76	DQ30	104	DQ47	132	NC	160	DQ62
21	NC	49	VDD	77	DQ31	105	NC	133	VDD	161	DQ63
22	NC	50	NC	78	VSS	106	NC	134	NC	162	VSS
23	VSS	51	NC	79	CLK2	107	VSS	135	NC	163	NC
24	NC	52	NC	80	NC	108	NC	136	NC	164	NC
25	NC	53	NC	81	*WP	109	NC	137	NC	165	**SA0
26	VDD	54	VSS	82	**SDA	110	VDD	138	VSS	166	**SA1
27	WE	55	DQ16	83	**SCL	111	CAS	139	DQ48	167	**SA2
28	DQM0	56	DQ17	84	VDD	112	DQM4	140	DQ49	168	VDD

PIN NAMES


A0 – A12	Address input (Multiplexed)
BA0-1	Select Bank
DQ0-63	Data Input/Output
CLK0,CLK2	Clock input
CKE0	Clock Enable input
CS0,CS2	Chip select Input
RAS	Row Address Strobe
CAS	Column Address Strobe
WE	Write Enable
DQM0-7	DQM
VDD	Power Supply (3.3V)
VSS	Ground
SDA	Serial data I/O
SCL	Serial clock
DNU	Do not use
NC	No Connect

* WP (write protect) option is available on Pin 81, see ordering information on page 5.

** These pins should be NC in the system which does not support SPD.



FUNCTIONAL BLOCK DIAGRAM



**ABSOLUTE MAXIMUM RATINGS**

Parameter	Symbol	Value	Units
Voltage on any pin relative to VSS	V _{IN} , V _{out}	-1.0 ~ 4.6	V
Voltage on VDD supply relative to VSS	VDD, VDDQ	-1.0 ~ 4.6	V
Storage Temperature	TSTG	-55 ~ +150	°C
Power Dissipation	PD	4	W
Short Circuit Current	IOS	50	mA

Note: Permanent device damage may occur if "ABSOLUTE MAXIMUM RATINGS" are exceeded.

Functional operation should be restricted to recommended operating condition.

Exposure to higher than recommended voltage for extended periods of time could affect device reliability.

RECOMMENDED DC OPERATING CONDITIONS

(Voltage Referenced to: V_{SS} = 0V, T_A = 0°C to +70°C)

Parameter	Symbol	Min	Typ	Max	Unit	Note
Supply Voltage	VDD	3.0	3.3	3.6	V	
Input High Voltage	V _{IH}	2.0	3.0	VDDQ+0.3	V	1
Input Low Voltage	V _{IL}	-0.3	—	0.8	V	2
Output High Voltage	V _{OH}	2.4	—	—	V	I _{OH} = -2mA
Output Low Voltage	V _{OL}	—	—	0.4	V	I _{OL} = -2mA
Input Leakage Current	I _{LI}	-10	—	10	μA	3

Note: 1. V_{IH} (max)= 5.6V AC. The overshoot voltage duration is ≤ 3ns.

2. V_{IL} (min)= -2.0V AC. The undershoot voltage duration is ≤ 3ns.

3. Any input 0V ≤ V_{IN} ≤ VDDQ

Input leakage currents include Hi-Z output leakage for all bi-directional buffers with Tri-State outputs.

CAPACITANCE

(T_A = 23°C, f = 1MHz, VDD = 3.3V, VREF=1.4V ± 200mV)

Parameter	Symbol	Min	Max	Unit
Input Capacitance (A0-A12)	CIN1	-	25	pF
Input Capacitance (RAS,CAS,WE)	CIN2	-	25	pF
Input Capacitance (CKE0)	CIN3	-	25	pF
Input Capacitance (CLK0,CLK2)	CIN4	-	13	pF
Input Capacitance (CS0,CS2)	CIN5	-	15	pF
Input Capacitance (DQM0-DQM7)	CIN6	-	10	pF
Input Capacitance (BA0-BA1)	CIN7	-	25	pF
Data input/output capacitance (DQ0-DQ63)	Cout	-	12	pF



OPERATING CURRENT CHARACTERISTICS

(V_{CC} = 3.3V, T_A = 0°C to +70°C)

Parameter	Symbol	Conditions	Version		Units	Note
			133	100		
Operating Current (One bank active)	ICC1	Burst Length = 1 tRC ≥ tRC(min) IOL = 0mA	600	560	mA	1
Precharge Standby Current in Power Down Mode	ICC2P	CKE ≤ VIL(max), tCC = 10ns	10		mA	
	ICC2PS	CKE & CLK ≤ VIL(max), tCC = ∞	10			
Precharge Standby Current in Non-Power Down Mode	ICC2N	CKE ≥ VIH(min), CS ≥ VIH(min), tcc = 10ns Input signals are charged one time during 20	70		mA	
	ICC2NS	CKE ≥ VIH(min), CLK ≤ VIL(max), tcc = ∞ Input signals are stable	60			
Active standby current in power-down mode	ICC3P	CKE ≥ VIL(max), tCC = 10ns	25		mA	
	ICC3PS	CKE & CLK ≤ VIL(max), tcc = ∞	25			
Active standby current in non power-down mode	ICC3N	CKE ≥ VIH(min), CS ≥ VIH(min), tcc = 10ns Input signals are changed one time during 20ns	140		mA	
	ICC3NS	CKE ≥ VIH(min), CLK ≤ VIL(max), tcc = ∞ input signals are stable	120			
Operating current (Burst mode)	ICC4	Io = mA Page burst 4 Banks activated tCCD = 2CLK	720	580	mA	1
Refresh current	ICC5	tRC ≥ tRC(min)	840	800	mA	2
Self refresh current	ICC6	CKE ≤ 0.2V	20		mA	

Notes: 1. Measured with outputs open.

2. Refresh period is 64ms.

3. Unless otherwise noticed, input swing level is CMOS (V_{IH}/V_{IL} = V_{DDQ}/V_{SSQ})




ORDERING INFORMATION

Part Number	Speed	CAS Latency
WED3DG6433V10D2	100MHz	CL=2
WED3DG6433V75D2	133MHz	CL=3

Part Number	Speed	CAS Latency
WED3DG6333V10D2	100MHz	CL=2
WED3DG6333V75D2	133MHz	CL=3

Note: Available with WP (write protection) on Pin 81.

PACKAGE DIMENSIONS



ALL DIMENSIONS ARE IN INCHES

White Electronic Designs Corp reserves the right to change products or specifications without notice.