

REVISIONS																				
LTR	DESCRIPTION										DATE (YR-MO-DA)	APPROVED								
A	Change to table I, parameters t_{BAA} , t_{BDA} , t_{BDC} , and t_{APS} . Deleted parameters t_{CDR} and t_R . Also deleted electrostatic discharged sensitivity paragraph from drawing. Editorial changes throughout.										1989 NOV 08	M.A. Frye								
B	Add device types 05 and 06 to the drawing. Add footnote 3 to table I, parameter t_{LI} . Editorial changes throughout.										1991 JULY 23	M.A. Frye								
C	Add devices 07 through 16. Add vendor CAGE 61772 as source of supply to devices 07 through 16. Add t_{WC} , t_{WP} , t_{DW} , t_{DH} , t_{APS} to Read with BUSY cycle waveform. Editorial changes throughout.										1993 SEPT 10	M.A. Frye								
D	Add case outline U. Update boilerplate. Editorial changes throughout.										96-12-09	Ray Monnin								

REV																			
SHEET																			
REV	D	D	D	D	D	D	D	D	D	D	D								
SHEET	15	16	17	18	19	20	21	22	23	24	25								
REV STATUS OF SHEETS				REV		D	D	D	D	D	D	D	D	D	D	D	D	D	D
				SHEET		1	2	3	4	5	6	7	8	9	10	11	12	13	14

PMIC N/A STANDARD MICROCIRCUIT DRAWING THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE AMSC N/A	PREPARED BY James E. Jamison CHECKED BY Charles Reusing APPROVED BY Michael A. Frye DRAWING APPROVAL DATE 88-12-12 REVISION LEVEL D	DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216 MICROCIRCUITS, MEMORY, DIGITAL, CMOS 2K X 16 DUAL PORT SRAM, MONOLITHIC SILICON <table border="1" style="width:100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width:15%;">SIZE A</td> <td style="width:25%;">CAGE CODE 67268</td> <td style="width:60%; text-align: center;">5962-88665</td> </tr> </table> SHEET 1 OF 25	SIZE A	CAGE CODE 67268	5962-88665
SIZE A	CAGE CODE 67268	5962-88665			

DESC FORM 193
JUL 94

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


5962-E030-97

■ 9004708 0025775 136 ■

1. SCOPE

1.1 Scope. This drawing describes device requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A.

1.2 Part or Identifying Number (PIN). The complete PIN is as shown in the following example:



1.2.1 Device type(s). The device type(s) identify the circuit function as follows:

Device type	Generic number 1/	Circuit function	Access time
01,07		2K X 16 dual port CMOS SRAM (master)	90 ns
02,08		2K X 16 dual port CMOS SRAM (slave)	90 ns
03,09		2K X 16 dual port CMOS SRAM (master)	70 ns
04,10		2K X 16 dual port CMOS SRAM (slave)	70 ns
05,11		2K X 16 dual port CMOS SRAM (master)	55 ns
06,12		2K X 16 dual port CMOS SRAM (slave)	55 ns
13		2K X 16 dual port CMOS SRAM (master)	45 ns
14		2K X 16 dual port CMOS SRAM (slave)	45 ns
15		2K X 16 dual port CMOS SRAM (master)	35 ns
16		2K X 16 dual port CMOS SRAM (slave)	35 ns

1.2.2 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

Outline letter	Descriptive designator	Terminals	Package style
X	See figure 1	68	dual-in-line
Y	CQCC1-N68	68	square leadless chip carrier
Z	CMGA3-PN	68	pin grid array 2/
U	See figure 1	68	flat pack

1.2.3 Lead finish. The lead finish is as specified in MIL-PRF-38535, appendix A.

1.3 Absolute maximum ratings.

Supply voltage range	-0.5 V dc to +7.0 V dc
Input voltage	-0.5 V dc to +6.0 V dc
DC output current	50 mA
Storage temperature range	-65°C to +150°C
Maximum power dissipation (P _D)	2.0 W
Lead temperature (soldering, 10 seconds)	+260°C
Thermal resistance, junction-to-case (Θ _{JC}):	
Case X	37°C/W
Cases Y and Z	See MIL-STD-1835
Case U	6°C/W
Junction temperature (T _J)	+150°C 3/

1/ Generic numbers are listed on the Standard Microcircuit Source Approval Bulletin at the end of this document and will also be listed in MIL-HDBK-103.

2/ The actual number of pins is 121, but the number of pins being used is 68. (See figure 2, case outline Z).

3/ Maximum junction temperature may be increased to +175°C during burn-in and steady-state life.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 2

1.4 Recommended operating conditions.

Supply voltage range (V_{CC})	4.5 V dc to 5.5 V dc
High level input voltage range (V_{IH})	2.2 V dc to 6.0 V dc
Low level input voltage range (V_{IL})	-0.5 V dc to +0.8 V dc <u>4/</u>
Case operating temperature range (T_C)	-55°C to +125°C

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATION

MILITARY

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

STANDARDS

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.
MIL-STD-973 - Configuration Management.
MIL-STD-1835 - Microcircuit Case Outlines.

HANDBOOKS

MILITARY

MIL-HDBK-103 - List of Standard Microcircuit Drawings (SMD's).
MIL-HDBK-780 - Standard Microcircuit Drawings.

(Unless otherwise indicated, copies of the specification, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein. Product built to this drawing that is produced by a Qualified Manufacturer Listing (QML) certified and qualified manufacturer or a manufacturer who has been granted transitional certification to MIL-PRF-38535 may be processed as QML product in accordance with the manufacturers approved program plan and qualifying activity approval in accordance with MIL-PRF-38535. This QML flow as documented in the Quality Management (QM) plan may make modifications to the requirements herein. These modifications shall not affect form, fit, or function of the device. These modifications shall not affect the PIN as described herein. A "Q" or "QML" certification mark in accordance with MIL-PRF-38535 is required to identify when the QML flow option is used.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535, appendix A and herein.

4/ V_{IL} (min) = -3.0 V dc for pulse width less than 20 ns.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 3

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 2.

3.2.2 Truth tables. The truth tables shall be as specified on figure 3.

3.2.3 Block diagram. The block diagram shall be as specified on figure 4.

3.2.4 Case outline(s). The case outline(s) shall be in accordance with 1.2.2 herein and figure 1.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full case operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table I.

3.5 Marking. Marking shall be in accordance with MIL-PRF-38535, appendix A. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked as listed in MIL-HDBK-103 (see 6.6 herein). For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device.

3.6 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6 herein). The certificate of compliance submitted to DSCC-VA prior to listing as an approved source of supply shall affirm that the manufacturer's product meets the requirements of MIL-PRF-38535, appendix A and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change. Notification of change to DSCC-VA shall be required in accordance with MIL-PRF-38535, appendix A.

3.9 Verification and review. DSCC, DSCC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition C or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015 of MIL-STD-883.

(2) $T_A = +125^{\circ}\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C ≤ T _C ≤ +125°C V _{CC} = 4.5 V to 5.5 V unless otherwise specified	Group A subgroups	Device types	Limits		Unit
					Min	Max	
Output high voltage	V _{OH}	V _{CC} = 4.5 V, I _{OH} = -4.0 mA, V _{IL} = 0.8 V, V _{IH} = 2.2 V	1, 2, 3	All	2.4		V
Output low voltage	V _{OL}	V _{CC} = 4.5 V, V _{IL} = 0.8 V, V _{IH} = 2.2 V	1, 2, 3	All		0.4	V
			1, 2, 3	01,03, 05,07, 09,11, 13,15		0.5	V
Input leakage current	I _{LI}	V _{CC} = 5.5 V, GND ≤ V _{IN} ≤ V _{CC}	1, 2, 3	All		5.0	μA
Output leakage current	I _{LO}	V _{CC} = 5.5 V, CE = V _{IH} , GND ≤ V _{OUT} ≤ V _{CC}	1, 2, 3	All		5.0	μA
Dynamic operating current (both ports active)	I _{CC}	V _{CC} = 5.5 V, CE = V _{IL} , f = f _{max} 1/, outputs open	1, 2, 3	01-04		240	mA
				05,06		260	
				07-10		280	
				11,12		285	
				13,14		290	
				15,16		295	
Standby power supply current (both ports, TTL input levels)	I _{SB1}	V _{CC} = 5.5 V, CE _L and CE _R ≥ V _{IH} , f = f _{MAX} 1/	1, 2, 3	01-04, 07-10		65	mA
				05,06, 11-14		70	
				15,16		75	
Standby power supply current (one port, TTL input levels)	I _{SB2}	V _{CC} = 5.5 V, CE _L or CE _R ≥ V _{IH} , f = f _{MAX} 1/, active port outputs open	1, 2, 3	01-04		150	mA
				05,06		160	
				07-10		180	
				11-14		190	
				15,16		200	

See footnotes at end of table.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
5

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions -55°C ≤ T _C ≤ +125°C V _{CC} = 4.5 V to 5.5 V unless otherwise specified	Group A subgroups	Device types	Limits		Unit
					Min	Max	
Full standby power supply current (both ports, CMOS input levels)	I _{SB3}	V _{CC} = 5.5 V, f = 0 1/, CE _L and CE _R ≥ V _{CC} - 0.2 V, V _{IN} ≥ V _{CC} - 0.2 V or ≤ 0.2 V	1, 2, 3	All		10	mA
Full standby power supply current (one port, CMOS input levels)	I _{SB4}	V _{CC} = 5.5 V, f _{max} 1/, CE _L or CE _R ≥ V _{CC} - 0.2 V, V _{IN} ≥ V _{CC} - 0.2 V or ≤ 0.2 V, active port outputs open	1, 2, 3	01,02		135	mA
				03,04		140	
				05,06		150	
				07-10		170	
				11-14		180	
				15,16		190	
V _{CC} for data retention	V _{DR}	CE ≥ V _{CC} - 0.2 V, V _{IN} ≥ V _{CC} - 0.2 V	1, 2, 3	All	2.0		V
Data retention current	I _{CCDR}		1, 2, 3	All		4.0	mA
Input leakage 2/ current (data retention mode)	I _{LI}		1, 2, 3	01-06		2.0	μA
Input capacitance	C _{IN}	V _{CC} = 5.0 V, V _{I/O} = 0 V, f = 1.0 MHz, T _A = +25°C, see 4.3.1c	4	All		11	pF
Output capacitance	C _{OUT}	V _{CC} = 5.0 V, V _{I/O} = 0 V, f = 1.0 MHz, T _A = +25°C, see 4.3.1c	4	All		11	pF
Functional tests		See 4.3.1d	7, 8A, 8B	All			
Read cycle time	t _{RC}	See figures 5 and 6 3/	9, 10, 11	01,02, 07,08	90		ns
				03,04, 09,10	70		
				05,06, 11,12	55		
				13,14	45		
				15,16	35		

See footnotes at end of table.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
6

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions -55°C ≤ T _C ≤ +125°C V _{CC} = 4.5 V to 5.5 V unless otherwise specified	Group A subgroups	Device types	Limits		Unit
					Min	Max	
Address access time	t _{AA}	See figures 5 and 6 3/	9, 10, 11	01,02, 07,08		90	ns
				03,04, 09,10		70	
				05,06, 11,12		55	
				13,14		45	
				15,16		35	
Output hold from address change	t _{OH}	See figures 5 and 6 3/	9, 10, 11	01,02, 07,08	10		ns
				03-06, 09-16	0		
Chip enable access time	t _{ACE}	See figures 5 and 6 3/	9, 10, 11	01,02, 07,08		90	ns
				03,04, 09,10		70	
				05,06, 11,12		55	
				13,14		45	
				15,16		35	
Output enable access time	t _{AOE}	See figures 5 and 6 3/	9, 10, 11	01-04, 07-10		40	ns
				05,06, 11-12		35	
				13,14		25	
				15,16		20	
Output low Z time	t _{LZ}	See figures 5 and 6 2/ 4/	9, 10, 11	01-12	5.0		ns
				13-16	0		
Output high Z time	t _{HZ}	See figures 5 and 6 2/ 4/	9, 10, 11	01,02, 07,08		40	ns
				03,04, 09,10		35	
				05,06, 11-16		20	
Chip enable to power-up time	t _{PU}	See figures 5 and 6 2/ 3/	9, 10, 11	All	0		ns
Chip disable to power-down time	t _{PD}	See figures 5 and 6 2/ 3/	9, 10, 11	All		50	ns

See footnotes at end of table.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
7

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions -55°C ≤ T _C ≤ +125°C V _{CC} = 4.5 V to 5.5 V unless otherwise specified	Group A subgroups	Device types	Limits		Unit
					Min	Max	
Write cycle time <u>5/</u>	t _{WC}	See figures 5 and 7 <u>3/</u>	9, 10, 11	01,02, 07,08	90		ns
				03,04, 09,10	70		
				05,06, 11,12	55		
				13,14	45		
				15,16	35		
Chip enable to end of write	t _{EW}	See figures 5 and 7 <u>3/</u>	9, 10, 11	01,02, 07,08	85		ns
				03,04, 09,10	50		
				05,06, 11,12	40		
				13,14	30		
				15,16	25		
Address valid to end of write	t _{AW}	See figures 5 and 7 <u>3/</u>	9, 10, 11	01,02, 07,08	85		ns
				03,04, 09,10	50		
				05,06, 11,12	40		
				13,14	30		
				15,16	25		
Address setup time	t _{AS}	See figures 5 and 7 <u>3/</u>	9, 10, 11	All	0		ns
Write pulse width <u>6/</u>	t _{WP}	See figures 5 and 7 <u>3/</u>	9, 10, 11	01,02, 07,08	55		ns
				03,04, 09,10	50		
				05,06, 11,12	40		
				13,14	30		
				15,16	25		
Write recovery time	t _{WR}	See figures 5 and 7 <u>3/</u>	9, 10, 11	All	0		ns
Data valid to end of write	t _{DW}	See figures 5 and 7 <u>3/</u>	9, 10, 11	01,02, 07,08	30		ns
				03,04, 09,10	25		
				05,06, 11,12	20		

See footnotes at end of table.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
8

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions -55°C ≤ T _C ≤ +125°C V _{CC} = 4.5 V to 5.5 V unless otherwise specified	Group A subgroups	Device types	Limits		Unit
					Min	Max	
Output high Z time	t _{HZ}	See figures 5 and 7 <u>2/ 4/</u>	9, 10, 11	01-04, 07-10 05,06, 11-16		25 20	ns
Data hold time <u>7/</u>	t _{DH}	See figures 5 and 7 <u>3/</u>	9, 10, 11	01-14 15,16	5.0 0		ns
Write enable to output in high Z	t _{WZ}	See figures 5 and 7 <u>2/ 4/</u>	9, 10, 11	01-04, 07-10 05,06, 11-16		25 20	ns
Output active <u>7/</u> from end of write	t _{OW}	See figures 5 and 7 <u>2/ 4/</u>	9, 10, 11	01-06, 15,16 07-14	0 5		ns
Write to BUSY <u>8/</u>	t _{WB}	See figures 5 and 8 <u>3/</u>	9, 10, 11	02,04, 06,08, 10,12, 14,16	0		ns
Write hold after BUSY <u>9/</u>	t _{WH}	See figures 5 and 8 <u>3/</u>	9, 10, 11	02,04, 06,08, 10,12, 14 16	30 25		ns
BUSY access time to address	t _{BAA}	See figures 5 and 8 <u>3/</u>	9, 10, 11	01,03, 07,09 05,11 13 15		55 50 45 35	ns
BUSY disable time to address	t _{BDA}	See figures 5 and 8 <u>3/</u>	9, 10, 11	01,03, 07,09 05,11, 13 15		45 40 30	ns
BUSY access time to chip enable	t _{BAC}	See figures 5 and 8 <u>3/</u>	9, 10, 11	01,07 03,05, 09,11 13 15		45 35 30 25	ns

See footnotes at end of table.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
9

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions -55°C ≤ T _C ≤ +125°C V _{CC} = 4.5 V to 5.5 V unless otherwise specified	Group A subgroups	Device types	Limits		Unit
					Min	Max	
BUSY disable time to chip enable	t _{BDC}	See figures 5 and 8 3/	9, 10, 11	01,07		45	ns
				03,05, 09,11		30	
				13		25	
				15		20	
Write pulse to data delay 2/ 10/	t _{WDD}	See figures 5 and 8 3/	9, 10, 11	01,02, 07,08		100	ns
				03,04, 09,10		90	
				05,06, 11-14		80	
				15,16		60	
Write data valid to read data delay 2/ 10/	t _{DDD}	See figures 5 and 8 3/	9, 10, 11	01,02, 07,08		90	ns
				03,04, 09,10		70	
				05,06		80	
				11-14		55	
				15,16		45	
BUSY disable to valid data	t _{BDD}	See figures 5 and 8 3/	9, 10, 11	All		11/	ns
Arbitration priority setup time	t _{APS}	See figures 5 and 8 3/	9, 10, 11	01,07	10		ns
				03,05, 09,11, 13,15	5.0		

- 1/ At f = f_{MAX} address and data inputs are cycling at the maximum frequency of read cycles of 1/t_{RC}. f = 0 means no input lines change.
- 2/ May not be tested, but shall be guaranteed to the limits specified in table I.
- 3/ Test conditions assume signal transition times of 5.0 ns or less. Timing is referenced at input and output levels of 1.5 V and input pulse levels of 0 V to 3.0 V. Output loading is equivalent to the specified I_{OL}/I_{OH} with a load capacitance of 30 pF (see figure 5).
- 4/ Test conditions assume signal transition times of 5.0 ns or less. Transition is measured at steady-state high level of -500 mV or steady-state low level of +500 mV on the output from 1.5 V level on the input with a load capacitance of 5.0 pF (see figure 5).
- 5/ For master/slave combination, t_{WC} = t_{BAA} + t_{WR} + t_{WP}.
- 6/ Specified for OE at high.
- 7/ The specification for t_{DH} must be met by the device supplying write data to the RAM under all conditions. Although t_{DH} and t_{OW} values will vary over voltage and temperature the actual t_{DH} will always be smaller than the actual t_{OW}.
- 8/ To ensure that the write cycle is inhibited during contention. Applicable to slave devices only (device types 02, 04, 06, 08, 10, 12, 14, and 16).
- 9/ To ensure that a write cycle is completed after contention. Applicable to slave devices only (device types 02, 04, 06, 08, 10, 12, 14, and 16).
- 10/ Port to port delay through RAM cells from writing port to reading port.
- 11/ t_{BDD} is a calculated parameter and is the greater of 0, t_{WDD} - t_{WP} (actual), or t_{DDD} - t_{DW} (actual).

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000


SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
10

Case outline X



Symbol	Inches		Millimeters	
	Min	Max	Min	Max
A	.085	.190	2.16	4.83
b	.014	.023	0.36	0.58
b1	.030	.060	0.76	1.52
C	.008	.015	0.20	0.38
D	2.380	2.440	60.45	61.98
E	.580	.610	14.73	15.49
E1	.590	.620	14.99	15.75

Symbol	Inches		Millimeters	
	Min	Max	Min	Max
e	.070 BSC		1.78 BSC	
L	.125	.200	3.18	5.08
L1	.150	---	3.81	---
Q	.020	.070	0.51	1.78
S	.030	.065	0.77	1.66
S1	.005	---	0.13	---
S2	.005	---	0.13	---

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are for general information only.

FIGURE 1. Case outlines.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000


SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
11

Case outline U



Symbol	Inches		Millimeters	
	Min	Max	Min	Max
A	.080	.120	2.03	3.05
A1	.070	.090	1.78	2.29
B	.014	.021	0.36	0.53
C	.008	.012	0.20	0.30
D/E	1.640	1.870	41.66	47.50
D1/E1	.926	.970	23.52	24.64

Symbol	Inches		Millimeters	
	Min	Max	Min	Max
D2/E2	.800 BSC		20.32 BSC	
e	.050 BSC		1.27 BSC	
L	.350	.450	8.89	11.43
N	68			
ND	17			

NOTES:

1. All dimensions are in inches.
2. Metric equivalents are given for general information only.
3. BSC - Basic lead spacing between centers.
4. Symbol "N" represents number of leads.

FIGURE 1. Case outlines - continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 12

Device types	ALL	ALL	Device types	ALL	ALL
Case outlines	X, Y, and U	Z	Case outlines	X, Y, and U	Z
Terminal number	Terminal symbol 1/		Terminal number	Terminal symbol 1/	
1	I/O _{0L}	I/O _{9L}	35	GND 2/	A _{5R}
2	I/O _{1L}	I/O _{10L}	36	R/W _{RUB}	A _{4R}
3	I/O _{2L}	I/O _{11L}	37	R/W _{RLB}	A _{3R}
4	I/O _{3L}	I/O _{12L}	38	OE _R	A _{2R}
5	I/O _{4L}	I/O _{13L}	39	A _{10R}	A _{1R}
6	I/O _{5L}	I/O _{14L}	40	A _{9R}	A _{0R}
7	I/O _{6L}	I/O _{15L}	41	A _{8R}	BUSY _R
8	I/O _{7L}	V _{CC} 2/	42	A _{7R}	CE _R
9	I/O _{8L}	GND 2/	43	A _{6R}	CE _L
10	I/O _{9L}	I/O _{0R}	44	A _{5R}	BUSY _L
11	I/O _{10L}	I/O _{1R}	45	A _{4R}	A _{0L}
12	I/O _{11L}	I/O _{2R}	46	A _{3R}	A _{1L}
13	I/O _{12L}	I/O _{3R}	47	A _{2R}	A _{2L}
14	I/O _{13L}	I/O _{4R}	48	A _{1R}	A _{3L}
15	I/O _{14L}	I/O _{5R}	49	A _{0R}	A _{4L}
16	I/O _{15L}	I/O _{6R}	50	BUSY _R	A _{5L}
17	V _{CC} 2/	I/O _{7R}	51	CE _R	A _{6L}
18	GND 2/	I/O _{8R}	52	CE _L	A _{7L}
19	I/O _{0R}	I/O _{9R}	53	BUSY _L	A _{8L}
20	I/O _{1R}	I/O _{10R}	54	A _{0L}	A _{9L}
21	I/O _{2R}	I/O _{11R}	55	A _{1L}	A _{10L}
22	I/O _{3R}	I/O _{12R}	56	A _{2L}	OE _L
23	I/O _{4R}	I/O _{13R}	57	A _{3L}	R/W _{LLB}
24	I/O _{5R}	I/O _{14R}	58	A _{4L}	R/W _{LUB}
25	I/O _{6R}	I/O _{15R}	59	A _{5L}	V _{CC} 2/
26	I/O _{7R}	GND 2/	60	A _{6L}	I/O _{0L}
27	I/O _{8R}	R/W _{RUB}	61	A _{7L}	I/O _{1L}
28	I/O _{9R}	R/W _{RLB}	62	A _{8L}	I/O _{2L}
29	I/O _{10R}	OE _R	63	A _{9L}	I/O _{3L}
30	I/O _{11R}	A _{10R}	64	A _{10L}	I/O _{4L}
31	I/O _{12R}	A _{9R}	65	OE _L	I/O _{5L}
32	I/O _{13R}	A _{8R}	66	R/W _{LLB}	I/O _{6L}
33	I/O _{14R}	A _{7R}	67	R/W _{LUB}	I/O _{7L}
34	I/O _{15R}	A _{6R}	68	V _{CC} 2/	I/O _{8L}

- 1/ An "L" suffix on a terminal indicates it applies to the "left port", and an "R" suffix indicates it applies to the "right port".
2/ Both V_{CC} pins and both GND pins must be connected to the supply in order to assure reliable operation.

FIGURE 2. Terminal connections.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 13

Device types: All

Noncontention read/write control (see note 1)

Left or right port (see note 2)						Function
R/W _{LB}	R/W _{UB}	CE	OE	I/O ₀₋₇	I/O ₈₋₁₅	
X	X	H	X	Z	Z	Port disabled and in power down mode, I _{SB2} or I _{SB4}
X	X	H	X	Z	Z	CE _R = CE _L = H, power down mode, I _{SB1} or I _{SB3}
L	L	L	X	DATA _{IN}	DATA _{IN}	Data on lower byte and upper byte written into memory (see note 3).
L	H	L	L	DATA _{IN}	DATA _{OUT}	Data on lower byte written into memory (see note 3). Data in memory output on upper byte (see note 4).
H	L	L	L	DATA _{OUT}	DATA _{IN}	Data in memory output on lower byte (see note 4). Data on upper byte written into memory (see note 3).
L	H	L	H	DATA _{IN}	Z	Data on lower byte written in memory (see note 3).
H	L	L	H	Z	DATA _{IN}	Data on upper byte written into memory (see note 3).
H	H	L	L	DATA _{OUT}	DATA _{OUT}	Data in memory output on lower byte and upper byte (see note 4).
H	H	L	H	Z	Z	High impedance outputs.

NOTES:

1. H = High, L = Low, X = Don't care, Z = High impedance, LB = Lower byte, UB = Upper byte.
2. A_{0L} - A_{10L} ≠ A_{0R} - A_{10R}
3. If BUSY = L, data is not written.
4. If BUSY = L, data may not be valid, see t_{WDD} and t_{DDD} timing.

FIGURE 3. Truth tables.


STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 14

Left port		Right port		Flags		Function
$\overline{CE}_L$	$A_{0L}-A_{10L}$	$\overline{CE}_R$	$A_{0R}-A_{10R}$	$BUSY_L$	$BUSY_R$	
H	X	H	X	H	H	No contention
L	Any	H	X	H	H	No contention
H	X	L	Any	H	H	No contention
L	$\neq A_{0R}-A_{10R}$	L	$\neq A_{0L}-A_{10L}$	H	H	No contention
Address arbitration with $\overline{CE}$ low before address match						
L	LV5R	L	LV5R	H	L	L-Port wins
L	RV5L	L	RV5L	L	H	R-Port wins
L	Same	L	Same	H	L	Arbitration resolved
L	Same	L	Same	L	H	Arbitration resolved
$\overline{CE}$ arbitration with address match before $\overline{CE}$						
LL5R	$= A_{0R}-A_{10R}$	LL5R	$= A_{0L}-A_{10L}$	H	L	L-Port wins
RL5L	$= A_{0R}-A_{10R}$	RL5L	$= A_{0L}-A_{10L}$	L	H	R-Port wins
LW5R	$= A_{0R}-A_{10R}$	LW5R	$= A_{0L}-A_{10L}$	H	L	Arbitration resolved
LW5R	$= A_{0R}-A_{10R}$	LW5R	$= A_{0L}-A_{10L}$	L	H	Arbitration resolved

NOTE: X = Don't care, L = Low, H = High, LV5R = Left address valid ≥ 5 ns before right address, RV5L = Right address valid ≥ 5 ns before left address, Same = Left and right address match within 5 ns of each other, LL5R = Left $\overline{CE}$ = Low ≥ 5 ns before right $\overline{CE}$, RL5L = Right $\overline{CE}$ = Low ≥ 5 ns before left $\overline{CE}$, LW5R = Left and right $\overline{CE}$ = Low within 5 ns of each other.

FIGURE 3. Truth tables - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 15




NOTES:


1. On device types 01, 03, 05, 07, 09, 11, 13, and 15, $\overline{BUSY}$ is an open drain output and requires the use of a pull-up resistor. On device types 02, 04, 06, 08, 10, 12, 14, and 16, $\overline{BUSY}$ is an input.
2. An L suffix on a terminal indicates it applies to the left port, and an R suffix indicates it applies to the right port. UB indicates upper byte, and a LB indicates lower byte.

FIGURE 4. Block diagram.


STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 16



OUTPUT LOAD CIRCUIT
FOR t_{HZ} , t_{LZ} , t_{WZ} ,
AND t_{OW}



OUTPUT LOAD CIRCUIT
FOR BUSY OUTPUT.
(APPLIES TO DEVICE
TYPES 01, 03, 05,
07, 09, 11, 13,
AND 15 ONLY)



OUTPUT LOAD CIRCUIT
FOR ALL OTHER MEASUREMENTS

NOTE: C_L = Load capacitance and includes scope and jig capacitance.

FIGURE 5. Output load circuits.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000


SIZE
A

5962-88665


REVISION LEVEL
D

SHEET
17

READ CYCLE 1 - EITHER SIDE: SEE NOTES 1, 2, AND 4



READ CYCLE 2 - EITHER SIDE: SEE NOTES 1 AND 3



NOTES:

1. R/W is high for read cycles.
2. Device is continuously enabled, $\overline{CE} = V_{IL}$.
3. Addresses valid prior to or coincident with $\overline{CE}$ transition low.
4. $\overline{OE} = V_{IL}$.

FIGURE 6. Read cycle timing diagrams.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
18

WRITE CYCLE NUMBER 1, R/W CONTROLLED
SEE NOTES 1, 2, 3, AND 6




FIGURE 7. Write cycle timing diagrams.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000


SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
19

WRITE CYCLE NUMBER 2, $\overline{CE}$ CONTROLLED
SEE NOTES 1, 2, 3, AND 5




NOTES:

1. R/W or $\overline{CE}$ must be high during all address transitions.
2. A write occurs during the overlap (t_{EW} or t_{WP}) of a low $\overline{CE}$ and a low R/W.
3. t_{WR} is measured from the earlier of $\overline{CE}$ or R/W going high to the end of write cycle.
4. During this period, the I/O pins are in the output state, and input signals must not be applied.
5. If the $\overline{CE}$ low transition occurs simultaneously with or after the R/W low transition, the outputs remain in the high impedance state.
6. If $\overline{OE}$ is low during a R/W controlled write cycle, the write pulse width must be the larger of t_{WP} or ($t_{WZ} + t_{DW}$) to allow the I/O drivers to turn off and data to be placed on the bus for the required t_{DW} . If $\overline{OE}$ is high during a R/W controlled write cycle, this requirement does not apply and the write pulse can be as short as the specified t_{WP} .
7. R/W for either upper or lower byte.
8. Transition is measured ± 500 mV from steady state with a 5 pF load (including scope and jig).


FIGURE 7. Write cycle timing diagrams - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 20

READ WITH $\overline{\text{BUSY}}$ CYCLE FOR DEVICE TYPES 01, 03, 05, 07, 09, 11, 13, AND 15. SEE NOTES 1, 2, AND 3



WRITE WITH $\overline{\text{BUSY}}$ CYCLE FOR DEVICE TYPES 02, 04, 06, 08, 10, 12, 14, AND 16



NOTES:

1. To ensure that the earlier of the two ports wins.
2. Write cycle parameter should be adhered to in order to ensure proper writing.
3. Device is continuously enabled for both ports.
4. $\overline{\text{OE}}$ at low for the reading port.

FIGURE 8. BUSY timing diagrams.

STANDARD
MICROCIRCUIT DRAWING
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000


SIZE
A

5962-88665

REVISION LEVEL
D

SHEET
21

CONTENTION CYCLE 1: $\overline{CE}$ ARBITRATION FOR DEVICE
 TYPES 01, 03, 05, 07, 09,
 $\overline{CE}_L$ VALID FIRST 11, 13, AND 15



$\overline{CE}_R$ VALID FIRST




FIGURE 8. BUSY timing diagrams - Continued.

STANDARD
 MICROCIRCUIT DRAWING
 DEFENSE SUPPLY CENTER COLUMBUS
 COLUMBUS, OHIO 43216-5000


SIZE
A

5962-88665

REVISION LEVEL
 D

SHEET
 22

CONTENTION CYCLE 2: ADDRESS VALID ARBITRATION ($\overline{CE}_L = \overline{CE}_R = V_{IL}$)
 FOR DEVICE TYPES 01, 03, 05, 07, 09, 11, 13, AND 15)
 LEFT ADDRESS VALID FIRST



RIGHT ADDRESS VALID FIRST




FIGURE 8. BUSY timing diagrams - Continued.

STANDARD
 MICROCIRCUIT DRAWING
 DEFENSE SUPPLY CENTER COLUMBUS
 COLUMBUS, OHIO 43216-5000

SIZE
A

5962-88665

REVISION LEVEL
 D

SHEET
23

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	1*,2,3,7*,8A,8B,9,10,11
Group A test requirements (method 5005)	1,2,3,4**,7,8A,8B,9,10,11
Groups C and D end-point electrical parameters (method 5005)	2,3,7,8A,8B

* PDA applies to subgroups 1 and 7.

** See 4.3.1c.

4.3.1 Group A inspection.

- Tests shall be as specified in table II herein.
- Subgroups 5 and 6 in table I, method 5005 of MIL-STD-883 shall be omitted.
- Subgroup 4 (C_{IN} and C_{OUT} measurements) shall be measured only for the initial test and after process or design changes which may affect input capacitance. Sample size is 15 devices with no failures, and all input and output terminals tested.
- Subgroups 7 and 8 shall include verification of the truth table.

4.3.2 Groups C and D inspections.

- End-point electrical parameters shall be as specified in table II herein.
- Steady-state life test conditions, method 1005 of MIL-STD-883.
 - Test condition C or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.
 - $T_A = +125^\circ\text{C}$, minimum.
 - Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-STD-883 (see 3.1 herein).

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 24

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-973 using DD Form 1692, Engineering Change Proposal.

6.4 Record of users. Military and industrial users shall inform Defense Supply Center Columbus when a system application requires configuration control and the applicable SMD. DSCC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DSCC-VA, telephone (614) 692-0525.

6.5 Comments. Comments on this drawing should be directed to DSCC-VA, Columbus, Ohio 43216-5000, or telephone (614) 692-0674.

6.6 Approved sources of supply. Approved sources of supply are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DSCC-VA.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-88665
		REVISION LEVEL D	SHEET 25

DESC FORM 193A
JUL 94

9004708 0025799 67T

STANDARD MICROCIRCUIT DRAWING SOURCE APPROVAL BULLETIN

DATE: 96-12-09

Approved sources of supply for SMD 5962-88665 are listed below for immediate acquisition only and shall be added to MIL-HDBK-103 during the next revision. MIL-HDBK-103 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DSCC-VA. This bulletin is superseded by the next dated revision of MIL-HDBK-103.

Standard microcircuit drawing PIN <u>1</u> /	Vendor CAGE number	Vendor similar PIN <u>2</u> /
5962-8866501XX 5962-8866501YX 5962-8866501ZX	<u>3</u> / <u>3</u> / <u>3</u> /	
5962-8866502XX 5962-8866502YX 5962-8866502ZX	<u>3</u> / <u>3</u> / <u>3</u> /	
5962-8866503XX 5962-8866503YX 5962-8866503ZX	<u>3</u> / <u>3</u> / <u>3</u> /	
5962-8866504XX 5962-8866504YX 5962-8866504ZX	<u>3</u> / <u>3</u> / <u>3</u> /	
5962-8866505XX 5962-8866505YX 5962-8866505ZX	<u>3</u> / <u>3</u> / <u>3</u> /	
5962-8866506XX 5962-8866506YX 5962-8866506ZX	<u>3</u> / <u>3</u> / <u>3</u> /	
5962-8866507ZA	61772	IDT7133LA90GB
5962-8866507UA	61772	IDT7133LA90FB
5962-8866508ZA	61772	IDT7143LA90GB
5962-8866508UA	61772	IDT7143LA90FB
5962-8866509ZA	61772	IDT7133LA70GB
5962-8866509UA	61772	IDT7133LA70FB

See footnotes at end of list.

■ 9004708 0025800 111 ■

Standard microcircuit drawing PIN <u>1/</u>	Vendor CAGE number	Vendor similar PIN <u>2/</u>
5962-8866510ZA	61772	IDT7143LA70GB
5962-8866510UA	61772	IDT7143LA70FB
5962-8866511ZA	61772	IDT7133LA55GB
5962-8866511UA	61772	IDT7133LA55FB
5962-8866512ZA	61772	IDT7143LA55GB
5962-8866512UA	61772	IDT7143LA55FB
5962-8866513ZA	61772	IDT7133LA45GB
5962-8866513UA	61772	IDT7133LA45FB
5962-8866514ZA	61772	IDT7143LA45GB
5962-8866514UA	61772	IDT7143LA45FB
5962-8866515ZA	61772	IDT7133LA35GB
5962-8866515UA	61772	IDT7133LA35FB
5962-8866516ZA	61772	IDT7143LA35GB
5962-8866516UA	61772	IDT7143LA35FB

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. The device manufacturers listed herein are authorized to supply alternate lead finishes "A", "B", or "C" at their discretion. Contact the listed approved source of supply for further information.
- 2/ Caution. Do not use this number for item acquisition. Items acquired by this number may not satisfy the performance requirements of this drawing.
- 3/ Not available from an approved source of supply.

Vendor CAGE
number

61772

Vendor name
and address

Integrated Device Technology, Incorporated
2975 Stender Way
Santa Clara, CA 95054-8015

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in this information bulletin.