

Ta=25°C

2桁LED数字表示 2 Digits LED numeric display

字高 Character height	機 種 名 Type No.		ピーク発光波長 Peak-emission wavelength	絶対最大定格 Absolute maximum ratings					推奨動作電流 Recommend. If/seg	電気的光学的特性 Electro-optical characteristics				
	Com.-Anode	Com.-Cathode		If/seg	IfP/seg	Vr/seg	Pd	Topr		Vf Typ.	If	Luminous intensity Iv Typ.	Intensity If	Ir Max. (Vr=3V) μA/seg
mm			nm (Color)	mA	mA	V	W	°C	mA	V	mA	μcd/seg	mA	
7.62	SL-1275-20	SL-1276-20	700 (R)	20	40	3	0.8	-25~+70	3~10	1.9	5	600	5	10
	SL-2275-20	SL-2276-20	565 (G)	20	40	3	0.8	-25~+70	5~10	2.05	15	1500	15	10
10	SL-1255	SL-1256	700 (R)	20	40	3	0.65	-25~+70	3~10	1.9	5	400	5	10
	SL-2255	SL-2256	565 (G)	20	40	3	0.65	-25~+70	10~15	2.05	15	1000	15	10
10.16	SL-1283	SL-1284	700 (R)	20	40	3	0.8	-25~+70	3~10	1.9	5	350	5	10
	SL-2283	SL-2284	565 (G)	20	40	3	0.8	-25~+70	10~15	2.05	15	800	15	10
	SL-1283-20,22	SL-1284-20,22	700 (R)	20	40	3	0.8	-25~+70	3~10	1.9	5	350	5	10
	SL-2283-20,22	SL-2284-20,22	565 (G)	20	40	3	0.8	-25~+70	10~15	2.05	15	800	15	10

外觀図 Package dimensions

Tolerance : ±0.25
Unit : mm

