



Solid State Devices, Inc.


14701 Firestone Blvd. * La Mirada, Ca 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

SER30KB60 / SER30KE60 Series

30 AMP 300-600 VOLT ULTRAFAST POWER SURFACE MOUNT RECTIFIER



Designer's Data Sheet

Part Number / Ordering Information ^{1/}



- FEATURES:**
- Low Reverse Leakage
 - Low Forward Voltage Drop
 - Hermetically Sealed Power Surface Mount Package
 - TX, TXV, and Space Level Screening Available^{2/}

| MAXIMUM RATINGS | | Symbol | Value | Units |
|---|----------------------|---------------------------------|-------------|--------------------|
| Peak Repetitive Reverse Voltage and DC Blocking Voltage | SER30KE30, SER30KB30 | V_{RRM} V_{RWM} V_R | 300 | Volts |
| | SER30KE40, SER30KB40 | | 400 | |
| | SER30KE50, SER30KB50 | | 500 | |
| | SER30KE60, SER30KB60 | | 600 | |
| Average Rectified Forward Current (Resistive Load, 60 Hz, Sine Wave, $T_A = 100^\circ\text{C}$) | | I_O | 30 | Amps |
| Peak Surge Current (8.3 ms Pulse, Half Sine Wave, Superimposed on I_O , Allow Junction to Reach Equilibrium between Pulses, $T_A = 25^\circ\text{C}$) | | I_{FSM} | 400 | Amps |
| Operating and Storage Temperature | | $T_{OP} \ \& \ T_{stg}$ | -55 to +200 | $^\circ\text{C}$ |
| Maximum Thermal Resistance Junction to Case | | $R_{\theta JC}$ | 1.2 | $^\circ\text{C/W}$ |



NOTE: All specifications are subject to change without notification. SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0128D

DOC



Solid State Devices, Inc.
 14701 Firestone Blvd. * La Mirada, Ca 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

SER30KB60 / SER30KE60 Series

| ELECTRICAL CHARACTERISTICS | | Symbol | Typical | Maximum | Unit | |
|--|--|---------------------|----------|---------|-------------------------|-------------|
| Instantaneous Forward Voltage Drop ($I_F = 5 \text{ A}$, 300 μsec Pulse) | $T_A = -55^\circ\text{C}$ | V_{F1a} | 1070 | - | mV_{DC} | |
| | $T_A = 25^\circ\text{C}$ | V_{F1b} | 950 | - | | |
| | $T_A = 100^\circ\text{C}$ | V_{F1c} | 760 | - | | |
| | $T_A = 125^\circ\text{C}$ | V_{F1d} | 710 | - | | |
| | $T_A = 150^\circ\text{C}$ | V_{F1e} | 650 | - | | |
| Instantaneous Forward Voltage Drop ($I_F = 10 \text{ A}_{\text{DC}}$, 300 μsec Pulse) | $T_A = -55^\circ\text{C}$ | V_{F2a} | 1150 | - | mV_{DC} | |
| | $T_A = 25^\circ\text{C}$ | V_{F2b} | 1050 | 1150 | | |
| | $T_A = 100^\circ\text{C}$ | V_{F2c} | 860 | - | | |
| | $T_A = 125^\circ\text{C}$ | V_{F2d} | 810 | 975 | | |
| | $T_A = 150^\circ\text{C}$ | V_{F2e} | 750 | - | | |
| Instantaneous Forward Voltage Drop ($I_F = 20 \text{ A}_{\text{DC}}$, 300 μsec Pulse) | $T_A = -55^\circ\text{C}$ | V_{F3a} | 1260 | - | mV_{DC} | |
| | $T_A = 25^\circ\text{C}$ | V_{F3b} | 1170 | - | | |
| | $T_A = 100^\circ\text{C}$ | V_{F3c} | 1000 | - | | |
| | $T_A = 125^\circ\text{C}$ | V_{F3d} | 950 | - | | |
| | $T_A = 150^\circ\text{C}$ | V_{F3e} | 880 | - | | |
| Instantaneous Forward Voltage Drop ($I_F = 30 \text{ A}_{\text{DC}}$, 300 μsec Pulse) | $T_A = -55^\circ\text{C}$ | V_{F4a} | 1340 | - | mV_{DC} | |
| | $T_A = 25^\circ\text{C}$ | V_{F4b} | 1260 | 1400 | | |
| | $T_A = 100^\circ\text{C}$ | V_{F4c} | 1100 | - | | |
| | $T_A = 125^\circ\text{C}$ | V_{F4d} | 1050 | 1250 | | |
| | $T_A = 150^\circ\text{C}$ | V_{F4e} | 990 | - | | |
| Instantaneous Forward Voltage Drop ($I_F = 50 \text{ A}_{\text{DC}}$, 300 μsec Pulse) | $T_A = -55^\circ\text{C}$ | V_{F5a} | 1480 | - | mV_{DC} | |
| | $T_A = 25^\circ\text{C}$ | V_{F5b} | 1400 | - | | |
| | $T_A = 100^\circ\text{C}$ | V_{F5c} | 1240 | - | | |
| | $T_A = 125^\circ\text{C}$ | V_{F5d} | 1190 | - | | |
| | $T_A = 150^\circ\text{C}$ | V_{F5e} | 1150 | - | | |
| Reverse Leakage Current (Rated V_R , 300 μsec pulse minimum) | $T_A = 25^\circ\text{C}$ | I_{R1} | 0.1 | 10 | μA | |
| | $T_A = 100^\circ\text{C}$ | I_{R2} | 6 | - | | |
| | $T_A = 125^\circ\text{C}$ | I_{R3} | 25 | 500 | | |
| | $T_A = 150^\circ\text{C}$ | I_{R4} | 80 | - | | |
| Junction Capacitance ($T_A = 25^\circ\text{C}$, $f = 1 \text{ MHz}$) | $V_R = 5 \text{ V}$ | C_J | 190 | - | pF | |
| | $V_R = 10 \text{ V}$ | | 140 | 250 | | |
| Reverse Recovery | $I_F = 0.5 \text{ A}$, $I_R = 1 \text{ A}$, $I_{rr} = 0.25 \text{ A}$ | t_{rr1} | 32 | 35 | ns | |
| | $I_F = 1 \text{ A}$, $I_R = 1 \text{ A}$, $I_{rr} = 0.1 \text{ A}$ | t_{rr2} | 75 | - | ns | |
| | $I_F = 10 \text{ A}$, $dI_F/dt = 45 \text{ A/us}$, $T_A = 25^\circ\text{C}$ | t_{rr3} | 46 | - | ns | |
| | $I_F = 10 \text{ A}$, $dI_F/dt = 45 \text{ A/us}$, $T_A = 25^\circ\text{C}$ | I_{RM3} | 1.8 | - | A | |
| | $I_F = 10 \text{ A}$, $dI_F/dt = 45 \text{ A/us}$, $T_A = 100^\circ\text{C}$ | t_{rr4} | 115 | - | ns | |
| | $I_F = 10 \text{ A}$, $dI_F/dt = 45 \text{ A/us}$, $T_A = 100^\circ\text{C}$ | I_{RM4} | 3.8 | - | A | |
| | $I_F = 10 \text{ A}$, $dI_F/dt = 100 \text{ A/us}$, $T_A = 25^\circ\text{C}$ | t_{rr5} | 45 | - | ns | |
| | $I_F = 10 \text{ A}$, $dI_F/dt = 100 \text{ A/us}$, $T_A = 25^\circ\text{C}$ | I_{RM5} | 3.7 | - | A | |
| | Forward Recovery | $I_F = 1 \text{ A}$ | t_{fr} | 60 | - | ns |
| | | | V_{fr} | 880 | - | mV |

NOTES:

- 1/ For ordering information, price, operating curves, and availability – contact factory.
- 2/ Screening based on MIL-PRF-19500. Screening flows available on request.

NOTE: All specifications are subject to change without notification.
 SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0128D

DOC