

AT28HC16/L

T-46-13-27

Features

- Fast Read Access Time - 45ns
- Fast Byte Write - 1ms
- Self-Timed Byte Write Cycle
 - Internal Address and Data Latches
 - Internal Control Timer
 - Automatic Clear Before Write
- Direct Microprocessor Control
 - DATA POLLING
- Low Power
 - 80mA Active Current
 - 500µA CMOS Standby Current (28HC16L)
- High Reliability CMOS Technology
 - Endurance: 10⁴ cycles
 - Data Retention: 10 years
- 5V ± 10% Supply
- CMOS & TTL Compatible Inputs and Outputs
- JEDEC Approved Byte-Wide Pinout
- Full Military, Commercial, and Industrial Temperature Ranges



**16K (2K x 8)
High Speed
CMOS
E²PROM**

Description


The ATMEL 28HC16/16L is a high-speed, low-power Electrically Erasable and Programmable Read Only Memory. The device is optimized for high speed applications, featuring access times to 45ns. Its 16k of memory is organized as 2,048 words by 8 bits. The AT28HC16/16L comes in a space saving 24 pin DIP or in a 32 pad leadless chip carrier.

The AT28HC16/16L is accessed like a static RAM for the read or write cycles without the need of external components. During a byte write, the address and data are latched internally, freeing the microprocessor address and data bus for other operations. Following the initiation of a write cycle, the device being written will go to a busy state and automatically clear and write the latched data using an internal control timer. Data polling of I/O7 may be used to detect the end of the write cycle. Once a write cycle has been completed, a new access for a read or a write may begin immediately.

ATMEL's high-speed CMOS technology is used to achieve access times of 45ns for the AT28HC16 with under 440mW of power dissipation. The AT28HC16L offers ultra low standby power consumption of under 2.75mW at access time to 55ns.

The AT28HC16/16L has additional features to ensure high quality and manufacturability. The device utilizes internal error correction for extended endurance and for improved data retention characteristics. An extra 16 bytes of E²PROM are available for device identification or tracking.

Pin Configurations




Note: PLCC package pins 1 and 17 are DON'T CONNECT.





Block Diagram



Operating Modes

MODE	\overline{CE}	\overline{OE}	\overline{WE}	I/O
Read	V _{IL}	V _{IL}	V _{IH}	D _{OUT}
Write ²	V _{IL}	V _{IH}	V _{IL}	D _{IN}
Standby/Write Inhibit	V _{IH}	X ¹	X	High Z
Write Inhibit	X	X	V _{IH}	
Write Inhibit	X	V _{IL}	X	
Output Disable	X	V _{IH}	X	High Z
Chip Erase	V _{IL}	V _H ³	V _{IL}	High Z

Notes: 1. X can be V_{IL} or V_{IH}. 2. Refer to A.C. Programming Waveforms. 3. V_H = 12.0 ± 0.5V.

Device Operation

READ: The AT28HC16/16L is accessed like a Static RAM. When \overline{CE} and \overline{OE} are low and \overline{WE} is high, the data stored at the memory location determined by the address pins is asserted on the outputs. The outputs are put in a high impedance state whenever \overline{CE} or \overline{OE} is high. This dual line control gives designers increased flexibility in preventing bus contention.

BYTE WRITE: Writing data into the AT28HC16/16L is similar to writing into a Static RAM. A low pulse on the \overline{WE} or \overline{CE} input with \overline{OE} high and \overline{CE} or \overline{WE} low (respectively) initiates a byte write. The address location is latched on the last falling edge of \overline{WE} (or \overline{CE}); the new data is latched on the first rising edge. Internally, the device performs a self-clear before write. Once a byte write has been started, it will automatically time itself to completion.

DATA POLLING: The AT28HC16/16L provides $\overline{DATA POLLING}$ to signal the completion of a write cycle. During a write cycle, an attempted read of the data being written results in the complement of that data for I/O7 (the other outputs are indeterminate). When the write cycle is finished, true data appears on all outputs.

WRITE PROTECTION: Inadvertent writes to the device are protected against in the following ways: (a) Vcc sense--if Vcc is below 3.8V (typical) the write function is inhibited. (b) Vcc power on delay--once Vcc has reached 3.8V the device will automatically time out 5ms (typical) before allowing a byte write. (c) Write Inhibit--holding any one of \overline{OE} low, \overline{CE} high or \overline{WE} high inhibits byte write cycles. (d) Noise Protection - a \overline{WE} or \overline{CE} pulse of less than 10ns (typical) will not initiate a write cycle.

CHIP CLEAR: The contents of the entire memory of the AT28HC16/16L may be set to the high state by the CHIP CLEAR operation. By setting \overline{CE} low and \overline{OE} to 12 volts, the chip is cleared when a 10 msec low pulse is applied to \overline{WE} .

DEVICE IDENTIFICATION: In the AT28HC16/16L there are an extra 16 bytes of E²PROM memory available to the user for device identification. By raising A9 to 12 ± 0.5V and using address locations 7F0H to 7FFH the additional bytes may be written to or read from in the same manner as the regular memory array.

AT28HC16/L

Absolute Maximum Ratings*

Temperature Under Bias.....	-55°C to +125°C
Storage Temperature.....	-65°C to +150°C
All Input Voltages (including N.C. Pins) with Respect to Ground.....	-0.6V to +6.25V
All Output Voltages with Respect to Ground.....	-0.6V to V _{CC} +0.6V
Voltage on OE and A9 with Respect to Ground.....	-0.6V to +13.5V

2

*NOTICE: Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

D.C. and A.C. Operating Range

		AT28HC16-45	AT28HC16L-55	AT28HC16-55	AT28HC16-70	AT28HC16-90
				AT28HC16L-70	AT28HC16L-90	
Operating Temperature (Case)	Com.	0°C - 70°C	0°C - 70°C	0°C - 70°C	0°C - 70°C	0°C - 70°C
	Ind.	-40°C - 85°C	-40°C - 85°C	-40°C - 85°C	-40°C - 85°C	-40°C - 85°C
	Mil.			-55°C - 125°	-55°C - 125°C	-55°C - 125°C
VCC Power Supply		5V ± 10%	5V ± 10%	5V ± 10%	5V ± 10%	5V ± 10%

D.C. Characteristics

Symbol	Parameter	Condition	Min	Max	Units
I _{LI}	Input Load Current	V _{IN} = 0V to V _{CC} + 1V		10	μA
I _{LO}	Output Leakage Current	V _{I/O} = 0V to V _{CC}		10	μA
I _{SB1}	VCC Standby Current CMOS	CE = V _{CC} - 0.3V to V _{CC} + 1.0V (AT28HC16L)		500	μA
I _{SB2}	VCC Standby Current TTL	CE = 2.0V		3	mA
		to V _{CC} + 1.0V	AT28HC16L AT28HC16	60	mA
I _{CC}	VCC Active Current A.C	f = 10MHz; I _{out} = 0mA		80	mA
V _{IL}	Input Low Voltage			0.8	V
V _{IH}	Input High Voltage		2.0		V
V _{OL}	Output Low Voltage	I _{OL} = 12mA		.4	V
V _{OH}	Output High Voltage	I _{OH} = -4.0mA	2.4		V

Pin Capacitance (f = 1MHz T = 25°C)⁵

	Typ	Max	Units	Conditions
C _{IN}	4	6	pF	V _{IN} = 0V
C _{OUT}	8	12	pF	V _{OUT} = 0V






A.C. Read Characteristics¹

Symbol		28HC16-45	28HC16-55	28HC16L-55	28HC16-70	28HC16L-70	28HC16L-90	Units
		Min	Max	Min	Max	Min	Max	
t _{ACC}	Address to Output Delay	45	55	55	70	70	90	ns
t _{CE} ²	\overline{CE} to Output Delay	30	40	55	50	70	90	ns
t _{OE} ³	\overline{OE} to Output Delay	0	30	0	40	0	50	ns
t _{DF} ^{4,5}	\overline{OE} to Output Float	0	30	0	40	0	50	ns
t _{OH}	Output Hold from \overline{OE} or Address, whichever occurred first	0	0	0	0	0	0	ns


A.C. Read Waveforms




Notes:

1. $C_L = 30\text{pF}$.
2. \overline{CE} may be delayed up to $t_{ACC} - t_{CE}$ after the address transition without impact on t_{ACC} .
3. \overline{OE} may be delayed up to $t_{CE} - t_{OE}$ after the falling edge of \overline{CE} without impact on t_{CE} or by $t_{ACC} - t_{OE}$ after an address change without impact on t_{ACC} .
4. t_{DF} is specified from \overline{OE} or \overline{CE} whichever occurs first ($C_L = 5\text{pF}$).
5. This parameter is characterized and is not 100% tested.

Input Test Waveforms and Measurement Level



Output Test Load




A.C. Write Characteristics


Symbol	Parameter	Min	Typ	Max	Units
t_{AS}, t_{OES}	Address, \overline{OE} Set-up Time	0			ns
t_{AH}	Address Hold Time	50			ns
t_{WP}	Write Pulse Width	100		1000	ns
t_{DS}	Data Set-up Time	50			ns
t_{DH}, t_{OEH}	Data, \overline{OE} Hold Time	0			ns
t_{WC}	Write Cycle Time		0.5	1.0	ms

2

A.C. Write Waveforms - \overline{WE} Controlled



A.C. Write Waveforms - \overline{CE} Controlled






Data Polling Characteristics¹


Symbol	Parameter	Min	Typ	Max	Units
t _{DH}	Data Hold Time	0			ns
t _{OE}	OE Hold Time	0			ns
t _{OE}	OE to Output Delay			100	ns
t _{WR}	Write Recovery Time	0			ns

Note: 1. These parameters are characterized and not 100% tested.

Data Polling Waveforms



Chip Erase Waveforms




t_S = t_H = 1μsec (min.)

t_W = 10msec (min.)


V_H = 12 ± 0.5V

2


NORMALIZED SUPPLY CURRENT vs. TEMPERATURE



NORMALIZED SUPPLY CURRENT vs. SUPPLY VOLTAGE



NORMALIZED SUPPLY CURRENT vs. ADDRESS FREQUENCY





Ordering Information

tACC (ns)	Icc (mA)		Ordering Code	Package	Operation Range
	Active	Standby			
55	80	0.5	AT28HC16LN-55DC	24D3	Commercial (0°C to 70°C)
			AT28HC16L-55DC	24D6	
			AT28HC16L-55JC	32J	
			AT28HC16L-55LC	32L	
			AT28HC16LN-55PC	24P3	
			AT28HC16L-55PC	24P6	
			AT28HC16LN-55DI	24D3	Industrial (-40°C to 85°C)
			AT28HC16L-55DI	24D6	
			AT28HC16L-55JI	32J	
			AT28HC16L-55LI	32L	
			AT28HC16LN-55PI	24P3	
			AT28HC16L-55PI	24P6	
AT28HC16LN-55DM	24D3	Military (-55°C to 125°C)			
AT28HC16L-55DM	24D6				
AT28HC16L-55LM	32L				
AT28HC16LN-55DM/883	24D3	Military/883C Class B, Fully Compliant (-55°C to 125°C)			
AT28HC16L-55DM/883	24D6				
AT28HC16L-55LM/883	32L				
70	80	0.5	AT28HC16LN-70DC	24D3	Commercial (0°C to 70°C)
			AT28HC16L-70DC	24D6	
			AT28HC16L-70JC	32J	
			AT28HC16L-70LC	32L	
			AT28HC16LN-70PC	24P3	
			AT28HC16L-70PC	24P6	
			AT28HC16L-70W	DIE	
			AT28HC16LN-70DI	24D3	Industrial (-40°C to 85°C)
			AT28HC16L-70DI	24D6	
			AT28HC16L-70JI	32J	
			AT28HC16L-70LI	32L	
			AT28HC16LN-70PI	24P3	
			AT28HC16L-70PI	24P6	
			AT28HC16LN-70DM	24D3	Military (-55°C to 125°C)
			AT28HC16L-70DM	24D6	
			AT28HC16L-70LM	32L	
AT28HC16LN-70DM/883	24D3	Military/883C Class B, Fully Compliant (-55°C to 125°C)			
AT28HC16L-70DM/883	24D6				
AT28HC16L-70LM/883	32L				
90	80	0.5	AT28HC16LN-90DC	24D3	Commercial (0°C to 70°C)
			AT28HC16L-90DC	24D6	
			AT28HC16L-90JC	32J	
			AT28HC16L-90LC	32L	
			AT28HC16LN-90PC	24P3	
			AT28HC16L-90PC	24P6	
			AT28HC16L-90W	DIE	

Ordering Information

t _{ACC} (ns)	I _{CC} (mA)		Ordering Code	Package	Operation Range
	Active	Standby			
90	80	0.5	AT28HC16LN-90DI	24D3	Industrial (-40°C to 85°C)
			AT28HC16L-90DI	24D6	
			AT28HC16L-90JI	32J	
			AT28HC16L-90LJ	32L	
			AT28HC16LN-90PI	24P3	
			AT28HC16L-90PI	24P6	
			AT28HC16LN-90DM	24D3	Military (-55°C to 125°C)
			AT28HC16L-90DM	24D6	
			AT28HC16L-90LM	32L	
			AT28HC16LN-90DM/883	24D3	Military/883C Class B, Fully Compliant (-55°C to 125°C)
			AT28HC16L-90DM/883	24D6	
			AT28HC16L-90LM/883	32L	
45	80	0.5	5962-88676 04 JX	24D6	Military/883C Class B, Fully Compliant (-55°C to 125°C)
			5962-88676 04 LX	24D3	
			5962-88676 04 XX	32L	
55	80	0.5	5962-88676 03 JX	24D6	Military/883C Class B, Fully Compliant (-55°C to 125°C)
			5962-88676 03 LX	24D3	
			5962-88676 03 XX	32L	
70	80	0.5	5962-88676 02 JX	24D6	Military/883C Class B, Fully Compliant (-55°C to 125°C)
			5962-88676 02 LX	24D3	
			5962-88676 02 XX	32L	
90	80	0.5	5962-88676 01 JX	24D6	Military/883C Class B, Fully Compliant (-55°C to 125°C)
			5962-88676 01 LX	24D3	
			5962-88676 01 XX	32L	

2

Package Type	
24D3	24 Lead, 0.3" Wide, Non-Windowed, Cerdip
24D6	24 Lead, 0.6" Wide, Non-Windowed, Cerdip
32J	32 Lead, Plastic J-Lead Chip Carrier
32L	32 Pad, Non-Windowed, Ceramic Leadless Chip Carrier
24P3	24 Lead, 0.3" Wide, Plastic Dual-In-Line
24P6	24 Lead, 0.6" Wide, Plastic Dual-In-Line
W	Die





Ordering Information

t _{ACC} (ns)	I _{CC} (mA)		Ordering Code	Package	Operation Range
	Active	Standby			
45	80	60	AT28HC16N-45DC AT28HC16-45DC AT28HC16-45LC AT28HC16N-45PC AT28HC16-45PC	24D3 24D6 32L 24P3 24P6	Commercial (0°C to 70°C)
			AT28HC16N-45DI AT28HC16-45DI AT28HC16-45LI AT28HC16N-45PI AT28HC16-45PI	24D3 24D6 32L 24P3 24P6	Industrial (-40°C to 85°C)
55	80	60	AT28HC16N-55DC AT28HC16-55DC AT28HC16-55JC AT28HC16-55LC AT28HC16N-55PC AT28HC16-55PC	24D3 24D6 32J 32L 24P3 24P6	Commercial (0°C to 70°C)
			AT28HC16N-55DI AT28HC16-55DI AT28HC16-55JI AT28HC16-55LI AT28HC16N-55PI AT28HC16-55PI	24D3 24D6 32J 32L 24P3 24P6	Industrial (-40°C to 85°C)
			AT28HC16N-55DM AT28HC16-55DM AT28HC16-55LM	24D3 24D6 32L	Military (-55°C to 125°C)
			AT28HC16N-55DM/883 AT28HC16-55DM/883 AT28HC16-55LM/883	24D3 24D6 32L	Military/883C Class B, Fully Compliant (-55°C to 125°C)
70	80	60	AT28HC16N-70DC AT28HC16-70DC AT28HC16-70JC AT28HC16-70LC AT28HC16N-70PC AT28HC16-70PC	24D3 24D6 32J 32L 24P3 24P6	Commercial (0°C to 70°C)
			AT28HC16N-70DI AT28HC16-70DI AT28HC16-70JI AT28HC16-70LI AT28HC16N-70PI AT28HC16-70PI	24D3 24D6 32J 32L 24P3 24P6	Industrial (-40°C to 85°C)
			AT28HC16N-70DM AT28HC16-70DM AT28HC16-70LM	24D3 24D6 32L	Military (-55°C to 125°C)
			AT28HC16N-70DM/883 AT28HC16-70DM/883 AT28HC16-70LM/883	24D3 24D6 32L	Military/883C Class B, Fully Compliant (-55°C to 125°C)

AT28HC16/L

Ordering Information

tACC (ns)	Icc (mA)		Ordering Code	Package	Operation Range
	Active	Standby			
90	80	60	AT28HC16N-90DC	24D3	Commercial (0°C to 70°C)
			AT28HC16-90DC	24D6	
			AT28HC16-90JC	32J	
			AT28HC16-90LC	32L	
			AT28HC16N-90PC	24P3	
			AT28HC16-90PC	24P6	
			AT28HC16-90W	DIE	Industrial (-40°C to 85°C)
			AT28HC16N-90DI	24D3	
			AT28HC16-90DI	24D6	
			AT28HC16-90JI	32J	
			AT28HC16-90LI	32L	
			AT28HC16N-90PI	24P3	
			AT28HC16-90PI	24P6	Military (-55°C to 125°C)
			AT28HC16N-90DM	24D3	
			AT28HC16-90DM	24D6	
			AT28HC16-90LM	32L	Military/883C Class B, Fully Compliant (-55°C to 125°C)
AT28HC16N-90DM/883	24D3				
AT28HC16-90DM/883	24D6				
AT28HC16-90LM/883	32L				

2

Package Type

24D3	24 Lead, 0.3" Wide, Non-Windowed, Cerdip
24D6	24 Lead, 0.6" Wide, Non-Windowed, Cerdip
32J	32 Lead, Plastic J-Lead Chip Carrier
32L	32 Pad, Non-Windowed, Ceramic Leadless Chip Carrier
24P3	24 Lead, 0.3" Wide, Plastic Dual-In-Line
24P6	24 Lead, 0.6" Wide, Plastic Dual-In-Line
W	Die

