

[illegible]

DESC FORM 193
SEP 87

U.S. GOVERNMENT PRINTING OFFICE: 1987 — 748-129/60911
5962-E804

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part number. The complete part number shall be as shown in the following example:

5962-88571	01	C	X
Drawing number	Device type (1.2.1)	Case outline (1.2.2)	Lead finish per MIL-M-38510

1.2.1 Device type. The device type shall identify the circuit function as follows:

Device type	Generic number	Circuit function
01	1596	Balanced modulator/demodulator

1.2.2 Case outlines. The case outlines shall be as designated in appendix C of MIL-M-38510, and as follows:

Outline letter	Case outline
C	D-1 (14-lead, .785" x .310" x .200"), dual-in-line package
I	A-2 (10-lead, .370" x .185"), can package

1.3 Absolute maximum ratings.

Differential input signal:

+V _C to -V _C	+5.0 V dc
+V _S to -V _S	*(5 + I _B R _e) V dc 1/
Maximum bias current (I _B)	10 mA

Applied voltage (delta V):

+V _O to +V _C	30 V dc
-V _C to +V _S	30 V dc
-V _O to +V _C	30 V dc
-V _O to -V _C	30 V dc
+V _C to -V _S	30 V dc
+V _C to +V _S	30 V dc
-V _C to -V _S	30 V dc
+V _O to -V _C	30 V dc
G _A to V _B	30 V dc
G _B to V _B	30 V dc

Thermal resistance, junction-to-ambient (θ_{JA}):

Case C	180°C/W
Case I	200°C/W
Thermal resistance, junction-to-case (θ _{JC})	See MIL-M-38510, appendix C
Case storage temperature	-65°C to +150°C

1.4 Recommended operating conditions.

Ambient operating temperature range (T _A)	-55°C to +125°C
---	-----------------

1/ R_e = Emitter resistor between gain adjust pins.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-88571	
		REVISION LEVEL	SHEET 2

DESC FORM 193A
SEP 87

★ U. S. GOVERNMENT PRINTING OFFICE: 1989-549-904

2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1. Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2. Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full ambient operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-88571
		REVISION LEVEL	SHEET 3

DESC FORM 193A
SEP 87

★ U. S. GOVERNMENT PRINTING OFFICE: 1968-549-904

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C < T _A < +125°C unless otherwise specified 1/	Group A subgroups	Limits		Unit
				Min	Max	
Input bias current $\frac{I_{+S} + I_{-S}}{2}$	I _B Signal		1, 2, 3		25	μA
Input bias current $\frac{I_{+C} + I_{-C}}{2}$	I _B Carrier		1, 2, 3		25	μA
Input offset current I _{+S} - I _{-S}	I _{IO} Signal		1, 2, 3		5	μA
Input offset current I _{+C} - I _{-C}	I _{IO} Carrier		1, 2, 3		5	μA
Power supply current I ₊₀ + I ₋₀	I _{CC}		1, 2, 3		3	mA
Power supply current	I _{EE}		1, 2, 3		4	mA
Output offset current I ₊₀ - I ₋₀	I _O		1, 2, 3		50	μA
Differential output voltage swing capability	V _O	T _A = +25°C	4	12.0		V _{p-p}
Signal gain	A _{VS}	+V _S = 100 mV rms, f _S = 1 kHz; V _C = 0.5 V T _A = +25°C	4	2.5		V/V
Carrier feed-thru	V _{CFT1}	f _C = 1 kHz, V _C = 300 mV _{p-p} square wave: Offset adjusted to zero, T _A = +25°C	4		200	μV rms

See footnote at end of table.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-88571
		REVISION LEVEL	SHEET 4

DESC FORM 193A
SEP 87

★ U. S. GOVERNMENT PRINTING OFFICE: 1988-549-904

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C ≤ T _A ≤ +125°C unless otherwise specified 1/	Group A subgroups	Limits		Unit
				Min	Max	
Carrier feed-thru	VCFT2	f _C = 1 kHz, V _C = 300 mV _{p-p} square wave: Offset not adjusted T _A = +25°C	4		100	mV rms
Carrier suppression	VCS	f _S = 10 kHz, 300 mV (rms), f _C = 500 kHz, 60 mV (rms) sine wave, T _A = +25°C	4	50		dB

1/ V⁺ = +12 V dc, V⁻ = -8.0 V dc, Bias current (I_B) = 1.0 mA dc, R_L = 3.9 kΩ, R_e = 1.0 kΩ.

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) T_A = +125°C, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-88571
		REVISION LEVEL	SHEET 5

DESC FORM 193A
SEP 87

* U. S. GOVERNMENT PRINTING OFFICE: 1988-549-904

Device type	01	
Case outlines	C	I
Terminal number	Terminal symbol	
1	V _S ⁺	V _S ⁺
2	GA	GA
3	GB	GB
4	V _S ⁻	V _S ⁻
5	V _B	V _B
6	V _O ⁺	V _O ⁺
7	NC	V _C ⁺
8	V _C ⁺	V _C ⁻
9	NC	V _O ⁻
10	V _C ⁻	V ₋
11	NC	
12	V _O ⁻	
13	NC	
14	V ₋	

NC = No connect

FIGURE 1. Terminal connections.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-88571	
		REVISION LEVEL	SHEET 6

DESC FORM 193A
SEP 87

★ U. S. GOVERNMENT PRINTING OFFICE: 1988-846-004

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 5, 6, 7, 8, 9, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test conditions, method 1005 of MIL-STD-883.
 - (1) Test condition A using the circuit submitted with the certificate of compliance (see 3.5 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
 - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	1,2,3
Final electrical test parameters (method 5004)	1*,2,3,4
Group A test requirements (method 5005)	1,2,3,4
Groups C and D end-point electrical parameters (method 5005)	1,2,3

* PDA applies to subgroup 1.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-88571
		REVISION LEVEL	SHEET 7

DESC FORM 193A
SEP 87

★ U. S. GOVERNMENT PRINTING OFFICE: 1988-549-904

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

6.4 Approved source of supply. An approved source of supply is listed herein. Additional sources will be added as they become available. The vendor listed herein has agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number <u>1/</u>
5962-8857101CX	04713	1596/BCAJC
5962-8857101IX	04713	1596/BIAJC

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE number

04713

Vendor name and address

Motorola, Incorporated
7402 S. Price Road
Tempe, AZ 85283

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-88571
		REVISION LEVEL	SHEET 8

DESC FORM 193A
SEP 87

★ U. S. GOVERNMENT PRINTING OFFICE: 1985-549-904