




PRELIMINARY SPECIFICATION MOS FIELD EFFECT POWER TRANSISTOR ARRAY

PA1552H

FAST SWITCHING N-CHANNEL SILICON POWER MOS FET ARRAY

PACKAGE DIMENSIONS in millimeters



2,4,6,8:Gate
3,5,7,9:Drain
1,10:Source

FEATURES

- Suitable for switching power supplies, actuator controls, and pulse circuits
- Low $R_{DS(on)}$
- No second breakdown

ABSOLUTE MAXIMUM RATINGS ($T_a=25^\circ\text{C}$)

Drain to Source Voltage	V_{DS}	60V
Gate to Source Voltage	V_{GS}	$\pm 20V$
Continuous Drain Current	$I_D(DC)$	5A
Total Power Dissipation	PT	3.5W
Total Power Dissipation	PT $\pm$	22W
Channel Temperature	T_{ch}	150 $^\circ\text{C}$
Storage Temperature	T_{stg}	-55~150 $^\circ\text{C}$ $\pm T_c=25^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Drain Leakage Current	I_{DSS}			10	μA	$V_{DS}=60V, V_{GS}=0$
Gate to Source Leakage Current	I_{GSS}			± 100	nA	$V_{GS}=\pm 20V, V_{DS}=0$
Gate to Source Cutoff Voltage	$V_{GS(off)}$	1.0		2.5	V	$V_{DS}=10V, I_D=1\text{mA}$
Forward Transfer Admittance	$ y_{fs} $	5			S	$V_{DS}=10V, I_D=2A$
Drain to Source On-State Resistance	$R_{DS(on)}$		0.11	0.30	Ω	$V_{GS}=10V, I_D=5A$
			0.17	0.35	Ω	$V_{GS}=4V, I_D=5A$
Input Capacitance	C_{iss}		900		pF	$V_{DS}=10V$
Output Capacitance	C_{oss}		350		pF	$V_{GS}=0$
Reverse Transfer Capacitance	C_{rss}		50		pF	$f=1\text{MHz}$
Turn-On Delay Time	$t_d(on)$		10		ns	$I_D=2A, V_{GS}=50V$
Rise Time	t_r		40		ns	$V_{GS(on)}=10V$
Turn-Off Delay Time	$t_d(off)$		110		ns	$R_L=17\Omega$
Fall Time	t_f		20		ns	$R_{in}=10\Omega$



Mar.29.1986

ID-1779


uPA1552H

NEC ELECTRON DEVICE


TURN-ON AND TURN-OFF TIME TEST CIRCUIT




DERATING FACTOR OF FORWARD BIAS SAFE OPERATING AREA




FORWARD BIAS SAFE OPERATING AREA



TOTAL POWER DISSIPATION vs. CASE TEMPERATURE




DRAIN CURRENT vs. DRAIN TO SOURCE VOLTAGE




NEC ELECTRON DEVICE

UD 115524


FORWARD TRANSFER ADMITTANCE
vs. DRAIN CURRENT




SOURCE TO DRAIN DIODE
FORWARD VOLTAGE




CAPACITANCE vs. DRAIN TO
SOURCE VOLTAGE




DRAIN TO SOURCE ON-STATE RESISTANCE
vs. GATE TO SOURCE VOLTAGE




DRAIN TO SOURCE ON-STATE RESISTANCE
vs. CHANNEL TEMPERATURE




DRAIN TO SOURCE ON-STATE RESISTANCE
vs. DRAIN CURRENT




TRANSFER CHARACTERISTICS



GATE TO SOURCE CUTOFF VOLTAGE vs. CHANNEL TEMPERATURE



TURN-ON AND TURN-OFF TIME



VEC Corporation

INTERNATIONAL ELECTRON DEVICES DIV.
 NEC Building, 33-1, Shiba Gochome
 Minato-ku, Tokyo 108, Japan
 Tel: Tokyo 454-1111
 Telex Address: NECTOK J22886
 Cable Address: MICROPHONE TOKYO