

## MATERIAL DATA SHEET

Types : V15H, V40H, V80H, V65HT, V110HT, V150H, V200H, V250H, CP300H, V300H, V350H  
 Chemical system : NiOOH | KOH | MH - Rechargeable Date: 1999-03-22  
 Voltage : 1.2V

### 1. TYPE, CAPACITY AND WEIGHT

Cell Type	Typical Capacity (mAh)	Weight (g)
V15H	16	1,3
V40H	43	1,7
V80H	80	4
V65HT	70	4
V110HT	120	6
V150H	150	6
V200H	220	7
V250H	250	10
CP300H	300	11
V300H	320	12
V350H	380	13

### 2. INGREDIENTS

		Approx. percentage (%) of total weight
Active materials*	- Nickel hydroxide - Ni(OH) <sub>2</sub> - Hydrogen storage mischmetal alloy - Potassium hydroxide - KOH	10 10 - 11 8
Passive materials*	- Steel - Metallic nickel - Plastic	40 - 50 20 - 25 3

\* All cell types are sealed button cells, no chemical hazard will be posed as long as the cell remains in sealed condition.

### 3. SAFETY GUIDELINE

- 3.1 Keep out of the reach of children. If swallowed, contact a physician at once.
- 3.2 Do not incinerate or mutilate, may burst or release toxic materials.
- 3.3 Do not short circuit, may cause burns.
- 3.4 Do not solder the battery directly.
- 3.5 Restrict charging current and time to the recommended value.
- 3.6 Observe charging temperature: 0 to +65°C.
- 3.7 Battery compartment should provide sufficient space for battery to expand in case of abuse.
- 3.8 Either battery compartment or battery connector should have a design that makes it impossible to place the battery in reverse polarity.
- 3.9 Equipment intended for use by children should have tamper-proof battery compartment.
- 3.10 Battery of different electrochemical system, grades, or brands should not be mixed.
- 3.11 Battery disposal method should be in accordance with local and state regulations.

4. V15H, V40H, V150H, V250H, V300H and CP300H are UL recognized components: category BBET2, file no. MH13654.

Prepared by : E Pytlík

Approved by : M Kilb