

E-Series Plug-In Mixer

5 - 1000 MHz

EMA-2CM

V3.00

Features

- LO Power: +7 dBm
- Up to +1 dBm RF

Specifications @ 25°C

Frequency Range		
RF		5 - 1000 MHz
LO		5 - 1000 MHz
IF		DC - 1000 MHz
Conversion Loss (dB)	Typical	Maximum
10 - 500 MHz	6.0	7.0
5 - 1000 MHz	6.5	8.5
Isolation (dB)	Typical	Minimum
LO to RF		
5 - 50 MHz	60	50
50 - 500 MHz	35	30
500 - 1000 MHz	30	25
LO to IF		
5 - 50 MHz	50	45
50 - 500 MHz	30	25
500 - 1000 MHz	25	20

Operating Characteristics

Impedance	50 Ohms Nominal
RF input for 1dB Compression	+ 1 dBm


Ordering Information

Part No.	Packaging
EMA-2CM	Tube
EMA-2CMTR	Forward Tape & Reel

Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	50 mW
Peak IF Current	40 mA
Storage Temperature	-55°C to 100°C
Operating Temperature	-55°C to 100°C
Pin Temperature (10 Seconds)	260°C

R-1



Dimensions in () are in mm.
 Unless Otherwise Noted: .x = ±0.04 (1.00)
 .xx = ±0.02 (0.50)
 .xxx = ±0.010 (0.250)
 WEIGHT (APPROX.): 0.16 OUNCES 4.4 GRAMS

Pin Configuration

Function	Pin No.
LO	8
RF	1
IF*	3,4
Ground	2,5,6,7
Case Ground	2,5,6,7

*IF pins must be connected together externally.

S 0028 B