



# 3.3V CMOS 18-BIT BUS-INTERFACE FLIP-FLOP WITH 3-STATE OUTPUTS AND BUS-HOLD

IDT74ALVCH16823

## FEATURES:

- 0.5 MICRON CMOS Technology
- Typical  $t_{sk(o)}$  (Output Skew) < 250ps
- ESD > 2000V per MIL-STD-883, Method 3015;  
> 200V using machine model (C = 200pF, R = 0)
- 0.635mm pitch SSOP, 0.50mm pitch TSSOP,  
and 0.40mm pitch TVSOP packages
- Extended commercial range of  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$
- $V_{cc} = 3.3\text{V} \pm 0.3\text{V}$ , Normal Range
- $V_{cc} = 2.7\text{V}$  to  $3.6\text{V}$ , Extended Range
- $V_{cc} = 2.5\text{V} \pm 0.2\text{V}$
- CMOS power levels ( $0.4\mu\text{W}$  typ. static)
- Rail-to-Rail output swing for increased noise margin

## Drive Features for ALVCH16823:

- High Output Drivers:  $\pm 24\text{mA}$
- Suitable for heavy loads

## APPLICATIONS:

- 3.3V High Speed Systems
- 3.3V and lower voltage computing systems

## DESCRIPTION:

This 18-bit bus-interface flip-flop is built using advanced dual metal CMOS technology. The ALVCH16823 features 3-state outputs designed specifically for driving highly capacitive or relatively low-impedance loads. The device is particularly suitable for implementing wider buffer

registers, I/O ports, bidirectional bus drivers with parity, and working registers.



The ALVCH16823 can be used as two 9-bit flip-flops or one 18-bit flip-flop. With the clock-enable ( $\overline{\text{CLKEN}}$ ) input low, the D-type flip-flops enter data on the low-to-high transitions of the clock. Taking  $\overline{\text{CLKEN}}$  high disables the clock buffer, thus latching the outputs. Taking the clear ( $\overline{\text{CLR}}$ ) input low causes the Q outputs to go low independently of the clock.

A buffered output-enable ( $\overline{\text{OE}}$ ) input can be used to place the nine outputs in either a normal logic state (high or low logic levels) or a high-impedance state. In the high-impedance state, the outputs neither load nor drive the bus lines significantly. The high-impedance state and increased drive provide the capability to drive bus lines without need for interface or pullup components. The output-enable ( $\overline{\text{OE}}$ ) input does not affect the internal operation of the flip-flops. Old data can be retained or new data can be entered while the outputs are in the high-impedance state.

The ALVCH16823 has been designed with a  $\pm 24\text{mA}$  output driver. This driver is capable of driving a moderate to heavy load while maintaining speed performance.

The ALVCH16823 has "bus-hold" which retains the inputs' last state whenever the input goes to a high impedance. This prevents floating inputs and eliminates the need for pull-up/down resistor.


## Functional Block Diagram



EXTENDED COMMERCIAL TEMPERATURE RANGE

APRIL 1999

## PIN CONFIGURATION



SSOP/TSSOP/TVSOP  
TOP VIEW

## PIN DESCRIPTION

| Pin Names                   | Description                  |
|-----------------------------|------------------------------|
| xDx                         | Data Inputs <sup>(1)</sup>   |
| xCLK                        | Clock Inputs                 |
| x $\overline{\text{CLKEN}}$ | Clock Enable Inputs          |
| xQx                         | 3-State Outputs              |
| x $\overline{\text{OE}}$    | 3-State Output Enable Inputs |
| xCLR                        | Clear Inputs                 |

### NOTE:

- These pins have "Bus-Hold." All other pins are standard inputs, outputs, or I/Os.

## ABSOLUTE MAXIMUM RATING <sup>(1)</sup>

| Symbol                             | Description                                                                      | Max.                           | Unit |
|------------------------------------|----------------------------------------------------------------------------------|--------------------------------|------|
| V <sub>TERM</sub> <sup>(2)</sup>   | Terminal Voltage with Respect to GND                                             | − 0.5 to + 4.6                 | V    |
| V <sub>TERM</sub> <sup>(3)</sup>   | Terminal Voltage with Respect to GND                                             | − 0.5 to V <sub>CC</sub> + 0.5 | V    |
| T <sub>STG</sub>                   | Storage Temperature                                                              | − 65 to + 150                  | °C   |
| I <sub>OUT</sub>                   | DC Output Current                                                                | − 50 to + 50                   | mA   |
| I <sub>IK</sub>                    | Continuous Clamp Current, V <sub>I</sub> < 0 or V <sub>I</sub> > V <sub>CC</sub> | ± 50                           | mA   |
| I <sub>OK</sub>                    | Continuous Clamp Current, V <sub>O</sub> < 0                                     | − 50                           | mA   |
| I <sub>CC</sub><br>I <sub>SS</sub> | Continuous Current through each V <sub>CC</sub> or GND                           | ±100                           | mA   |

NEW16link

### NOTES:

- Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.
- V<sub>CC</sub> terminals.
- All terminals except V<sub>CC</sub>.

## CAPACITANCE (T<sub>A</sub> = +25°C, f = 1.0MHz)

| Symbol           | Parameter <sup>(1)</sup> | Conditions            | Typ. | Max. | Unit |
|------------------|--------------------------|-----------------------|------|------|------|
| C <sub>IN</sub>  | Input Capacitance        | V <sub>IN</sub> = 0V  | 5    | 7    | pF   |
| C <sub>OUT</sub> | Output Capacitance       | V <sub>OUT</sub> = 0V | 7    | 9    | pF   |
| C <sub>I/O</sub> | I/O Port Capacitance     | V <sub>IN</sub> = 0V  | 7    | 9    | pF   |

NEW16link

### NOTE:

- As applicable to the device type.

## FUNCTION TABLE (each 9-bit flip-flop) <sup>(1)</sup>

| Inputs                   |                           |                             |      |     | Output         |
|--------------------------|---------------------------|-----------------------------|------|-----|----------------|
| x $\overline{\text{OE}}$ | x $\overline{\text{CLR}}$ | x $\overline{\text{CLKEN}}$ | xCLK | xDx | xQx            |
| L                        | L                         | X                           | X    | X   | L              |
| L                        | H                         | L                           | ↑    | H   | H              |
| L                        | H                         | L                           | ↑    | L   | L              |
| L                        | H                         | L                           | L    | X   | Q <sub>o</sub> |
| L                        | H                         | H                           | X    | X   | Q <sub>o</sub> |
| H                        | X                         | X                           | X    | X   | Z              |

### NOTE:

- H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Don't Care  
Z = High-Impedance  
↑ = LOW-to-HIGH Transition  
Q<sub>o</sub> = Indicates the previous state

## DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE

Following Conditions Apply Unless Otherwise Specified:

Operating Condition: TA = - 40°C to +85°C

| Symbol                                                | Parameter                                              | Test Conditions                                                    |                                                                                | Min. | Typ. <sup>(1)</sup> | Max.  | Unit |
|-------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------------------|--------------------------------------------------------------------------------|------|---------------------|-------|------|
| V <sub>IH</sub>                                       | Input HIGH Voltage Level                               | V <sub>CC</sub> = 2.3V to 2.7V                                     |                                                                                | 1.7  | —                   | —     | V    |
|                                                       |                                                        | V <sub>CC</sub> = 2.7V to 3.6V                                     |                                                                                | 2    | —                   | —     |      |
| V <sub>IL</sub>                                       | Input LOW Voltage Level                                | V <sub>CC</sub> = 2.3V to 2.7V                                     |                                                                                | —    | —                   | 0.7   | V    |
|                                                       |                                                        | V <sub>CC</sub> = 2.7V to 3.6V                                     |                                                                                | —    | —                   | 0.8   |      |
| I <sub>IH</sub>                                       | Input HIGH Current                                     | V <sub>CC</sub> = 3.6V                                             | V <sub>I</sub> = V <sub>CC</sub>                                               | —    | —                   | ± 5   | μA   |
| I <sub>IL</sub>                                       | Input LOW Current                                      | V <sub>CC</sub> = 3.6V                                             | V <sub>I</sub> = GND                                                           | —    | —                   | ± 5   |      |
| I <sub>OZH</sub>                                      | High Impedance Output Current<br>(3-State Output pins) | V <sub>CC</sub> = 3.6V                                             | V <sub>O</sub> = V <sub>CC</sub>                                               | —    | —                   | ± 10  | μA   |
| I <sub>OZL</sub>                                      |                                                        |                                                                    | V <sub>O</sub> = GND                                                           | —    | —                   | ± 10  | μA   |
| V <sub>IK</sub>                                       | Clamp Diode Voltage                                    | V <sub>CC</sub> = 2.3V, I <sub>IN</sub> = − 18mA                   |                                                                                | —    | − 0.7               | − 1.2 | V    |
| V <sub>H</sub>                                        | Input Hysteresis                                       | V <sub>CC</sub> = 3.3V                                             |                                                                                | —    | 100                 | —     | mV   |
| I <sub>CC</sub><br>I <sub>CC</sub><br>I <sub>CC</sub> | Quiescent Power Supply Current                         | V <sub>CC</sub> = 3.6V<br>V <sub>IN</sub> = GND or V <sub>CC</sub> |                                                                                | —    | 0.1                 | 40    | μA   |
| ΔI <sub>CC</sub>                                      |                                                        | Quiescent Power Supply Current Variation                           | One input at V <sub>CC</sub> − 0.6V,<br>other inputs at V <sub>CC</sub> or GND |      | —                   | —     |      |

NEW16link

### NOTE:

1. Typical values are at VCC = 3.3V, +25°C ambient.

## BUS-HOLD CHARACTERISTICS

| Symbol         | Parameter <sup>(1)</sup>         | Test Conditions |                | Min. | Typ. <sup>(2)</sup> | Max.  | Unit |
|----------------|----------------------------------|-----------------|----------------|------|---------------------|-------|------|
| IBHH<br>IBHL   | Bus-Hold Input Sustain Current   | VCC = 3.0V      | VI = 2.0V      | - 75 | —                   | —     | µA   |
|                |                                  |                 | VI = 0.8V      | 75   | —                   | —     |      |
| IBHH<br>IBHL   | Bus-Hold Input Sustain Current   | VCC = 2.3V      | VI = 1.7V      | - 45 | —                   | —     | µA   |
|                |                                  |                 | VI = 0.7V      | 45   | —                   | —     |      |
| IBHHO<br>IBHLO | Bus-Hold Input Overdrive Current | VCC = 3.6V      | VI = 0 to 3.6V | —    | —                   | ± 500 | µA   |

NEW16link

### NOTES:

1. Pins with Bus-hold are identified in the pin description.
2. Typical values are at VCC = 3.3V, +25°C ambient.

**OUTPUT DRIVE CHARACTERISTICS**

| Symbol | Parameter           | Test Conditions <sup>(1)</sup> |               | Min.      | Max. | Unit |
|--------|---------------------|--------------------------------|---------------|-----------|------|------|
| VOH    | Output HIGH Voltage | VCC = 2.3V to 3.6V             | IOH = - 0.1mA | VCC - 0.2 | —    | V    |
|        |                     | VCC = 2.3V                     | IOH = - 6mA   | 2         | —    |      |
|        |                     | VCC = 2.3V                     | IOH = - 12mA  | 1.7       | —    |      |
|        |                     | VCC = 2.7V                     |               | 2.2       | —    |      |
|        |                     | VCC = 3.0V                     |               | 2.4       | —    |      |
|        |                     | VCC = 3.0V                     | IOH = - 24mA  | 2         | —    |      |
| VOL    | Output LOW Voltage  | VCC = 2.3V to 3.6V             | IOL = 0.1mA   | —         | 0.2  | V    |
|        |                     | VCC = 2.3V                     | IOL = 6mA     | —         | 0.4  |      |
|        |                     |                                | IOL = 12mA    | —         | 0.7  |      |
|        |                     | VCC = 2.7V                     | IOL = 12mA    | —         | 0.4  |      |
|        |                     | VCC = 3.0V                     | IOL = 24mA    | —         | 0.55 |      |

**NOTE:**

NEW16link

1. VIH and VIL must be within the min. or max. range shown in the DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE table for the appropriate VCC range. TA = - 40°C to + 85°C.

**OPERATING CHARACTERISTICS, TA = 25°C**

| Symbol | Parameter                                         | Test Conditions     | VCC = 2.5V ± 0.2V | VCC = 3.3V ± 0.3V | Unit |
|--------|---------------------------------------------------|---------------------|-------------------|-------------------|------|
|        |                                                   |                     | Typical           | Typical           |      |
| CPD    | Power Dissipation Capacitance<br>Outputs enabled  | CL = 0pF, f = 10Mhz | 27                | 30                | pF   |
| CPD    | Power Dissipation Capacitance<br>Outputs disabled |                     | 16                | 18                | pF   |

**SWITCHING CHARACTERISTICS (1)**

| Symbol                               | Parameter                                               | V <sub>CC</sub> = 2.5V ± 0.2V |      | V <sub>CC</sub> = 2.7V |      | V <sub>CC</sub> = 3.3V ± 0.3V |      | Unit |
|--------------------------------------|---------------------------------------------------------|-------------------------------|------|------------------------|------|-------------------------------|------|------|
|                                      |                                                         | Min.                          | Max. | Min.                   | Max. | Min.                          | Max. |      |
| f <sub>MAX</sub>                     |                                                         | 150                           | —    | 150                    | —    | 150                           | —    | MHz  |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay<br>xCLK to xQx                        | 1                             | 5.8  | —                      | 5.2  | 1                             | 4.5  | ns   |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay<br>xCLR to xQx                        | 1                             | 5.4  | —                      | 5.2  | 1.2                           | 4.6  | ns   |
| t <sub>PZH</sub><br>t <sub>PZL</sub> | Output Enable Time<br>xOE to xQx                        | 1                             | 6    | —                      | 5.7  | 1                             | 4.8  | ns   |
| t <sub>PHZ</sub><br>t <sub>PLZ</sub> | Output Disable Time<br>xOE to xQx                       | 1.1                           | 5.4  | —                      | 4.7  | 1.3                           | 4.5  | ns   |
| t <sub>w</sub>                       | Pulse Width, $\overline{\text{xCLR}}$ LOW               | 3.3                           | —    | 3.3                    | —    | 3.3                           | —    | ns   |
| t <sub>w</sub>                       | Pulse Width, xCLK HIGH or LOW                           | 3.3                           | —    | 3.3                    | —    | 3.3                           | —    | ns   |
| t <sub>su</sub>                      | Setup Time, $\overline{\text{xCLR}}$ inactive           | 0.7                           | —    | 0.7                    | —    | 0.8                           | —    | ns   |
| t <sub>su</sub>                      | Setup Time, data LOW before xCLK↑                       | 1.4                           | —    | 1.6                    | —    | 1.3                           | —    | ns   |
| t <sub>su</sub>                      | Setup Time, data HIGH before xCLK↑                      | 1.1                           | —    | 1.1                    | —    | 1                             | —    | ns   |
| t <sub>su</sub>                      | Setup Time, $\overline{\text{xCLKEN}}$ LOW before xCLK↑ | 1.8                           | —    | 1.9                    | —    | 1.5                           | —    | ns   |
| t <sub>h</sub>                       | Hold Time, data LOW after xCLK↑                         | 0.4                           | —    | 0.5                    | —    | 0.5                           | —    | ns   |
| t <sub>h</sub>                       | Hold Time, data HIGH after xCLK↑                        | 0.7                           | —    | 0.1                    | —    | 0.8                           | —    | ns   |
| t <sub>h</sub>                       | Hold Time, $\overline{\text{xCLKEN}}$ LOW after xCLK↑   | 0.2                           | —    | 0.3                    | —    | 0.4                           | —    | ns   |
| t <sub>SK(O)</sub>                   | Output Skew(2)                                          | —                             | —    | —                      | —    | —                             | 500  | ps   |

**NOTES:**

1. See test circuits and waveforms. T<sub>A</sub> = − 40°C to + 85°C.
2. Skew between any two outputs of the same package and switching in the same direction.


## TEST CIRCUITS AND WAVEFORMS:

### TEST CONDITIONS

| Symbol            | Vcc(1)= 3.3V±0.3V | Vcc(1)= 2.7V | Vcc(2)= 2.5V±0.2V   | Unit |
|-------------------|-------------------|--------------|---------------------|------|
| V <sub>LOAD</sub> | 6                 | 6            | 2 x V <sub>cc</sub> | V    |
| V <sub>IH</sub>   | 2.7               | 2.7          | V <sub>cc</sub>     | V    |
| V <sub>T</sub>    | 1.5               | 1.5          | V <sub>cc</sub> / 2 | V    |
| V <sub>LZ</sub>   | 300               | 300          | 150                 | mV   |
| V <sub>HZ</sub>   | 300               | 300          | 150                 | mV   |
| C <sub>L</sub>    | 50                | 50           | 30                  | pF   |

NEW16link

### TEST CIRCUITS FOR ALL OUTPUTS



#### DEFINITIONS:

C<sub>L</sub> = Load capacitance: includes jig and probe capacitance.  
R<sub>T</sub> = Termination resistance: should be equal to Z<sub>OUT</sub> of the Pulse Generator.

#### NOTES:


1. Pulse Generator for All Pulses: Rate ≤ 10MHz; t<sub>F</sub> ≤ 2.5ns; t<sub>R</sub> ≤ 2.5ns.
2. Pulse Generator for All Pulses: Rate ≤ 10MHz; t<sub>F</sub> ≤ 2ns; t<sub>R</sub> ≤ 2ns.

### SWITCH POSITION

| Test                                    | Switch            |
|-----------------------------------------|-------------------|
| Open Drain<br>Disable Low<br>Enable Low | V <sub>LOAD</sub> |
| Disable High<br>Enable High             | GND               |
| All Other tests                         | Open              |

NEW16link

### OUTPUT SKEW - t<sub>SK</sub> (x)




$$t_{SK}(x) = |t_{PLH2} - t_{PLH1}| \text{ or } |t_{PHL2} - t_{PHL1}|$$

ALVC Link

#### NOTES:


1. For t<sub>SK</sub>(o) OUTPUT1 and OUTPUT2 are any two outputs.
2. For t<sub>SK</sub>(b) OUTPUT1 and OUTPUT2 are in the same bank.

### PROPAGATION DELAY



ALVC Link

### ENABLE AND DISABLE TIMES




ALVC Link

#### NOTE:


1. Diagram shown for input Control Enable-LOW and input Control Disable-HIGH.

### SET-UP, HOLD, AND RELEASE TIMES



ALVC Link

### PULSE WIDTH



ALVC Link

## ORDERING INFORMATION

| IDT         | XX       | ALVC   | X           | XXX     | XXX | XX |                                                     |
|-------------|----------|--------|-------------|---------|-----|----|-----------------------------------------------------|
| Temp. Range | Bus-Hold | Family | Device Type | Package |     |    |                                                     |
|             |          |        |             |         | PV  |    | Shrink Small Outline Package (SO56-1)               |
|             |          |        |             |         | PA  |    | Thin Shrink Small Outline Package (SO56-2)          |
|             |          |        |             |         | PF  |    | Thin Very Small Outline Package (SO56-3)            |
|             |          |        |             |         | 823 |    | 18-Bit Bus-Interface Flip-Flop with 3-State Outputs |
|             |          |        |             |         | 16  |    | Double-Density with Resistors, $\pm 24\text{mA}$    |
|             |          |        |             |         | H   |    | Bus-Hold                                            |
|             |          |        |             |         | 74  |    | $-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$      |



**CORPORATE HEADQUARTERS**  
2975 Stender Way  
Santa Clara, CA 95054

**for SALES:**  
800-345-7015 or 408-727-6116  
fax: 408-492-8674  
[www.idt.com](http://www.idt.com)\*

*\*To search for sales office near you, please click the sales button found on our home page or dial the 800# above and press 2.*  
The IDT logo is a registered trademark of Integrated Device Technology, Inc.