

Stratos

SLC-25-C-1-x-R6 Optical Transceiver

Connectivity for
Business Critical Continuity™

InfiniBand Applications – 2.5 GBaud
850nm SFF 2x5, +3.3V



Product Overview

The Emerson Network Power Connectivity Solutions SLC-25-C-1-x-R6 Small Form Factor (SFF) optical transceivers are high performance integrated duplex data links for bi-directional communication over multimode fiber. The SLC-25-C-1-x-R6 module is specifically designed to be used in multimode InfiniBand applications with data rates up to 2.5GBaud. The SLC-25-C-1-x-R6 transceivers are provided with the LC receptacle which is compatible with the industry standard LC connector. The Stratos Lightwave SFF transceivers measure 0.532 inches in width. These transceivers provide double port densities by fitting twice the number of transceivers into the same board space as a 1x9 transceiver. The optoelectronic transceiver module is a Class 1 Laser product compliant with FDA Radiation Performance Standards, 21 CFR Subchapter J. This component is also Class 1 Laser compliant according to International Safety Standard IEC-825-1.

Ordering Information

SLC - 25 - C - 1 - X - R6

Grounding Clip

N=No Clip
E=Individual Clip (.6" Center)
K=Extended Clip (.6" Center)
G=Gang Clip (.55" Center)

Key Features & Benefits

- 2.5Gbps InfiniBand Compliant
- Die Cast Metal Package
- TTL Signal Detect Output
- Transmitter Disable Input
- Low Profile Fits Mezzanine Card Applications
- 100Ω Differential AC Coupled CML Level Outputs
- Single +3.3V Power Supply
- Wave Solderable / Aqueous Washable
- Class 1 Laser Safety Compliant
- RoHS Compliant
- UL 1950 Approved

Module Specifications – Electrical: $-5^{\circ}\text{C} < \text{Tc} < +80^{\circ}\text{C}; +3.0\text{V} < \text{Vcc} < +3.6\text{V}$

Parameter	Sym	MIN	Typ	MAX	Unit	Notes
Supply Current	I_{CC}		150	200	mA	
Transmitter						
CML/PECL Inputs (Differential)		400		2500	mVpp	AC Coupled Inputs
Input Impedance	Z_{in}	85	100	115	Ω	
TX_DISABLE Input Voltage – High	V_{IH}	2.0		$V_{CC}+0.3$	V	
TX_DISABLE Input Voltage – Low	V_{IL}	0		0.8	V	
Receiver						
CML Outputs (Differential)		400	600	1000	mVpp	AC Coupled Outputs
Output Impedance (Differential)	Z_{in}	90	100	110	Ω	
Total Contributed Jitter	T_j			68	pS	Measured with 2^7-1 PRBS
TTL Signal Detect Output – Low				0.8	V	$I_{OL} = -1.6\text{mA}$, 1TTL unit load
TTL Signal Detect Output – High		2.4	3		V	$I_{OH} = 40\mu\text{A}$, 1TTL unit load

Stratos

SLC-25-C-1-x-R6 Optical Transceiver

Connectivity for
Business-Critical Continuity™

Module Specifications – Optical: $-5^{\circ}\text{C} < T_c < +80^{\circ}\text{C}; +3.0\text{V} < V_{cc} < +3.6\text{V}$

Parameter	Sym	MIN	Typ	MAX	Unit	Notes
Transmission Distance						
50 μm Core Diameter MMF		250	500		m	BER<1.0E-12 @ 1.25/2.5 GBaud
62.5 μm Core Diameter MMF		150	300		m	BER<1.0E-12 @ 1.25/2.5 GBaud
Transmitter						
Optical Center Wavelength	λ	830	850	860	nm	
Spectral Width	$\Delta\lambda$			0.85	nm	RMS
Optical Transmit Power	Popt	-10.0		-3	dBm	Average @ 850nm
Optical Modulation Amplitude	OMA	200			μW	pk-pk
Relative Intensity Noise	RIN			-117	dB/Hz	
Total Jitter	Tj			84	pS	Measured with 2 ⁷ -1 PRBS
Output Rise/Fall Time	t _R , t _F			150	pS	20-80%; measured unfiltered
Receiver						
Optical Input Wavelength	λ	770		860	nm	
Optical Input Power	Pr	-15		-1.5	dBm	BER<1.0E-12
Optical Modulation Amplitude	OMA	50			μW	pk-pk
Optical Return Loss	ORL	12			dBm	
Signal Detect – Asserted	Pa			-15	dBm	Measured on transition – Low to High
Signal Detect – Deasserted	Pd	-29			dBm	Measured on transition – High to Low
Signal Detect – Hysteresis	Pa-Pd		1.5	5.0	dB	

For more information on this product consult the SLC-25-C-1-x-R6 product data sheet.

IMPORTANT NOTICE

Stratos International, Inc. reserves the right to make changes to or discontinue any optical link product or service identified in this publication, without notice. Stratos International, Inc. recommends that its customers obtain the latest version of the publications to verify, before placing orders, that the information being relied on is current. Stratos International, Inc. warrants performance of its optical link products to current specifications in accordance with the Stratos International, Inc. standard warranty. Testing and other quality control techniques are utilized to the extent that Stratos International, Inc. has determined it to be necessary to support this warranty. Specific testing of all parameters of each optical link product is not necessarily performed on all optical link products. Stratos International, Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of a Stratos International, Inc. product can reasonably be expected to result in a personal injury. Stratos International, Inc. customers using or selling optical link products for use in such applications do so at their own risk and agree to fully indemnify Stratos International, Inc. for any damages resulting from such improper use or sale. Stratos International, Inc. assumes no liability for Stratos International, Inc. applications assistance, customer product design, software performance, or infringement of patents or services described here in. Nor does Stratos International, Inc. warrant or represent that a license, either expressed or implied is granted under any patent right, copyright, or intellectual property right, and makes no representations or warranties that these products are free from patent, copyright, or intellectual property rights. Applications that are described herein for any of the optical link products are for illustrative purposes only. Stratos International, Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.