

- ◆ CMOS 2-Input OR Gate
- ◆ High Speed Operation  $t_{pd}=8\text{ns}$  TYP
- ◆ Operating Voltage Range 2V~5.5V
- ◆ Low Power Consumption  $1\mu\text{A}$  MAX

### Applications

- Palmtops
- Digital Equipment

### General Description

The XC74UL32AA is a 2-input CMOS OR gate, manufactured using silicon gate CMOS fabrication.

CMOS low power circuit operation makes high speed LS-TTL operations achievable.

With a wave forming buffer connected internally, stabilized output can be achieved as the circuit offers high noise immunity.

As the XC74UL32AA is integrated into mini molded, SSOT-25 and SOT-25 packages, high density mounting is possible.

### Features


**High Speed Operation:**  $t_{pd}=8\text{ns}$  TYP

**Operating Voltage Range:** 2V~5.5V

**Low Power Consumption:**  $1\mu\text{A}$  MAX

**Space Saving Package:** SSOT-25 and SOT-25

### Pin Configuration



### Function

| INPUT |   | OUTPUT |
|-------|---|--------|
| A     | B | Y      |
| L     | L | L      |
| L     | H | H      |
| H     | L | H      |
| H     | H | H      |

H=High level, L=Low level

### Absolute Maximum Ratings

$T_a = -40^\circ\text{C} \sim 85^\circ\text{C}$

| PARAMETER                          | SYMBOL               | RATINGS               | UNITS            |
|------------------------------------|----------------------|-----------------------|------------------|
| Power Supply Voltage               | $V_{CC}$             | -0.5 ~ +6.0           | V                |
| Input Voltage                      | $V_{IN}$             | -0.5 ~ +6.0           | V                |
| Output Voltage                     | $V_{OUT}$            | -0.5 ~ $V_{CC} + 0.5$ | V                |
| Input Diode Current                | $I_{IK}$             | -20                   | mA               |
| Output Diode Current               | $I_{OK}$             | $\pm 20$              | mA               |
| Output Current                     | $I_{OUT}$            | $\pm 25$              | mA               |
| $V_{CC}$ , GND Current             | $I_{CC}$ , $I_{GND}$ | $\pm 50$              | mA               |
| Continuous Total Power Dissipation | $P_d$                | 150                   | mW               |
| Storage Temperature                | $T_{stg}$            | -65 ~ +150            | $^\circ\text{C}$ |

Note: Voltage is all Ground standardized.

### Ordering Information

XC74UL xxxxxx  
 ↑↑  
 a b

| DESIGNATOR | DESCRIPTION                                                                                                               |
|------------|---------------------------------------------------------------------------------------------------------------------------|
| a          | Package Type<br>N=SSOT-25<br>M=SOT-25                                                                                     |
| b          | Device Orientation<br>R=Embossed Tape<br>(Orientation of Device:Right)<br>L=Embossed Tape<br>(Orientation of Device:Left) |

## DC Electrical Characteristics

| PARAMETER                | SYMBOL          | V <sub>CC</sub> (V) | CONDITIONS                                                     |                        | Ta=25℃ |     |      | Ta=-40~85℃ |      | UNITS |
|--------------------------|-----------------|---------------------|----------------------------------------------------------------|------------------------|--------|-----|------|------------|------|-------|
|                          |                 |                     |                                                                |                        | MIN    | TYP | MAX  | MIN        | MAX  |       |
| Input Voltage            | V <sub>IH</sub> | 2.0                 |                                                                |                        | 1.5    | -   | -    | 1.5        | -    | V     |
|                          |                 | 3.0                 |                                                                |                        | 2.1    | -   | -    | 2.1        | -    |       |
|                          |                 | 5.5                 |                                                                |                        | 3.85   | -   | -    | 3.85       | -    |       |
|                          | V <sub>IL</sub> | 2.0                 |                                                                |                        | -      | -   | 0.5  | -          | 0.5  | V     |
|                          |                 | 3.0                 |                                                                |                        | -      | -   | 0.9  | -          | 0.9  |       |
|                          |                 | 5.5                 |                                                                |                        | -      | -   | 1.65 | -          | 1.65 |       |
| Output Voltage           | V <sub>OH</sub> | 2.0                 | V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub>            | I <sub>OH</sub> =-50μA | 1.9    | 2.0 | -    | 1.9        | -    | V     |
|                          |                 | 3.0                 |                                                                |                        | 2.9    | 3.0 | -    | 2.9        | -    |       |
|                          |                 | 4.5                 |                                                                |                        | 4.4    | 4.5 | -    | 4.4        | -    |       |
|                          |                 | 3.0                 |                                                                | I <sub>OH</sub> =-4mA  | 2.58   | -   | -    | 2.48       | -    |       |
|                          |                 | 4.5                 |                                                                | I <sub>OH</sub> =-8mA  | 3.94   | -   | -    | 3.80       | -    |       |
|                          | V <sub>OL</sub> | 2.0                 | V <sub>IN</sub> =V <sub>IH</sub>                               | I <sub>OL</sub> =50μA  | -      | -   | 0.1  | -          | 0.1  | V     |
|                          |                 | 3.0                 |                                                                |                        | -      | -   | 0.1  | -          | 0.1  |       |
|                          |                 | 4.5                 |                                                                |                        | -      | -   | 0.1  | -          | 0.1  |       |
|                          |                 | 3.0                 |                                                                | I <sub>OL</sub> =4mA   | -      | -   | 0.36 | -          | 0.44 |       |
|                          |                 | 4.5                 |                                                                | I <sub>OL</sub> =8mA   | -      | -   | 0.36 | -          | 0.44 |       |
| Input Current            | I <sub>IN</sub> | 5.5                 | V <sub>IN</sub> =V <sub>CC</sub> or GND                        |                        | -0.1   | -   | 0.1  | -1.0       | 1.0  | μA    |
| Quiescent Supply Current | I <sub>CC</sub> | 5.5                 | V <sub>IN</sub> =V <sub>CC</sub> or GND. I <sub>OUT</sub> =0μA |                        | -      | -   | 1.0  | -          | 10.0 |       |


## Switching Electrical Characteristics

| PARAMETER                     | SYMBOL           | C <sub>L</sub> | V <sub>CC</sub> (V) | CONDITIONS                              | Ta=25°C |     |      | Ta=-40~85°C |     | UNITS |
|-------------------------------|------------------|----------------|---------------------|-----------------------------------------|---------|-----|------|-------------|-----|-------|
|                               |                  |                |                     |                                         | MIN     | TYP | MAX  | MIN         | MAX |       |
| Propagation Delay Time        | t <sub>PLH</sub> | 15pF           | 3.3                 |                                         | -       | 5.5 | 7.9  | 1           | 9.5 | ns    |
|                               |                  |                | 5.0                 |                                         | -       | 3.8 | 5.5  | 1           | 6.5 |       |
|                               |                  | 50pF           | 3.3                 |                                         | -       | 8   | 11.4 | 1           | 13  | ns    |
|                               |                  |                | 5.0                 |                                         | -       | 5.3 | 7.5  | 1           | 8.5 |       |
|                               | t <sub>PHL</sub> | 15pF           | 3.3                 |                                         | -       | 5.5 | 7.9  | 1           | 9.5 | ns    |
|                               |                  |                | 5.0                 |                                         | -       | 3.8 | 5.5  | 1           | 6.5 |       |
|                               |                  | 50pF           | 3.3                 |                                         | -       | 8   | 11.4 | 1           | 13  | ns    |
|                               |                  |                | 5.0                 |                                         | -       | 5.3 | 7.5  | 1           | 8.5 |       |
| Input Capacitance             | C <sub>IN</sub>  | -              | 5.0                 | V <sub>IN</sub> =V <sub>CC</sub> or GND | -       | 2   | 10   | -           | 10  | pF    |
| Power Dissipation Capacitance | C <sub>pd</sub>  |                |                     | No Load, f=1MHz                         | -       | 8.9 | -    | -           | -   | pF    |


## Recommended Operating Conditions

| PARAMETER                | SYMBOL                          | V <sub>CC</sub> (V) | CONDITIONS          | UNITS |
|--------------------------|---------------------------------|---------------------|---------------------|-------|
| Supply Voltage           | V <sub>CC</sub>                 | -                   | 2 ~ 5.5             | V     |
| Input Voltage            | V <sub>IN</sub>                 | -                   | 0 ~ 5.5             | V     |
| Output Voltage           | V <sub>OUT</sub>                | -                   | 0 ~ V <sub>CC</sub> | V     |
| Operating Temperature    | T <sub>opr</sub>                | -                   | -40 ~ +85           | °C    |
| Output Current           | I <sub>OH</sub>                 | 3.0                 | -4                  | mA    |
|                          |                                 | 4.5                 | -8                  |       |
|                          | I <sub>OL</sub>                 | 3.0                 | 4                   |       |
|                          |                                 | 4.5                 | 8                   |       |
| Input Rise and Fall Time | t <sub>r</sub> , t <sub>f</sub> | 3.3                 | 0 ~ 100             | ns/V  |
|                          |                                 | 5.0                 | 0 ~ 20              |       |

## Waveforms



## Typical Application Circuit



Note: open output when measuring supply current