







RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free

FEATURES

- Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors (see equivalent circuit).
- The bias resistors consist of thin-film resistors with complete isolation to allow positive biasing of the input. They also have the advantage of almost completely eliminating parasitic effects.
- Only the on/off conditions need to be set for operation, making device design easy.

EQUIVALENT CIRCUIT



<u>DTC114EE (SOT-523)</u>	<u>DTC114EUA (SOT-323)</u>
 1.IN 2.GND 3.OUT	 1.IN 2.GND 3.OUT
Abbreviated symbol : 24	Abbreviated symbol : 24
<u>DTC114EM (SOT-723)</u>	<u>DTC114ECA (SOT-23)</u>
 1.IN 2.GND 3.OUT	 1.IN 2.GND 3.OUT
Abbreviated symbol : 24	Abbreviated symbol : 24
<u>DTC114ESA (TO-92S)</u>	
 1.GND 2.OUT 3.IN (1) (2) (3)	





ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Limits (DTC114E□)					Unit
		M	E	UA	CA	SA	
Collector-Base Voltage	V_{CC}			50			V
Input voltage	V_{IN}			-10~40			V
Output current	I_O			50			mA
	$I_{C(MAX)}$			100			
Power dissipation	P_D	100	150	200	300		mW
Junction & Storage temperature	T_J, T_{STG}	150, -55~150					°C

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Input voltage	$V_{I(\text{off})}$	0.5	-	-	V	$V_{CC}=5\text{V}$, $I_O=100\mu\text{A}$
	$V_{I(\text{on})}$	-	-	3		$V_O=0.3\text{V}$, $I_O=10\text{mA}$
Output voltage	$V_{O(\text{on})}$	-	-	0.3	V	$I_O/I_I=10\text{mA}/0.5\text{mA}$
Input current	I_I	-	-	0.88	mA	$V_I=5\text{V}$
Output current	$I_O(\text{off})$	-	-	0.5	μA	$V_{CC}=50\text{V}$, $V_I=0$
DC current gain	G_I	30	-	-		$V_O=5\text{V}$, $I_O=5\text{mA}$
Input resistance	R_I	7	10	13	$\text{K}\Omega$	
Resistance ratio	R_2/R_1	0.8	1	1.2		
Transition frequency	f_T	-	250	-	MHz	$V_O=10\text{V}$, $I_O=5\text{mA}$, $f=100\text{MHz}$

CHARACTERISTIC CURVES



CHARACTERISTIC CURVES

