

### — REVERSE SERVICE — MALE RECEPTACLES AND FEMALE PLUGS 30, 60 and 100 Amp-250 Volts D.C., 600 Volts A.C.

Receptacles with male interiors and plugs with female interiors are for portable equipment where it is desirable to disconnect the portable cord at the machine. The machine is fitted with a male receptacle, which engages a female plug. The contacts of the female plug when disengaged, are fully enclosed in molded Phenolic which prevents the possibility of accidental touching of live parts.

An important advantage of installing male service receiving receptacles on portable equipment is in the use of two or more cable lengths when extra long extensions are required. The extension cord is made up of a female plug on one end, and a male plug on the other end. The female plugs listed on this page serve as extension connector receptacles, when two cables are connected together.

Receptacles fit JR Series conduit boxes (see page 6). Receptacles can also be surface mounted on sheet metal cabinets and panels. Housings have square flanges, and are mountable in any of four positions.

The products listed below have male contact interiors in the receptacles, and female contact interiors in the plugs. This arrangement is simply the reverse of the plugs and receptacles listed on the previous pages.



Hinged Spring  
Door & Gasket

CIRCUIT TYPE	AMPS	MALE RECEPT'S	CABLE DIAM. RANGE	STD. FEMALE PLUGS	MALE RECEPT'S	CABLE DIAM. RANGE	THREADED FEMALE PLUGS
2-Pole 3-Wire	30	JZC-3036	.250-.625	JWPD-53036	—	—	—
3-Pole 4-Wire			.625-1.00	JWPD-53036			
3-Pole 4-Wire	60	JZC-3046	.375-.625	JWPD-53046	—	—	—
4-Wire			.625-1.00	JWPD-53046			
2-Pole 3-Wire	60	JZC-6036	.625-1.000	JWPD-83036	JZL-6036	.625-1.00	JWPLD-83036
3-Wire			1.000-1.250	JWPD-106036			JWPLD-106036
3-Pole 4-Wire	100	JZC-6046	.625-1.000	JWPD-83046	JZL-6046	.625-1.00	JWPLD-83046
4-Wire			1.000-1.375	JWPD-114046			JWPLD-116046
2-Pole 3-Wire	100	JZC-10036	1.000-1.375	JWPD-1110036	—	—	—
3-Wire			1.375-1.625	JWPD-1310036			
3-Pole 4-Wire			1.000-1.375	JWPD-1110046			
4-Wire	1.375-1.750	JWPD-1410046					
3-Pole 4-Wire	100	JRZ-10046	1.000-1.375	JWPD-1110446	—	—	—
4-Wire			1.375-1.750	JWPD-1410446			

### IN-LINE CONNECTOR PLUG & RECEPTACLE SETS



- ① Other cable ranges available. Consult factory.
- ② Optional strain relief available. Add appropriate suffix from note at left.
- ③ Non-circuit breaking low profile sets.

CIRCUIT TYPE	AMPS	CABLE DIAM. RANGE ①	COMPLETE SET W/CLAMP NUT ②
2-Pole 3-Wire	30	.250-.625	JRKD-53036
3-Wire		.625-1.000	JRKD-53036
3-Pole 4-Wire	60	.375-.625	JRKD-53046
4-Wire		.625-1.000	JRKD-53046
2-Pole 3-Wire	60	.625-1.000	JRKD-86036
3-Wire		1.000-1.250	JRKD-106036
3-Pole 4-Wire	100	.625-1.000	JRKD-83046
4-Wire		1.000-1.375	JRKD-116046
2-Pole 3-Wire	100	1.000-1.375	JRKD-1110036
3-Wire		1.375-1.625	JRKD-1310036
3-Pole 4-Wire	100	1.000-1.375	JRKD-1110046
4-Wire		1.375-1.750	JRKD-1410046
3-Pole 4-Wire ③	100	1.000-1.375	JRKD-1110446
4-Wire		1.375-1.750	JRKD-1410446