



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. BRASS PER QQ-B-613
  3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  4. PHOSPHOR BRONZE PER QQ-B-750
  5. GOLD PL 3 MIN. THICK OVER NICKEL PL. 100 MIN THICK OVER COPPER STRIKE

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
8	HEX NUT			1	HN22-3/4-20X4
7	LOCK WASHER			1	LW-27/195X06
6	PIN			1	TW7630-9
5	PIN			2	TW7630-8
4	RING			1	TW7690-4
3	CONTACT PIN			2	TW7690-3
2	INSULATOR	PBT	WHITE	2	TWX6351B1-2
1	BODY			1	TW7691-1

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

PART NO.	TWX7471B1-NPB3G-95	
APPROVED	DATE	10-11-01'
CHECKED	DATE	10-11-01'
DRAWN	DATE	10-11-01'
FILE NO.		

**Amphenol**

TITLE TWINAXIAL FEMALE-FEMALE  
BULKHEAD ADAPTOR

DRAWING NO.  
KJ-TWX7471B1-NPB3G-95

ITEM NO.

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	2/1	ISSUE	A	FILE NO.
-----	-------------	----------	--------	------	-------------	-------	-----	-------	---	----------