


OMI-SH-124D,394 Product Details



OMI-SH-124D,394



Active

Mid-Range PC Board Relays



Always EU RoHS compliant but not ELV Compliant (Statement of Compliance)

Product Highlights:

- OMI Series
- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Contact Current Rating = 10 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

[View all Features](#) | [Find Similar Products](#)



[Previous](#) [1](#) [2](#) [\[3\]](#) [4](#) [5](#) ... [20](#) [Next](#)



Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [OMI-SH-112D SPEC,394 CUSTOMER DRAWING](#) (PDF, Japanese)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [Wiring Diagram](#)
- [PCB Layout \(Bottom Surface\)](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Termination Type](#) = Through Hole

Electrical Characteristics:

- [Contact Current Rating \(Amps.\)](#) = 10
- [Coil Resistance \(?\)](#) = 820
- [Coil Power, Nominal \(mW\)](#) = 720
- [Actuating System](#) = DC
- [Input Voltage \(VDC\)](#) = 24

Body Related Features:

- [Series](#) = OMI
- Polarized = No

Contact Related Features:

- [Mounting Options](#) = PC Board
- [Enclosure](#) = Sealed
- FCC Part 68 Isolation = No
- Relay Type = PCB
- [Contact Material](#) = Silver Alloy
- Approx. Dimensions (L x W x H) (mm[in]) = 29.20 x 12.80 x 20.60 [1.151 x .504 x .812]
- Approved Standards = UL Recognized, CSA Certified, SEMKO, VDE Component Mark

Configuration Related Features:

- [Contact Arrangement](#) = 1 Form C, SPDT, 1 C/O
- [Coil Magnetic System](#) = Monostable
- [Coil Suppression Diode](#) = Without
- [Coil Selection Criteria](#) = Nominal Voltage
- Coil Latching = Without
- [LED Indicator](#) = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Always was RoHS not ELV compliant

Other:

- Brand = OEG