

OMR-209H,SV000 Product Details



OMR-209H,SV000

(1-1440000-9)

TE Internal Number: 1-1440000-9

Obsolete

[Contact Product Information Center](#)

[View 3D PDF](#)

Communications/Signal PC Board Relays

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- OMR Series
- DC Actuating System
- Input Voltage = 9 VDC
- Contact Arrangement = 2 Form A, DPST-NO, 2 N/O
- Contact Current Rating = .5 Amps.

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files: (CAD Format & Compression Information)</p> <ul style="list-style-type: none"> • 2D Drawing (DXF, Version E) • 3D Model (IGES, Version E) • 3D Model (STEP, Version E) 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Additional Product Images:</p> <ul style="list-style-type: none"> • Schematic • Wiring Diagram • PCB Layout (Bottom Surface) <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Termination Type = Through Hole <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Actuating System = DC • Input Voltage (VDC) = 9 • Contact Current Rating (Amps.) = 0.5 • Coil Resistance (?) = 700 • Coil Power, Nominal (mW) = 100 - 280 <p>Body Related Features:</p> <ul style="list-style-type: none"> • Series = OMR <p>Contact Related Features:</p> <ul style="list-style-type: none"> • Mounting Options = PC Board • Enclosure = Open • FCC Part 68 Isolation = No • Approved Standards = UL Recognized 	<p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Contact Arrangement = 2 Form A, DPST-NO, 2 N/O • Coil Magnetic System = Monostable • Coil Suppression Diode = Without <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C • RoHS/ELV Compliance History = Converted to comply with RoHS directive <p>Other:</p> <ul style="list-style-type: none"> • Brand = OEG

Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)