


T92P11D22-110 Product Details



T92P11D22-110



Active

Power Plug-in Relays



[Converted to EU RoHS but not ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- T92 Series
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 30 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

[View all Features](#) | [Find Similar Products](#)



[Previous](#) [1](#) ... [6](#) [7](#) **[8]** [9](#) [10](#) ... [20](#) [Next](#)



Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [T92 Two-Pole, 30 Amp, PC Board or Panel Mount Relay](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [PCB Layout](#)
- [Wiring Diagram](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Termination Type](#) = .250 x .032 Quick Connect Terminals

Electrical Characteristics:

- [Contact Current Rating \(Amps.\)](#) = 30
- [Coil Resistance \(?\)](#) = 7255
- [Actuating System](#) = DC
- [Coil Power, Nominal \(W\)](#) = 1.70
- [Input Voltage \(VDC\)](#) = 110

Body Related Features:

- [Series](#) = T92
- Polarized = No

Contact Related Features:

- [Mounting Options](#) = Flange Mount
- [Enclosure](#) = Dust Cover
- FCC Part 68 Isolation = No
- Relay Type = PCB
- [Contact Material](#) = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm[in]) = 52.30 x 34.50 x 30.70 [2.060 x 1.359 x 1.209]
- Wiring Diagram = 2 Form C
- Approved Standards = UL Recognized, CSA Component Acceptance, UL Listed, VDE Component Mark, CSA Certified

Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- [Coil Magnetic System](#) = Monostable
- [Coil Suppression Diode](#) = Without
- [Coil Selection Criteria](#) = Nominal Voltage
- Coil Latching = Without
- [LED Indicator](#) = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240C, Wave solder capable to 260C
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives
- Coil Insulation Classification = UL Class F

Other:

- Brand = Potter & Brumfield

