

METRIC NYLON INSERT NUTS DIN 982/985

Thread	Thread Pitch	Across Flats	Thickness "P" 982	Weight kg/1000 982	Thickness "T" 985	Weight kg/1000 985	Material
M3	0.50	5.50	NA	NA	4.00	0.50	DIN 982 C/F Grade 8
M4	0.70	7.00	NA	NA	5.00	1.00	
M5	0.80	8.00	6.30	1.40	5.00	1.40	
* M6	1.00	10.00	8.00	2.50	6.00	2.40	
* M8	1.25	13.00	9.50	5.60	8.00	5.10	
* M10	1.50	17.00	11.50	12.50	10.00	10.60	
* M12	1.75	19.00	14.00	18.00	12.00	17.20	
M14	2.00	22.00	16.00	26.50	14.00	26.00	
* M16	2.00	24.00	18.00	35.00	16.00	34.00	
M18	2.50	27.00	NA	NA	18.50	45.00	
* M20	2.50	30.00	22.00	65.00	20.00	65.00	
M22	2.50	32.00	NA	NA	22.00	75.00	
* M24	3.00	36.00	NA	NA	24.00	100.00	
M27	3.00	41.00	NA	NA	27.00	162.00	
M30	3.50	46.00	NA	NA	30.00	212.00	
M33	3.50	50.00	NA	NA	33.00	317.00	
M36	4.00	55.00	NA	NA	36.00	415.00	
M42	4.50	65.00	NA	NA	42.00	628.00	
M48	5.00	75.00	NA	NA	48.00	998.00	

\* - Also in DIN 985 Grade 10  
All dimensions in millimetres

*Nettlefold*