

2 Amp. Glass Passivated Avalanche Ultrafast Recovery Rectifier

<p>Dimensions in mm.</p> <p>DO-15 (Plastic)</p>	<p>Voltage 200 V.</p> <p>Current 2 A at 55 °C.</p> <p></p>
<p>Mounting instructions</p> <ol style="list-style-type: none"> Min. distance from body to soldering point, 4 mm. Max. solder temperature, 350 °C. Max. soldering time, 3.5 sec. Do not bend lead at a point closer than 2 mm. to the body. 	<ul style="list-style-type: none"> • Glass Passivated Junction • High current capability • The plastic material carries U/L recognition 94 V-0 • Terminals: Axial Leads • Polarity: Color band denotes cathode

Maximum Ratings, according to IEC publication No. 134

EGP20DT		
V_{RRM}	Peak Recurrent reverse voltage (V)	200
V_{RMS}	Maximum RMS voltage	140
V_{DC}	Maximum DC blocking voltage	200
$I_{F(AV)}$	Forward current at $T_{amb} = 55^\circ C$	2 A
I_{FRM}	Recurrent peak forward current	20 A
I_{FSM}	8.3 ms. peak forward surge current (Jedec Method)	75 A
t_{rr}	Max. reverse recovery time from $I_F = 0.5 A$; $I_R = 1 A$; $I_{RR} = 0.25 A$	25 ns
C_j	Typical Junction Capacitance at 1 MHz and reverse voltage of $4V_{DC}$	45 pF
T_j	Operating temperature range	- 65 to + 150 °C
T_{stg}	Storage temperature range	- 65 to + 150 °C
E_{RSM}	Maximum non repetitive peak reverse avalanche energy. $I_R = 1 A$; $T_j = 25^\circ C$	20 mJ

Electrical Characteristics at $T_{amb} = 25^\circ C$

V_F	Max. forward voltage drop at $I_F = 2 A$	0.95 V
I_R	Max. reverse current at V_{RRM} at 25 °C at 150 °C	5 μA 50 μA
R_{thj-a}	Max. thermal resistance ($l = 10 \text{ mm.}$)	30 °C/W

Rating And Characteristic Curves

