

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

Features

- Schottky Barrier Rectifier
- High Current Capability
- Low Forward Voltage
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Temperature: -55°C to +125°C
- Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance; 28°C/W Junction To Lead


MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage		Voltage
SMD15PL	D5	50V	35V	50V
SMD16PL	D6	60V	42V	60V
SMD18PL	D8	80V	56V	80V
SMD110PL	D10	100V	70V	100V
SMD1150PL	D15	150V	105V	150V
SMD1200PL	D20	200V	140V	200V

Electrical Characteristics @ 25°C Unless Otherwise Specified


			-
Average Forward Current	I _{F(AV)}	1.0A	T _L = 90°C
	1	30A	9 2mg half sing
Peak Forward Surge	FSM	30A	8.3ms, half sine
Current			
Maximum			
Instantaneous			
Forward Voltage			
SMD15PL-16PL	VF	.70V	I _{FM} = 1.0A;
SMD18PL-1150PL		.85V	$T_J = 25^{\circ}C(Note:2)$
SMD1200PL		.95V	
Maximum DC			
Reverse Current At	I _R	0.5mA	T _A = 25°C
Rated DC Blocking	•K	20mA	$T_{A} = 100^{\circ}C$
0		20117	$I_{A} = 100^{\circ}C$
Voltage			
Typical Junction			
Capacitance			
SMD12PL -16PL	CJ	110pF	Measured at
SMD18PL-1150PL		30pF	1.0MHz, V _R =4.0V

SMD15PL THRU SMD1200PL

1 Amp Schottky Rectifier 50 to 200 Volts



DIMENSIONS							
DIM	INCHES		MM		NOTE		
	MIN	MAX	MIN	MAX			
Α	.140	.152	3.55	3.85			
В	.100	.112	2.55	2.85			
С	.055	.071	1.40	1.80			
D	.037	.053	0.95	1.35			
Е	.020	.039	0.50	1.00			
G	.010		0.25				
Н		.008		.20			



Note:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7. 2.Pulse test: Pulse width 300 sec, Duty cycle 2%


www.mccsemi.com


1 of 3


SMD15PL thru SMD1200PL




Micro Commercial Components











www.mccsemi.com



Ordering Information :

Device	Packing	
Part Number-TP	Tape&Reel: 2.5Kpcs/Reel	

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

