


ZMM5221 THRU ZMM5262

0.5W SILICON PLANAR
ZENER DIODES

Features

- Standards Zener voltage tolerance is $\pm 20\%$. Add suffix "A" for $\pm 10\%$ tolerance and suffix "B" for $\pm 5\%$ tolerance other tolerance, non standards and higher zener voltage upon request.
- These diode are also available in DO-35 case with type designation 1N5221 thru 1N5262

MELF (DO-35)



Dimensions in inches and (millimeters)

Mechanical Data

- Case : MELF(DO-35) glass case
- Weight : Approx. 0.05 gram

Absolute Maximum Ratings (Limiting Values) (TA=25 °C)

	Symbols	Value	Units
Zener current see table "Characteristics"			
Power dissipation at TA=75 °C	P _{tot}	500 ¹⁾	mW
Junction Temperature	T _J	175	°C
Storage Temperature range	T _{STG}	-65 to +175	°C

1) Valid provided that electrodes are kept at ambient temperature

Electrical Characteristics (TA=25 °C)

	Symbols	Min.	Typ.	Max.	Units
Thermal resistance junction to ambient	R _{θJA}			300 ¹⁾	°C/W
Forward voltage at I _F =200mA	V _F			1.1	V

1) Valid provided that electrodes are kept at ambient temperature



ZMM5221...ZMM5262 SILICON PLANAR ZENER DIODES

Type	Nominal Zener Voltage	Test Current	Maximum zener impedance ¹⁾		Typical Temperature Coefficient	Maximum Reverse Leakage Current			Maximum Regulator Current ²⁾
	at I_{ZT} V_{zV}	I_{ZT} mA	at I_{ZT} $Z_{ZT} \Omega$	at $I_{zk}=0.25$ mA $Z_{zk} I_{ZT}$ mA	α_{VZ} %/K	$I_{R \mu A}$	Test-Voltage Suffix A V_{RV}	Suffix B V_{RV}	I_{ZM} mA
ZMM5221	2.4	20	30	1200	-0.085	100	0.95	1.0	191
ZMM5222	2.5	20	30	1250	-0.085	100	0.95	1.0	182
ZMM5223	2.7	20	30	1300	-0.080	75	0.95	1.0	168
ZMM5224	2.8	20	30	1400	-0.080	75	0.95	1.0	162
ZMM5225	3.0	20	29	1600	-0.075	50	0.95	1.0	152
ZMM5226	3.3	20	28	1600	-0.070	25	0.95	1.0	138
ZMM5227	3.6	20	24	1700	-0.065	15	0.95	1.0	126
ZMM5228	3.9	20	23	1900	-0.060	10	0.95	1.0	115
ZMM5229	4.3	20	22	2000	-0.055	5	0.95	1.0	106
ZMM5230	4.7	20	19	1900	± 0.030	5	1.9	2.0	97
ZMM5231	5.1	20	17	1600	± 0.030	5	1.9	2.0	89
ZMM5232	5.6	20	11	1600	+0.038	5	2.9	3.0	81
ZMM5233	6.0	20	7	1600	+0.038	5	3.3	3.5	76
ZMM5234	6.2	20	7	1000	+0.045	5	3.8	4.0	73
ZMM5235	6.8	20	5	750	+0.050	3	4.8	5.0	67
ZMM5236	7.5	20	6	500	+0.058	3	5.7	6.0	61
ZMM5237	8.2	20	8	500	+0.062	3	6.2	6.5	55
ZMM5238	8.7	20	8	600	+0.065	3	6.2	6.5	52
ZMM5239	9.1	20	10	600	+0.068	3	6.7	7.0	50
ZMM5240	10	20	17	600	+0.075	3	7.6	8.0	45
ZMM5241	11	20	22	600	+0.076	2	8.0	8.4	41
ZMM5242	12	20	30	600	+0.077	1	8.7	9.1	38
ZMM5243	13	9.5	13	600	+0.079	0.5	9.4	9.9	35
ZMM5244	14	9.0	15	600	+0.082	0.1	9.5	10	32
ZMM5245	15	8.5	16	600	+0.082	0.1	10.5	11	30
ZMM5246	16	7.8	17	600	+0.083	0.1	11.4	12	28
ZMM5247	17	7.4	19	600	+0.084	0.1	12.4	13	27
ZMM5248	18	7.0	21	600	+0.085	0.1	13.3	14	25
ZMM5249	19	6.6	23	600	+0.086	0.1	13.3	14	24
ZMM5250	20	6.2	25	600	+0.086	0.1	14.3	15	23
ZMM5251	22	5.6	29	600	+0.087	0.1	16.2	17	21
ZMM5252	24	5.2	33	600	+0.087	0.1	17.1	18	19.1
ZMM5253	25	5.0	35	600	+0.089	0.1	18.1	19	18.2
ZMM5254	27	4.6	41	600	+0.090	0.1	20	21	16.8
ZMM5255	28	4.5	44	600	+0.091	0.1	20	21	16.2
ZMM5256	30	4.2	49	600	+0.091	0.1	22	23	15.1
ZMM5257	33	3.8	58	700	+0.092	0.1	24	25	13.8
ZMM5258	36	3.4	70	700	+0.093	0.1	26	27	12.6
ZMM5259	39	3.2	80	800	+0.094	0.1	29	30	11.6
ZMM5260	43	3.0	93	900	+0.095	0.1	31	33	10.6
ZMM5261	47	2.7	105	1000	+0.095	0.1	34	36	9.7
ZMM5262	51	2.5	125	1100	+0.096	0.1	37	39	8.9

1) The zener impedance is derived from the 1kHz AC voltage which results when an AC current having an RMS value equal to 10% of the Zener current (I_{ZT} or I_{zk}) is superimposed on I_{ZT} or I_{zk} . Zener impedance is measured at two points to insure a sharp knee on the breakdown curve and to eliminate unstable units.

2) Valid provided that leads are kept at ambient temperature at a distance of 8mm from case.

3) Measured with device junction in thermal equilibrium.

ZMM5221 THRU ZMM5262 SILICON PLANAR ZENER DIODES

Admissible power dissipation versus ambient temperature
(Valid provided that electrodes are kept at ambient temperature)

