



















# LED-Holder SRL / PBL / FMS (for 3mm T1 LED)

Models	Dimensions	Drilling diagram	Color	select your color	Part Number
SRL 			red	<input type="checkbox"/>	0035.1340
			green	<input type="checkbox"/>	0035.1341
			yellow	<input type="checkbox"/>	0035.1342
SRL 			red	<input type="checkbox"/>	0035.1350
			green	<input type="checkbox"/>	0035.1351
			yellow	<input type="checkbox"/>	0035.1352
SRL 			red	<input type="checkbox"/>	0035.1360
			green	<input type="checkbox"/>	0035.1361
			yellow	<input type="checkbox"/>	0035.1362
PBL 			red	<input type="checkbox"/>	0035.7032
			green	<input type="checkbox"/>	0035.7033
			yellow	<input type="checkbox"/>	0035.7034
PBL 			red	<input type="checkbox"/>	0035.7022
			green	<input type="checkbox"/>	0035.7023
			yellow	<input type="checkbox"/>	0035.7024
FMS 			black	<input type="checkbox"/>	0031.7501

## Technical data

### 1. Electrical data

Technical data LED 0925.0029/30/67 see page 91

### 2. Other data

Solderability

max. 2s < 235 °C (IEC 68 2-20 Test Ta Method 1 )

Soldering heat resistance

max. 5s < 260 °C (IEC 68 2-20 Test Tb Method 1A )

Ambient temperature

-25°C - + 85°C

Storage temperature

-55°C - +100°C

### 3. Materials

Socket

Thermoplast