



# T1620-600W / 700W T1630-600W

## SNUBBERLESS TRIAC


### FEATURES

- $I_{T(RMS)} = 16\text{ A}$
- $V_{DRM} = V_{RRM} = 600\text{V to } 700\text{V}$
- EXCELLENT SWITCHING PERFORMANCES
- INSULATING VOLTAGE =  $1500V_{(RMS)}$
- U.L. RECOGNIZED : E81734

### DESCRIPTION

The T1620-600W/700W and 1630-600W triacs use high performance glass passivated chip technology, housed in a fully molded plastic ISOWATT220AB package.

The SNUBBERLESS™ concept offers suppression of R-C network, and is suitable for applications such as phase control and static switch on inductive and resistive loads.



### ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
$I_{T(RMS)}$	RMS on-state current (360° conduction angle)	$T_c = 75^\circ\text{C}$	16	A
$I_{TSM}$	Non repetitive surge peak on-state current ( $T_j$ initial = $25^\circ\text{C}$ )	$t_p = 16.7\text{ ms}$ (1 cycle, 60 Hz)	165	A
		$t_p = 10\text{ ms}$ (1/2 cycle, 50 Hz)	195	
$I^2t$	$I^2t$ Value (half-cycle, 50 Hz)	$t_p = 10\text{ ms}$	190	$\text{A}^2\text{s}$
dI/dt	Critical rate of rise of on-state current Gate supply : $I_G = 500\text{ mA}$ $dI_G/dt = 1\text{ A}/\mu\text{s}$ .	Repetitive $F = 50\text{ Hz}$	20	$\text{A}/\mu\text{s}$
		Non Repetitive	100	
$T_{stg}$ $T_j$	Storage temperature range Operating junction temperature range		- 40 to + 150 - 40 to + 125	$^\circ\text{C}$
TI	Maximum lead temperature for soldering during 10s at 4.5 mm from case		260	$^\circ\text{C}$

Symbol	Parameter	Value		Unit
		600	700	
$V_{DRM}$ $V_{RRM}$	Repetitive peak off-state voltage $T_j = 125^\circ\text{C}$	600	700	V

## T1620-600W / 1620-700W and T1630-600W

### THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
Rth(j-a)	Junction to ambient	50	°C/W
Rth(j-c)	Junction to case for A.C (360° conduction angle)	2.5	°C/W

### GATE CHARACTERISTICS (maximum values)

$P_{G(AV)} = 1 \text{ W}$   $P_{GM} = 10 \text{ W}$  ( $t_p = 20 \mu\text{s}$ )  $I_{GM} = 4 \text{ A}$  ( $t_p = 20 \mu\text{s}$ )


### ELECTRICAL CHARACTERISTICS

Symbol	Test Conditions	Quadrant		T1620	T1630	Unit	
$I_{GT}$	$V_D = 12\text{V (DC)}$ $R_L = 33\Omega$	$T_j = 25^\circ\text{C}$	I-II-III	MAX	20	30	mA
$V_{GT}$	$V_D = 12\text{V (DC)}$ $R_L = 33\Omega$	$T_j = 25^\circ\text{C}$	I-II-III	MAX	1.5		V
$V_{GD}$	$V_D = V_{DRM}$ $R_L = 3.3\text{k}\Omega$	$T_j = 125^\circ\text{C}$	I-II-III	MIN	0.2		V
tgt	$V_D = V_{DRM}$ $I_G = 500\text{mA}$ $dI_G/dt = 3\text{A}/\mu\text{s}$	$T_j = 25^\circ\text{C}$	I-II-III	TYP	2		$\mu\text{s}$
$I_H^*$	$I_T = 250\text{mA}$ Gate open	$T_j = 25^\circ\text{C}$		MAX	35	50	
$V_{TM}^*$	$I_{TM} = 22.5\text{A}$ $t_p = 380\mu\text{s}$	$T_j = 25^\circ\text{C}$		MAX	1.5		V
$I_{DRM}$ $I_{RRM}$	VDRM rated VRRM rated	$T_j = 25^\circ\text{C}$		MAX	10		$\mu\text{A}$
		$T_j = 125^\circ\text{C}$		MAX	2		mA
dV/dt *	Linear slope up to $V_D = 67\%V_{DRM}$ Gate open	$T_j = 125^\circ\text{C}$		MIN	200	300	V/ $\mu\text{s}$
(dV/dt)c *	(dI/dt)c = 9 A/ms (see note)	$T_j = 125^\circ\text{C}$		MIN	10	20	V/ $\mu\text{s}$


\* For either polarity of electrode A2 voltage with reference to electrode A1.

**Note :** In usual applications where (dI/dt)c is below 9 A/ms, the (dV/dt)c is always lower than 10V/ $\mu\text{s}$ , and, therefore, it is **unnecessary** to use a snubber R-C network across T1620W / T1630W triacs.


**Fig. 1:** Maximum power dissipation versus RMS on-state current.




**Fig. 3:** RMS on-state current versus case temperature.




**Fig. 5:** Relative variation of gate trigger current and holding current versus junction temperature.




**Fig. 2:** Correlation between maximum power dissipation and maximum allowable temperature (Tamb and Tcase) for different thermal resistances heatsink + contact.



**Fig. 4:** Thermal transient impedance junction to case and junction to ambient versus pulse duration.




**Fig. 6:** Non repetitive surge peak on-state current versus number of cycles.




## T1620-600W / 1620-700W and T1630-600W


**Fig. 7:** Non repetitive surge peak on-state current for a sinusoidal pulse with width :  $t_p$  @ 10ms, and corresponding value of  $I^2t$ .



**Fig. 8:** On-state characteristics (maximum values).



**PACKAGE MECHANICAL DATA**  
ISOWATT220AB



- Cooling method : C
- Marking : Type number
- Weight : 2.1g
- Recommended torque value : 0.55 m.N.
- Maximum torque value : 0.70 m.N.

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2001 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia  
Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>

