

6 5 4 3 2 1

**MATERIAL AND FINISH:**  
 Insulator: Polycarbonate, UL-94V-0 rated  
 Contacts: IEC C13, 70°C: Brass  
 IEC C15, 120°C: Bronze

**ELECTRICAL SPECIFICATIONS:**  
 Current rating: 10 A  
 Voltage rating: 250 VAC

**ORDERING CODE:**  
 43R01- $\frac{2}{1} \frac{1}{2}$

**1) ELECTRICAL CIRCUIT CONFIGURATION**

1 = IEC C13, 10A 250V 70°C  
 A DIN 49 457

2 = IEC C15, 10A 250V 120°C  
 D DIN 49 458

**2) COLOR**  
 1 = BLACK  
 2 = GRAY

**NOTES:**  
 1. Contains integral cable clamp strain relief & internal screw type connections. Maximum wire gauge is 16AWG stranded.  
 2. Recommended screw torque: 1.2Nm  
 3. Recommended strip length for jacket and conductors:

**RoHS COMPLIANT**

REV	DATE	CHANGE	CHNG		PB	PB	PB	PB	PB
			CHK	APPR					
A	1/25/07	ADD NOTES 2 & 3; RoHS							
B	3/30/09	ADD L, E & N TO HOUSING							
C	1/20/10	ADD 20.6 DIM.							
D	6/9/10	ADD C15 CONTACT MATERIAL							
E	11/12/12	CHANGED CSA TO GRU							

TOLERANCE UNLESS OTHERWISE SPECIFIED	
X	± 1
X.X	± 0.4
X.XX	± 0.20

DRAWN BY	GQ	DATE:	08/20/01
CHECK BY	TD	DATE:	08/22/01
APPR BY	PB	DATE:	08/22/01

**Power Dynamics, Inc.**  
 Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

PART: IEC 60320 C13 & C15 FEMALE POWER CORD PLUG; R/A RIGHT HANDED CONNECTION

**43R01-X2X1**

SIZE: A  
 SCALE: NTS

ALL DIMENSIONS FOR REFERENCE ONLY  
 DIMENSIONS ARE IN MILLIMETERS

SHEET 1 of 1  
 REV: E

6 5 4 3 2 1