



Economy Slide 204	Multifunctional Slide 206	Economy Slide 208	Auto-Insertable 209/210
2 - 10 & 12	2 - 10 & 12	2 - 10 & 12	2 - 10 & 12
50 Milliohms Max.	50 Milliohms Max.	100 Milliohms Max.	25 Milliohms Max.
100 Milliohms after 2,000 Cycles	100 Milliohms after 10,000 Cycles	500 Milliohms after 2,000 Cycles	25/100 Milliohms after 500/1000 Cycles
Maximum Rise of 30°C @ 5A	Maximum Rise of 30°C @ 5A	100 mA or 50 VDC	100 mA or 50 VDC
1,000 Megohms	1,000 Megohms	1,000 Megohms	1,000 Megohms
Min.: 500 VAC	Min.: 500 VAC	Min.: 500 VAC	Min.: 500 VDC
Max.: 5.0 pF	Max.: 5.0 pF	Max.: 5.0 pF	Max.: 5.0 pF
< 1 microsecond	< 1 microsecond	< 1 microsecond	< 1 microsecond
< 1 microsecond	< 1 microsecond	< 1 microsecond	< 1 microsecond
Slide (Top Actuated)	Slide (Top Actuated)	Slide (Top Actuated)	Slide (Top Actuated)
SPST	SPST; SPDT; 4PST; DPST; DPDT	SPST	SPST
.100 (2.54)	.100 (2.54)	.100 (2.54)	.100 (2.54)
"A" Dim (See Table Below)	"A" Dim (See Table Below)	"A" Dim (See Table Below)	"A" Dim (See Table Below)
.385 (9.78)	.385 (9.78)	.385 (9.78)	.263 (6.68)
.300 (7.62)	.300 (7.62)	.300 (7.62)	.148 (3.76)
Gold/Tin	Gold/Tin	Tin/Tin	(209)-Gold/Tin (210)-Gold Flash/Tin
-55° to +85°C	-55° to +85°C	-55° to +85°C	-40° to +85°C
Available	Available	Available	Standard
---	Available	---	---
---	Available - Contact CTS	Available - Contact CTS	Standard
Since June 2006	Since June 2006	Since June 2006	Since June 2006

STANDARD PART NUMBERS FOR 205 / 206

"A" Overall Dimension	Number of Switch Sections	Actuation	Part Number	Both Bottom & Top Sealed	Low Profile Both Bottom & Top Sealed	Right Angle Mount Sealed Bottom & Top
.156 (3.96)	1	SPST	206-1	206-1ST	206-1LPST	---
.286 (7.26)	2	SPST	205/206-2	205/206-2ST	206-2LPST	206-2RAST
.386 (9.80)	3	SPST	205/206-3	205/206-3ST	206-3LPST	206-3RAST
.486 (12.34)	4	SPST	205/206-4	205/206-4ST	206-4LPST	206-4RAST
.586 (14.88)	5	SPST	205/206-5	205/206-5ST	206-5LPST	206-5RAST
.686 (17.42)	6	SPST	205/206-6	205/206-6ST	206-6LPST	206-6RAST
.786 (19.96)	7	SPST	205/206-7	205/206-7ST	206-7LPST	206-7RAST
.886 (22.50)	8	SPST	205/206-8	205/206-8ST	206-8LPST	206-8RAST
.986 (25.04)	9	SPST	205/206-9	205/206-9ST	206-9LPST	206-9RAST
1.086 (27.58)	10	SPST	205/206-10	205/206-10ST	206-10LPST	206-10RAST
1.286 (32.66)	12	SPST	205/206-12	205/206-12ST	206-12LPST	206-12RAST
.286 (7.26)	1	SPDT	206-121	206-121ST	---	206-121RAST
.486 (12.34)	2	SPDT	206-122	206-122ST	---	206-122RAST
.686 (17.42)	3	SPDT	206-123	206-123ST	---	206-123RAST
.886 (22.50)	4	SPDT	206-124	206-124ST	---	206-124RAST
1.086 (27.58)	5	SPDT	206-125	206-125ST	---	206-125RAST
1.286 (32.66)	6	SPDT	206-126	206-126ST	---	206-126RAST
.286 (7.26)	1	DPST	206-211	206-211ST	---	206-211RAST
.486 (12.34)	2	DPST	206-212	206-212ST	---	206-212RAST
.686 (17.42)	3	DPST	206-213	206-213ST	---	206-213RAST
.886 (22.50)	4	DPST	206-214	206-214ST	---	206-214RAST
1.086 (27.58)	5	DPST	206-215	206-215ST	---	206-215RAST
1.286 (32.66)	6	DPST	206-216	206-216ST	---	206-216RAST
.486 (12.34)	1	DPDT	206-221	206-221ST	---	206-221RAST
.886 (22.50)	2	DPDT	206-222	206-222ST	---	206-222RAST
1.286 (32.66)	3	DPDT	206-223	206-223ST	---	206-223RAST
.486 (12.34)	1	4PST	206-411	206-411ST	---	206-411RAST
.886 (22.50)	2	4PST	206-412	206-412ST	---	206-412RAST
1.286 (32.66)	3	4PST	206-413	206-413ST	---	206-413RAST

STANDARD PART NUMBERS FOR 208

"A" Overall Dimension	No. of Switch Sections	Part No.	Both Bottom & Top Sealed
.156 (3.96)	1	208-1	208-1ST
.286 (7.26)	2	208-2	208-2ST
.386 (9.80)	3	208-3	208-3ST
.486 (12.34)	4	208-4	208-4ST
.586 (14.88)	5	208-5	208-5ST
.686 (17.42)	6	208-6	208-6ST
.786 (19.96)	7	208-7	208-7ST
.886 (22.50)	8	208-8	208-8ST
.986 (25.04)	9	208-9	208-9ST
1.086 (27.58)	10	208-10	208-10ST
1.286 (7.26)	11	208-12	208-12ST

STANDARD PART NUMBERS FOR 209/210

"A" Overall Dimension	No. of Switch Sections	Low Profile* Both Bottom & Top Sealed
.258 (7.26)	2	209/210-2LPST
.358 (9.80)	3	209/210-3LPST
.458 (12.34)	4	209/210-4LPST
.558 (14.88)	5	209/210-5LPST
.658 (17.42)	6	209/210-6LPST

* For Medium Height Actuators Replace "LP" with "M"
EXAMPLE: 209-2MST