

### General Description

The UD2410 is the highest performance trench N-ch MOSFETs with extreme high cell density , which provide excellent RDSON and gate charge for most of the small power switching and load switch applications.

The UD2410 meet the RoHS and Green Product requirement with full function reliability approved.

### Features

- Advanced high cell density Trench technology
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- Green Device Available


### Product Summary

<b>BV<sub>DSS</sub></b>	<b>R<sub>D(on)</sub></b>	<b>ID</b>
20V	25mΩ	22A

### Applications

- High Frequency Point-of-Load Synchronous Small power switching for MB/NB/UMPC/VGA
- Networking DC-DC Power System
- Load Switch

### TO-252 Pin Configuration



### Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V <sub>DS</sub>	Drain-Source Voltage	20	V
V <sub>GS</sub>	Gate-Source Voltage	±12	V
I <sub>D</sub> @T <sub>C</sub> =25°C	Continuous Drain Current, V <sub>GS</sub> @ 4.5V <sup>1</sup>	22	A
I <sub>D</sub> @T <sub>C</sub> =100°C	Continuous Drain Current, V <sub>GS</sub> @ 4.5V <sup>1</sup>	14.7	A
I <sub>D</sub> @T <sub>A</sub> =25°C	Continuous Drain Current, V <sub>GS</sub> @ 4.5V <sup>1</sup>	7.2	A
I <sub>D</sub> @T <sub>A</sub> =70°C	Continuous Drain Current, V <sub>GS</sub> @ 4.5V <sup>1</sup>	5.8	A
I <sub>DM</sub>	Pulsed Drain Current <sup>2</sup>	50	A
P <sub>D</sub> @T <sub>C</sub> =25°C	Total Power Dissipation <sup>3</sup>	21	W
P <sub>D</sub> @T <sub>A</sub> =25°C	Total Power Dissipation <sup>3</sup>	2	W
T <sub>STG</sub>	Storage Temperature Range	-55 to 150	°C
T <sub>J</sub>	Operating Junction Temperature Range	-55 to 150	°C

### Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
R <sub>θJA</sub>	Thermal Resistance Junction-ambient <sup>1</sup>	---	62	°C/W
R <sub>θJC</sub>	Thermal Resistance Junction-Case <sup>1</sup>	---	6	°C/W

**N-Ch 20V Fast Switching MOSFETs**
**Electrical Characteristics ( $T_J=25^\circ\text{C}$ , unless otherwise noted)**







Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0\text{V}$ , $I_D=250\mu\text{A}$	20	---	---	V
$\Delta BV_{DSS}/\Delta T_J$	BVDSS Temperature Coefficient	Reference to $25^\circ\text{C}$ , $I_D=1\text{mA}$	---	0.018	---	$\text{V}/^\circ\text{C}$
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance <sup>2</sup>	$V_{GS}=4.5\text{V}$ , $I_D=15\text{A}$	---	20	25	$\text{m}\Omega$
		$V_{GS}=2.5\text{V}$ , $I_D=10\text{A}$	---	27	34	
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{GS}=V_{DS}$ , $I_D=250\mu\text{A}$	0.5	0.7	1.2	V
$\Delta V_{GS(\text{th})}$	$V_{GS(\text{th})}$ Temperature Coefficient		---	-3.1	---	$\text{mV}/^\circ\text{C}$
$I_{DSS}$	Drain-Source Leakage Current	$V_{DS}=16\text{V}$ , $V_{GS}=0\text{V}$ , $T_J=25^\circ\text{C}$	---	---	1	$\mu\text{A}$
		$V_{DS}=16\text{V}$ , $V_{GS}=0\text{V}$ , $T_J=55^\circ\text{C}$	---	---	5	
$I_{GSS}$	Gate-Source Leakage Current	$V_{GS}=\pm 12\text{V}$ , $V_{DS}=0\text{V}$	---	---	$\pm 100$	nA
$g_{fs}$	Forward Transconductance	$V_{DS}=5\text{V}$ , $I_D=15\text{A}$	---	27.3	---	S
$R_g$	Gate Resistance	$V_{DS}=0\text{V}$ , $V_{GS}=0\text{V}$ , $f=1\text{MHz}$	---	1.5	3	$\Omega$
$Q_g$	Total Gate Charge (4.5V)	$V_{DS}=15\text{V}$ , $V_{GS}=4.5\text{V}$ , $I_D=15\text{A}$	---	9.4	13.2	nC
$Q_{gs}$	Gate-Source Charge		---	1.57	2.2	
$Q_{gd}$	Gate-Drain Charge		---	2.7	3.8	
$T_{d(on)}$	Turn-On Delay Time	$V_{DD}=10\text{V}$ , $V_{GS}=4.5\text{V}$ , $R_G=3.3\Omega$	---	4.4	8.8	ns
$T_r$	Rise Time		---	29	52	
$T_{d(off)}$	Turn-Off Delay Time		---	22	44	
$T_f$	Fall Time		---	8.4	16.8	
$C_{iss}$	Input Capacitance	$V_{DS}=15\text{V}$ , $V_{GS}=0\text{V}$ , $f=1\text{MHz}$	---	635	889	pF
$C_{oss}$	Output Capacitance		---	70	98	
$C_{rss}$	Reverse Transfer Capacitance		---	63	88	






**Diode Characteristics**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$I_s$	Continuous Source Current <sup>1,4</sup>	$V_G=V_D=0\text{V}$ , Force Current	---	---	22	A
$I_{SM}$	Pulsed Source Current <sup>2,4</sup>		---	---	50	A
$V_{SD}$	Diode Forward Voltage <sup>2</sup>	$V_{GS}=0\text{V}$ , $I_s=1\text{A}$ , $T_J=25^\circ\text{C}$	---	---	1.2	V
$t_{rr}$	Reverse Recovery Time	$IF=15\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$ , $T_J=25^\circ\text{C}$	---	4.6	---	nS
$Q_{rr}$	Reverse Recovery Charge		---	0.57	---	nC

Note :

- 1.The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width  $\leq 300\mu\text{s}$  , duty cycle  $\leq 2\%$
- 3.The power dissipation is limited by  $150^\circ\text{C}$  junction temperature
- 4.The data is theoretically the same as  $I_D$  and  $I_{DM}$  , in real applications , should be limited by total power dissipation.

**N-Ch 20V Fast Switching MOSFETs**
**Typical Characteristics**

**Fig.1 Typical Output Characteristics**

**Fig.2 On-Resistance vs. Gate-Source**

**Fig.3 Forward Characteristics Of Reverse**

**Fig.4 Gate-Charge Characteristics**

**Fig.5 Normalized  $V_{GS(th)}$  vs.  $T_J$** 

**Fig.6 Normalized  $R_{DS(on)}$  vs.  $T_J$**

**N-Ch 20V Fast Switching MOSFETs**

**Fig.7 Capacitance**

**Fig.8 Safe Operating Area**

**Fig.9 Normalized Maximum Transient Thermal Impedance**

**Fig.10 Switching Time Waveform**

**Fig.11 Gate Charge Waveform**