



SPECIFICATIONS

FREQUENCY RANGE: 2.6–5.2 GHz
 COUPLING (INCLUDES FREQUENCY SENSITIVITY): 30 ± 1.0 dB
 FREQUENCY SENSITIVITY: ± 0.75 dB
 INSERTION LOSS: 0.2 dB MAX
 DIRECTIVITY: 18 dB MIN
 VSWR, PRIMARY LINE: 1.20 MAX
 600 WATTS CW, 10K PEAK
 INPUT & OUTPUT CONNECTORS ARE "N" FEMALE
 COUPLED PORT IS SMA FEMALE



PASTERNAK ENTERPRISES, INC.

P.O. BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE2229-30

DES. HIGH POWER DIRECTIONAL COUPLER
 FREQUENCY RANGE: 2.6-5.2 GHz

REV. A **FSCM NO. 53919**

CAD FILE 092908

SCALE N/A

SIZE A 147

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.