

# SMA Male to SSMB Jack Adapter



# **TECHNICAL DATA SHEET**

PE9401

## **SMA Male to SSMB Jack Adapter**

## Configuration

Connector 1SMA MaleImpedance 150 OhmsConnector 2SSMB JackImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

## **Mechanical Specifications**

#### Size

Length, in [mm] 0.769 [19.53] Width/Dia., in [mm] 0.312 [7.92]

#### **Connector 1**

Type SMA Male Inner Conductor Material and Plating Gold Coupling Nut Material and Plating Brass, Nickel Hex Size, in. 5/16

Torque, in-lbs [Nm] 5 [0.57]
Body Material and Plating Brass, Nickel Dielectric Type PTFE

#### Connector 2

Type SSMB Jack
Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

# Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

# **Plotted and Other Data**

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-male-ssmb-jack-straight-adapter-pe9401-p.aspx

SMA Male to SSMB Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# **PE9401 CAD Drawing** SMA Male to SSMB Jack Adapter

