

# SC Male to SC Male Adapter



## TECHNICAL DATA SHEET

PE9403

### **SC Male to SC Male Adapter**

#### Configuration

Connector 1SC MaleImpedance 150 OhmsConnector 2SC MaleImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

### **Mechanical Specifications**

Temperature

Operating Range,deg C -65 to +165

Size

 Length, in [mm]
 1.663 [42.24]

 Width/Dia., in [mm]
 0.8 [20.32]

#### **Connector 1**

Type SC Male
Inner Conductor Material and Plating Silver
Coupling Nut Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

#### Connector 2

Type SC Male
Inner Conductor Material and Plating Silver
Coupling Nut Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

## Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sc-male-sc-male-straight-adapter-pe9403-p.aspx

SC Male to SC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



