



PASTERNAK
PE2237-10

SPECIFICATIONS

IMPEDANCE	50 OHMS
FREQUENCY RANGE	800-2500 MHz
COUPLING	10dB±0.8 dB MAX.
FREQUENCY SENSITIVITY	±0.7 dB MAX.
INSERTION LOSS	1.2 dB MAX.
DIRECTIVITY	20dB MIN.
VSWR	1.25:1 MAX.
POWER INPUT	60 WATTS
RF CONNECTORS	N FEMALE
OPERATING TEMPERATURE	-20° TO +70°C



PASTERNAK ENTERPRISES, INC.

P.O BOX 16759, IRVINE, CA 92623
PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE2237-10

DES.

N FEMALE DIRECTIONAL COUPLER, 800-2500
MHZ, 10 DB

REV. -

FSCM NO. 53919

CAD FILE 070809

SCALE N/A

SIZE A

127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.