# BGA Heat Sink (High Aspect Ratio Ext.) **Custom Pin Fin**



ATS Part#:

Description:

Heat Sink Type: Heat Sink Attachment:

**Custom Pin Fin** 

ATS014014014-PF-3M

14.00 x 14.00 x 14.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin

N/A Equivalent Part Number: N/A

\*Image above is for illustration purpose only.

### **Features & Benefits**

- · High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance .
- . Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

## **Thermal Performance**

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 14.76 °C/W          | 11.9 °C/W           | 10.4 °C/W           | 9.4 °C/W            | 8.6 °C/W            | 8 °C/W              | 7.6 °C/W            |
|                    | Ducted Flow   | 10.1                | 8.6                 | 7.6                 | 7                   | 6.5                 | 6.1                 | 5.7                 |

# **Product Detail**

| Schematic Image                               | Dimension A   | Dimension B   | Dimension C           | Dimension D   | ТІМ                | Finish         |
|---|---|---|-----------------------|---|--------------------|----------------|
| alta  | 14.00 mm  | 14.00 mm  | 14.00 mm              | 14 mm   | N/A                | BLACK-ANODIZED |
| Image above is for illustration purpose only. | <ul> <li>Dimensior</li> <li>Dimensior</li> <li>Thermal p<br/>application</li> <li>ATS reserver</li> <li>performan</li> <li>ATS certification</li> </ul> | D is fin tip to fin tip<br>performance data are<br>n.<br>ves the right to upd<br>ice.<br>ies that this heat sin | neight from the botto | nce only. Actual perf<br>ducts without notice<br>-6 and REACH com | formanc<br>to impr | e may vary by  |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA